

Team XF 29 Factory Racing

MATTE CARBON/CHROME/TEAM RED



GRAPHIC SIMULATION ONLY / REAL PICTURE 300N

MTB FULL-SUSPENSION / TEAM

BENEFITS

- Feather-light high modulus carbon frame with only 1717 g
- Wireless components from SRAM XX1 Eagle AXS
- Lightweight carbon wheelset DT Swiss XRC1501 SPLINE BOOST for a fast ride and dynamic acceleration
- Smart details: BlockLock headset, two bottle cages mounts, Smart Link suspension

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74.9	74.7	74.6	74.5
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
REACH (MM)	427	449	465	482
STACK HEIGHT (MM)	579	589	597	607
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	68	68	68	68
CHAINSTAY LENGTH (MM)	430	430	430	430
BB DROP (MM)	40	40	40	40
WHEELBASE (MM)	1124	1149	1169	1189
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	70	80	90
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	390/125	390/125	440/150	440/150

SPECIFICATION

FRAMESET

FRAME	Carbon MTB Race Pro SU-01, Advanced Race Geometry, Travel 100 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-220 R4, ZS44/28.6 ZS56/40, BlockLock 150°
REAR SHOCK	Bushing body for RockShox
COLOUR	MATTE CARBON/CHROME/TEAM RED
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SRAM SX Eagle Trigger Shifter, 12-speed
BOTTOM BRACKET	SRAM DUB PF MTB92, shell 41x92 mm

COMPONENTS

HANDLEBAR	ONE1 Carbon, Horizon Bow, 9° backsweep, 7mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO XTR BL-M9100/BR-M9100, hydraulic disc brake, SHIMANO XTR BL-M9100/BR-M9110, hydraulic disc brake
SEAT POST	Sram Reverb AXS dropper post, 30.9mm

WHEELS

TIRES	Schwalbe Racing Ray Evo LiteSkin TL Easy SuperRace, 29x2.25", ADDIX Speed/ Schwalbe Racing Ralph Evo LiteSkin TL Easy SuperRace, 29x2.25", ADDIX Speed
WHEELSET	DT Swiss XRC 1501 Spline DB30; 15x110mm, CENTER LOCK, Tubeless

Team XF 29 Issue R

MATTE CARBON/CHROME/TEAM RED



MTB FULL-SUSPENSION / TEAM

BENEFITS

- New geometry and kinematics for responsive suspension and 100 mm travel
- High modulus carbon material with frame weight only 1717 g
- Top racing components XTR/Race Face/DT Swiss
- Ready to race Tubeless wheelset
- Composite accessories ONE1

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74.9	74.7	74.6	74.5
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
REACH (MM)	427	449	465	482
STACK HEIGHT (MM)	579	589	597	607
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	68	68	68	68
CHAINSTAY LENGTH (MM)	430	430	430	430
BB DROP (MM)	40	40	40	40
WHEELBASE (MM)	1124	1149	1169	1189
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	70	80	90
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	390/125	390/125	440/150	440/150

SPECIFICATION

FRAMESET

FRAME	Carbon MTB Race Pro SU-01, Advanced Race Geometry, Travel 100 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-220 R4, ZS44/28.6 ZS56/40, BlockLock 150°
FORK	DT Swiss F232 ONE O.D.L., Tapered, 15x110mm axle, remote Lockout, 110mm travel
REAR SHOCK	DT Swiss R 232 ONE, remote Lockout, size 190x45mm, Bushing body for DT Swiss
COLOUR SIZES	MATTE CARBON/CHROME/TEAM RED 15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO XTR SL-M9100 Rapidfire Plus, 12-speed
REAR DERAILLEUR	SHIMANO XTR RD-M9100 Shadow Plus
CRANKSET	Race Face NEXT SL, 34T
BOTTOM BRACKET CHAIN	Race Face BB92, PressFit, shell 41x92mm SHIMANO CN-M8100

COMPONENTS

HANDLEBAR	ONE1 Carbon, Horizon Bow, 9° backsweep, 7mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO XTR BL-M9100/BR-M9100, hydraulic disc brake, SHIMANO XTR BL-M9100/BR-M9110, hydraulic disc brake
SEAT POST	Crankbrothers Highline 7 dropper post, 30.9mm
WHEELS	
TIRES	Schwalbe Racing Ray Evo LiteSkin TL Easy SuperRace, 29x2.25", ADDIX Speed/ Schwalbe Racing Ralph Evo LiteSkin TL Easy SuperRace, 29x2.25", ADDIX Speed
WHEELSET	DT Swiss XRC 1501 Spline DB30; 12x148mm, Shimano MICRO SPLINE 12 speed, CENTER LOCK, Tubeless, DT Swiss XRC 1501 Spline DB30; 15x110mm, CENTER LOCK, Tubeless

Team XF 29 Issue

MATTE CARBON/CHROME/TEAM RED



MTB FULL-SUSPENSION / TEAM

BENEFITS

- New kinematics and smooth, responsive DT Swiss suspension with a travel of 100 mm
- High Modulus carbon material reduces the frame weight to only 1,717 g
- Block Lock headset: frame protected against damage by handlebars
- Dropper post for better control in rough terrain
- Lightweight DT Swiss XM 1700 Spline DB30 wheelset: a fast ride and dynamic acceleration
- Two bottle cages option
- Remote lockout

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74.9	74.7	74.6	74.5
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
REACH (MM)	427	449	465	482
STACK HEIGHT (MM)	579	589	597	607
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	68	68	68	68
CHAINSTAY LENGTH (MM)	430	430	430	430
BB DROP (MM)	40	40	40	40
WHEELBASE (MM)	1124	1149	1169	1189
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	70	80	90
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	390/125	390/125	440/150	440/150

SPECIFICATION

FRAMESET

FRAME Carbon MTB Race Pro SU-01, Advanced Race Geometry, Travel 100 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 12x148 mm, Inner cable routing, Dropped seat post ready

HEAD SET ACROS AZX-220 R4, ZS44/28.6 | ZS56/40, BlockLock 150°

FORK DT Swiss F232 ONE O.D.L., Tapered, 15x110mm axle, remote Lockout, 110mm travel

REAR SHOCK Bushing body for DT Swiss, DT Swiss R 232 ONE, remote Lockout, size 190x45mm

COLOUR SIZES MATTE CARBON/CHROME/TEAM RED
15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER SHIMANO XTR SL-M9100 Rapidfire Plus, 12-speed

REAR DERAILLEUR SHIMANO XTR RD-M9100 Shadow Plus

CRANKSET Race Face NEXT SL, 34T

CASSETTE SHIMANO CS-M8100-12, 10-51T

BOTTOM BRACKET Race Face BB92, PressFit, shell 41x92mm

CHAIN SHIMANO CN-M8100

COMPONENTS

HANDLEBAR ONE1 Carbon, Horizon Bow, 9° backsweep, 7mm rise, 760mm, 31.8mm

STEM ONE1 Race Alloy, 31.8mm, -7°

GRIPS ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On

BRAKES SHIMANO XTR BL-M9100/BR-M9100, hydraulic disc brake, SHIMANO XTR BL-M9100/BR-M9110, hydraulic disc brake

SEAT POST Crankbrothers Highline 7 dropper post, 30.9mm

WHEELS

TIRES Schwalbe Racing Ralph SnakeSkin TL Easy, 29x2.25", ADDIX Speed/ Schwalbe Racing Ray SnakeSkin TL Easy, 29x2.25", ADDIX Speedgrip

WHEELSET DT Swiss XM 1700 Spline DB30; 12x148mm, CENTER LOCK, Tubeless, DT Swiss XM 1700 Spline DB30; 15x110mm, CENTER LOCK, Tubeless

Team XF 29 Elite

MATTE CARBON/CHROME/TEAM RED



MTB FULL-SUSPENSION / TEAM

BENEFITS

- New kinematics and smooth, responsive DT Swiss suspension with a travel of 110/100mm (F/R)
- High Modulus carbon material reduces the frame weight to only 1,717 g
- Block Lock headset: frame protected against damage by handlebars
- Dropper post for better control in rough terrain
- Lightweight DT Swiss XM 1700 Spline DB30 wheelset: a fast ride and dynamic acceleration
- Two bottle cages option
- Remote lockout

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74.9	74.7	74.6	74.5
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
REACH (MM)	427	449	465	482
STACK HEIGHT (MM)	579	589	597	607
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	68	68	68	68
CHAINSTAY LENGTH (MM)	430	430	430	430
BB DROP (MM)	40	40	40	40
WHEELBASE (MM)	1124	1149	1169	1189
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	70	80	90
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	390/125	390/125	440/150	440/150

SPECIFICATION

FRAMESET

FRAME	Carbon MTB Race Pro SU-01, Advanced Race Geometry, Travel 100 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-220 R4, ZS44/28.6 ZS56/40, BlockLock 150°
REAR SHOCK	DT Swiss R 232 ONE, remote Lockout, size 190x45mm, Bushing body for DT Swiss
COLOUR	MATTE CARBON/CHROME/TEAM RED
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE XT SL-M8100 RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100 Shadow Plus
CRANKSET	SHIMANO XT FC-M8120 Hollowtech II, 36T
CASSETTE	SHIMANO CS-M8100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO XT BL-M8100/BR-M8110, hydraulic disc brake, SHIMANO XT BL-M8100/BR-M8100, hydraulic disc brake
SEAT POST	ONE1 Alloy, MT171, dropper post, 30.9mm

WHEELS

TIRES	Schwalbe Racing Ray Performance TL-Ready, 29x2.25", ADDIX/ Schwalbe Racing Ralph Performance TL-Ready, 29x2.25", ADDIX Speedgrip
WHEELSET	DT Swiss XM 1700 Spline DB30; 12x148mm, CENTER LOCK, Tubeless, DT Swiss XM 1700 Spline DB30; 15x110mm, CENTER LOCK, Tubeless

XF 979 RC

GLOSS DARK RED/HOLOGRAM CHROME



MTB FULL-SUSPENSION / RACE

BENEFITS

- New kinematics and smooth, responsive DT Swiss suspension with a travel of 110/100 mm
- Lightweight and strong Rock Shox SID fork with a travel of 110 mm and complete lockout option
- Block Lock headset: frame protected against damage by handlebars
- Dropper post for better control in rough terrain
- Lightweight DT Swiss M 1900 SPLINE BOOST wheelset: a fast ride and dynamic acceleration
- Two bottle cages optional
- Remote lockout

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74.9	74.7	74.6	74.5
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
REACH (MM)	427	449	465	482
STACK HEIGHT (MM)	579	589	597	607
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	68	68	68	68
CHAINSTAY LENGTH (MM)	430	430	430	430
BB DROP (MM)	40	40	40	40
WHEELBASE (MM)	1124	1149	1169	1189
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	70	80	90
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	390/125	390/125	440/150	440/150

SPECIFICATION

FRAMESET

FRAME	Carbon MTB Race Pro SU-01, Advanced Race Geometry, Travel 100 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-220 R4, ZS44/28.6 ZS56/40, BlockLock 150°
REAR SHOCK	DT Swiss R 232 ONE, remote Lockout, size 190x45mm, Bushing body for DT Swiss
COLOUR	GLOSS DARK RED/HOLOGRAM CHROME
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO SLX SL-M7100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100 Shadow Plus
CRANKSET	SHIMANO XT FC-M8120 Hollowtech II, 36T
CASSETTE	SHIMANO CS-M7100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO XT BL-M8100/BR-M8100, hydraulic disc brake, SHIMANO XT BL-M8100/BR-M8110, hydraulic disc brake
SEAT POST	ONE1 Alloy, MT171, dropper post, 30.9mm
WHEELS	
TIRES	Schwalbe Racing Ray Performance TL-Ready, 29x2.25", ADDIX/ Schwalbe Racing Ralph Performance TL-Ready, 29x2.25", ADDIX Speedgrip

XF 929 RC

GLOSS WHITE/HOLOGRAM BLACK



MTB FULL-SUSPENSION / RACE

BENEFITS

- New kinematics and smooth, responsive DT Swiss suspension with a travel of 100 mm
- Block Lock headset: frame protected against damage by handlebars
- Geometry for cross country speed and trail fun
- Two bottle cages option
- Remote fork and damper lockout on a single lever, with complete lockout position

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74.9	74.7	74.6	74.5
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
REACH (MM)	427	449	465	482
STACK HEIGHT (MM)	579	589	597	607
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	68	68	68	68
CHAINSTAY LENGTH (MM)	430	430	430	430
BB DROP (MM)	40	40	40	40
WHEELBASE (MM)	1124	1149	1169	1189
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Carbon MTB Race Pro SU-01, Advanced Race Geometry, Travel 100 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-220 R4, ZS44/28.6 ZS56/40, BlockLock 150°
FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
REAR SHOCK	DT Swiss R 232 ONE, remote Lockout, size 190x45mm, Bushing body for DT Swiss
COLOUR SIZES	GLOSS WHITE/HOLOGRAM BLACK 15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100 Shadow Plus
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
BOTTOM BRACKET CHAIN	BB-MT500PA PressFit, shell 41x92mm SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM GRIPS	ONE1 Race Alloy, 31.8mm, -7° ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SEAT POST	ONE1 Race Alloy, SP 218, 30.9mm
WHEELS	
FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J30D, 32H
TIRES SPOKES	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX Sapim Leader, Stainless Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

XF 919 RC

GLOSS DARK RED/HOLOGRAM CHROME



MTB FULL-SUSPENSION / RACE

BENEFITS

- New frame kinematics and smooth, responsive 100 mm travel
- Geometry for cross country speed and trail fun
- Two bottle cages option
- Remote fork and damper lockout on a single lever
- Wider Schwalbe Racing Ralph tires for superb control

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	75	75	75	75
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
REACH (MM)	422	444	464	480
STACK HEIGHT (MM)	587	596	596	606
HEAD TUBE LENGTH (MM)	90	100	100	110
HEAD TUBE ANGLE (DEGREE)	67	67	67	67
CHAINSTAY LENGTH (MM)	432	432	432	432
BB DROP (MM)	30	30	30	30
WHEELBASE (MM)	1147	1173	1193	1213
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite MTB Trail SU-02, Advanced Geometry, Travel 130 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-212 R5,ZS44/28.6 ZS56/40
FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
REAR SHOCK	DT Swiss R 232 ONE, remote Lockout, size 190x45mm, Bushing body for DT Swiss
COLOUR	GLOSS DARK RED/HOLOGRAM CHROME
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100 Shadow Plus
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SEAT POST	ONE1 Race Alloy, SP 218, 30.9mm
WHEELS	
FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J30D, 32H
TIRES	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX Sapim Leader, Stainless Black
SPOKES	

XF 999 TR

MATTE BLACK/OLIVE METALLIC



MTB FULL-SUSPENSION / TRAIL

BENEFITS

- New kinematics, 130 mm travel, and responsive Rock Shox suspension
- Integrated down tube and chainstay protectors
- Block Lock headset: frame protected against damage by handlebars
- Dropper post for better control in rough terrain, 4-piston brakes
- The frame allows attaching two bottle cages
- Schwalbe Nobby Nic 2,35" tubeless-ready tires: a superior grip and few flats
- DT Swiss M1900 SPLINE wheelset with a 30 mm rim for a better tire fit and traction

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
REACH (MM)	407	429	449	465
STACK HEIGHT (MM)	589	600	608	617
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	66	66	66	66
CHAINSTAY LENGTH (MM)	430	430	430	430
BB DROP (MM)	29	29	29	29
WHEELBASE (MM)	1154	1180	1200	1220
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	70	70	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	390/125	390/125	440/150	440/150

SPECIFICATION

FRAMESET

FRAME	Carbon MTB Race Pro SU-01, Advanced Race Geometry, Travel 130 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-220 R4, ZS44/28.6 ZS56/40, BlockLock 150°
FORK	RockShox Revelation RC, Tapered, DebonAir, 15x110mm axle, 140mm travel
REAR SHOCK	Bushing body for RockShox
COLOUR	MATTE BLACK/OLIVE METALLIC
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE XT SL-M8100 RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100 Shadow Plus
CRANKSET	SHIMANO XT FC-M8120 Hollowtech II, 34T
CASSETTE	SHIMANO CS-M8100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-3712BT, 9° backsweep, 12mm rise, 760mm, 35mm
STEM	ONE1 TDS-D622 Alloy, 35mm
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO BL-M8100/BR-M8120, hydraulic disc brake
SEAT POST	ONE1 Alloy, MT171, dropper post, 30.9mm

XF 979 TR

MATTE TROOPER GREEN/BLACK



MTB FULL-SUSPENSION / TRAIL

BENEFITS

- New kinematics, 140/130 mm travel, and responsive Rock Shox suspension
- Integrated down tube and chainstay protectors
- BlockLock headset: frame protected against damage by handlebars
- Dropper post and 4-piston brakes for better control in rough terrain
- Two bottle cages option
- Schwalbe Nobby Nic 2,35" tubeless-ready tires: a superior grip and few flats
- DT Swiss M1900 SPLINE wheelset with a 30 mm rim for a better tire fit and traction

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
REACH (MM)	407	429	449	465
STACK HEIGHT (MM)	589	600	608	617
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	66	66	66	66
CHAINSTAY LENGTH (MM)	430	430	430	430
BB DROP (MM)	29	29	29	29
WHEELBASE (MM)	1154	1180	1200	1220
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	70	70	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	390/125	390/125	440/150	440/150

SPECIFICATION

FRAMESET

FRAME	Carbon MTB Race Pro SU-01, Advanced Race Geometry, Travel 130 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-220 R4, ZS44/28.6 ZS56/40, BlockLock 150°
FORK	RockShox Revelation RC, Tapered, DebonAir, 15x110mm axle, 140mm travel
REAR SHOCK	Bushing body for RockShox
COLOUR	MATTE TROOPER GREEN/BLACK
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO SLX SL-M7100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100 Shadow Plus
CRANKSET	SHIMANO SLX FC-M7120 Hollowtech II, 34T
CASSETTE	SHIMANO CS-M7100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-3712BT, 9° backsweep, 12mm rise, 760mm, 35mm
STEM	ONE1 TDS-D622 Alloy, 35mm
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO BL-M6100/BR-M6120, hydraulic disc brake
SEAT POST	ONE1 Alloy, MT171, dropper post, 30.9mm
WHEELS	
TIRES	Schwalbe Nobby Nic Performance, 29x2.35", ADDIX

XF 939 TR

MATTE OLIVE METALLIC/BLACK



MTB FULL-SUSPENSION / TRAIL

BENEFITS

- New kinematics, 130 mm travel, and Rock Shox fork
- Integrated down tube and chainstay protectors
- Dropper post travel 125/150 mm allows better control in rough terrain
- Two bottle cages option
- Schwalbe Nobby Nic 2,35" tubeless-ready tires: a superior grip and few flats
- DT Swiss M1900 SPLINE wheelset with a 30 mm rim for a better tire fit and traction

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
REACH (MM)	407	429	449	465
STACK HEIGHT (MM)	598	607	607	617
HEAD TUBE LENGTH (MM)	90	100	100	110
HEAD TUBE ANGLE (DEGREE)	66	66	66	66
CHAINSTAY LENGTH (MM)	432	432	432	432
BB DROP (MM)	25	25	25	25
WHEELBASE (MM)	1147	1173	1193	1213
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	40	50	50	50
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	390/125	390/125	440/150	440/150

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite MTB Trail SU-02, Advanced Geometry, Travel 130 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET FORK	ACROS AZX-212 R5,ZS44/28.6 ZS56/40 RockShox Revelation RC, Tapered, DebonAir, 15x110mm axle, 140mm travel
REAR SHOCK	Bushing body for RockShox, RockShox Monarch RT, external rebound, 2 position compression (Open/Pedal), size 190x51mm
COLOUR SIZES	MATTE OLIVE METALLIC/BLACK 15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO SLX SL-M7100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100 Shadow Plus
CRANKSET	SHIMANO SLX FC-M7120 Hollowtech II, 34T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
BOTTOM BRACKET CHAIN	BB-MT500PA PressFit, shell 41x92mm SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-3712BT, 9° backsweep, 12mm rise, 760mm, 35mm
STEM GRIPS	ONE1 TDS-D622 Alloy, 35mm ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M6100/BR-M6120, hydraulic disc brake
SEAT POST	ONE1 Alloy, MT171, dropper post, 30.9mm
WHEELS TIRES	Schwalbe Nobby Nic Performance, 29x2.35", ADDIX

XF 919 TR

MATTE TROOPER GREEN/BLACK



MTB FULL-SUSPENSION / TRAIL

BENEFITS

- New kinematics, 130 mm travel and Rock Shox fork
- Integrated down tube and chainstay protectors
- Size-related dropper post travel 125/150 mm for better control in rough terrain
- Two bottle cages option
- Schwalbe Nobby Nic 2,35" tubeless-ready tires: a superior grip and few flats
- 30 mm rim wheelsets allow better tire fit and traction

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	584	610	630	650
REACH (MM)	407	429	449	465
STACK HEIGHT (MM)	598	607	607	617
HEAD TUBE LENGTH (MM)	90	100	100	110
HEAD TUBE ANGLE (DEGREE)	66	66	66	66
CHAINSTAY LENGTH (MM)	432	432	432	432
BB DROP (MM)	25	25	25	25
WHEELBASE (MM)	1147	1173	1193	1213
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	40	50	50	50
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	390/125	390/125	440/150	440/150

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite MTB Trail SU-02, Advanced Geometry, Travel 130 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET FORK	ACROS AZX-212 R5,ZS44/28.6 ZS56/40 RockShox 35 Gold RL, Tapered, DebonAir, 15x110mm axle, 140mm travel
REAR SHOCK	Bushing body for RockShox, RockShox Monarch RT, external rebound, 2 position compression (Open/Pedal), size 190x51mm
COLOUR SIZES	MATTE TROOPER GREEN/BLACK 15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100 Shadow Plus
CRANKSET	SHIMANO FC-MT510, 32T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
BOTTOM BRACKET CHAIN	BB-MT500PA PressFit, shell 41x92mm SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-3712BT, 9° backsweep, 12mm rise, 760mm, 35mm
STEM GRIPS	ONE1 TDS-D622 Alloy, 35mm ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT420, hydraulic disc brake
SEAT POST	ONE1 Alloy, MT171, dropper post, 30.9mm
WHEELS	
FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J30D, 32H
TIRES	Schwalbe Nobby Nic Performance, 29x2.35", ADDIX Sapim Leader, Stainless Black
SPOKES	

Team 29 Elite

MATTE CARBON/CHROME/TEAM RED



MTB HARDTAIL / TEAM

BENEFITS

- Carbon MTB Race Pro High Modulus top stiffness frame, BOOST standard hubs, and inner routing
- Lightweight and strong Rock Shox SID fork with a travel of 100 mm and complete lockout option
- BlockLock headset: frame protected against damage by handlebars
- Shimano XT series groupset
- DT Swiss XR 1700 Spline DB25 tubeless wheelset
- ONE1 carbon seatpost

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	595	620	640	655
REACH (MM)	425	428	465	477
STACK HEIGHT (MM)	591	602	611	620
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	432	432	432	432
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1107	1133	1154	1169
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Carbon MTB Race Pro High Modulus, Advanced Race Geometry, Conical Head Tube, BB92, SH dropout, Thru Axle Boost 12x148mm, Inner cable routing
HEAD SET	ACROS AZX-220 R4, ZS44/28.6 ZS56/40, BlockLock 150°
FORK	RockShox SID SL Select RL R, Tapered, DebonAir, 15x110mm axle, 100mm travel
COLOUR	MATTE CARBON/CHROME/TEAM RED
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE XT SL-M8100 RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100 Shadow Plus
CRANKSET	SHIMANO XT FC-M8100 Hollowtech II, 36T
CASSETTE	SHIMANO CS-M8100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO XT BL-M8100/BR-M8100, hydraulic disc brake, SHIMANO XT BL-M8100/BR-M8110, hydraulic disc brake
SEAT POST	ONE1 Race Carbon, PMP12, 27.2mm

WHEELS

TIRES	Schwalbe Racing Ray Performance TL-Ready, 29x2.25", ADDIX/ Schwalbe Racing Ralph Performance TL-Ready, 29x2.25", ADDIX Speedgrip
WHEELSET	DT Swiss XR 1700 Spline DB25; 12x148mm, Shimano MICRO SPLINE 12 speed, CENTER LOCK, Tubeless, DT Swiss XR 1700 Spline DB25; 15x110mm, CENTER LOCK, Tubeless

XP 979

GLOSS DARK RED/HOLOGRAM CHROME



MTB HARDTAIL / RACE

BENEFITS

- Carbon MTB Race Pro Mid Modulus top stiffness and comfort frame, BOOST standard hubs, and inner routing
- Lightweight and strong complete lockout Rock Shox SID fork with a travel of 100 mm
- DT Swiss X1900 SPLINE BOOST Tubeless wheelset for a faster and more precise ride
- BlockLock headset: frame protected against damage by handlebars
- ONE1 carbon seatpost

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	595	620	640	655
REACH (MM)	425	428	465	477
STACK HEIGHT (MM)	591	602	611	620
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	432	432	432	432
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1107	1133	1154	1169
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus, Race Geometry, Tapered Head Tube, BB92, SR dropout, Boost Thru Axle 12x148 mm, Inner Cable Routing
HEAD SET	ACROS AZX-220 R4, ZS44/28.6 ZS56/40, BlockLock 150°
FORK	RockShox SID SL Select RL R, Tapered, DebonAir, 15x110mm axle, 100mm travel
COLOUR	GLOSS DARK RED/HOLOGRAM CHROME
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO SLX SL-M7100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100 Shadow Plus
CRANKSET	SHIMANO XT FC-M8100 Hollowtech II, 34T
CASSETTE	SHIMANO CS-M7100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO XT BL-M8100/BR-M8110, hydraulic disc brake, SHIMANO XT BL-M8100/BR-M8100, hydraulic disc brake
SEAT POST	ONE1 Race Carbon, PMP12, 27.2mm

WHEELS

TIRES	Schwalbe Racing Ray Performance TL-Ready, 29x2.25", ADDIX/ Schwalbe Racing Ralph Performance TL-Ready, 29x2.25", ADDIX Speedgrip
-------	--

XP 979

MATTE BLACK/HOLOGRAM CHROME



MTB HARDTAIL / RACE

BENEFITS

- Carbon MTB Race Pro Mid Modulus top stiffness and comfort frame, BOOST standard hubs, and inner routing
- Lightweight and strong complete lockout Rock Shox SID fork with a travel of 100 mm
- DT Swiss X1900 SPLINE BOOST Tubeless wheelset for a faster and more precise ride
- BlockLock headset: frame protected against damage by handlebars
- ONE1 carbon seatpost

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	595	620	640	655
REACH (MM)	425	428	465	477
STACK HEIGHT (MM)	591	602	611	620
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	432	432	432	432
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1107	1133	1154	1169
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus, Race Geometry, Tapered Head Tube, BB92, SR dropout, Boost Thru Axle 12x148 mm, Inner Cable Routing
HEAD SET	ACROS AZX-220 R4, ZS44/28.6 ZS56/40, BlockLock 150°
FORK	RockShox SID SL Select RL R, Tapered, DebonAir, 15x110mm axle, 100mm travel
COLOUR	MATTE BLACK/HOLOGRAM CHROME
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO SLX SL-M7100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100 Shadow Plus
CRANKSET	SHIMANO XT FC-M8100 Hollowtech II, 34T
CASSETTE	SHIMANO CS-M7100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO XT BL-M8100/BR-M8110, hydraulic disc brake, SHIMANO XT BL-M8100/BR-M8100, hydraulic disc brake
SEAT POST	ONE1 Race Carbon, PMP12, 27.2mm

WHEELS

TIRES	Schwalbe Racing Ray Performance TL-Ready, 29x2.25", ADDIX/ Schwalbe Racing Ralph Performance TL-Ready, 29x2.25", ADDIX Speedgrip
-------	--

XP 969

GLOSS GREY/CHROME/RED



MTB HARDTAIL / RACE

BENEFITS

- Carbon MTB Race Pro Mid Modulus top stiffness and comfort frame, BOOST standard hubs, and inner routing
- Lightweight and strong complete lockout Rock Shox SID fork with a travel of 100 mm
- DT Swiss X1900 SPLINE BOOST Tubeless wheelset for a faster and more precise ride
- BlockLock headset: frame protected against damage by handlebars
- ONE1 carbon seatpost

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	595	620	640	655
REACH (MM)	425	428	465	477
STACK HEIGHT (MM)	591	602	611	620
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	432	432	432	432
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1107	1133	1154	1169
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus, Race Geometry, Tapered Head Tube, BB92, SR dropout, Boost Thru Axle 12x148 mm, Inner Cable Routing
HEAD SET	ACROS AZX-220 R4, ZS44/28.6 ZS56/40, BlockLock 150°
FORK	RockShox SID SL Select RL R, Tapered, DebonAir, 15x110mm axle, 100mm travel
COLOUR	GLOSS GREY/CHROME/RED
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO SLX SL-M7100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100 Shadow Plus
CRANKSET	SHIMANO SLX FC-M7100 Hollowtech II, 34T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO BL-M6100/BR-M6100, hydraulic disc brake
SEAT POST	ONE1 Race Carbon, PMP12, 27.2mm

WHEELS

TIRES	Schwalbe Racing Ray Performance TL-Ready, 29x2.25", ADDIX/ Schwalbe Racing Ralph Performance TL-Ready, 29x2.25", ADDIX Speedgrip
-------	--

XP 969

MATTE BLACK/CHROME/TEAM RED



MTB HARDTAIL / RACE

BENEFITS

- Carbon MTB Race Pro Mid Modulus top stiffness and comfort frame, BOOST standard hubs, and inner routing
- Lightweight and strong complete lockout Rock Shox SID fork with a travel of 100 mm
- DT Swiss X1900 SPLINE BOOST Tubeless wheelset for a faster and more precise ride
- BlockLock headset: frame protected against damage by handlebars
- ONE1 carbon seatpost

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	595	620	640	655
REACH (MM)	425	428	465	477
STACK HEIGHT (MM)	591	602	611	620
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	432	432	432	432
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1107	1133	1154	1169
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus, Race Geometry, Tapered Head Tube, BB92, SR dropout, Boost Thru Axle 12x148 mm, Inner Cable Routing
HEAD SET	ACROS AZX-220 R4, ZS44/28.6 ZS56/40, BlockLock 150°
FORK	RockShox SID SL Select RL R, Tapered, DebonAir, 15x110mm axle, 100mm travel
COLOUR	MATTE BLACK/CHROME/TEAM RED
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO SLX SL-M7100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100 Shadow Plus
CRANKSET	SHIMANO SLX FC-M7100 Hollowtech II, 34T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO BL-M6100/BR-M6100, hydraulic disc brake
SEAT POST	ONE1 Race Carbon, PMP12, 27.2mm

WHEELS

TIRES	Schwalbe Racing Ray Performance TL-Ready, 29x2.25", ADDIX/ Schwalbe Racing Ralph Performance TL-Ready, 29x2.25", ADDIX Speedgrip
-------	--

XP 929

MATTE BLACK/WHITE



MTB HARDTAIL / RACE

BENEFITS

- Carbon MTB Race Pro Mid Modulus top stiffness and comfort frame, BOOST standard hubs, and inner routing
- Lightweight and strong complete lockout RockShox Recon Silver RL R fork with a travel of 100 mm
- BlockLock headset: frame protected against damage by handlebars
- Integrated guide to secure chain stability on the ring
- 1x12 Shimano drivetrain with a large range of gears to suit various terrain patterns

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	595	620	640	655
REACH (MM)	425	428	465	477
STACK HEIGHT (MM)	591	602	611	620
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	432	432	432	432
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1107	1133	1154	1169
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus, Race Geometry, Tapered Head Tube, BB92, SR dropout, Boost Thru Axle 12x148 mm, Inner Cable Routing
HEAD SET	ACROS AZX-220 R4, ZS44/28.6 ZS56/40, BlockLock 150°
FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
COLOUR	MATTE BLACK/WHITE
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100 Shadow Plus
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SEAT POST	ONE1 Race Alloy, SP 218, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	Sapim Laser, Stainless Black/ Sapim Laser/ Sapim Race, Stainless Black

XP 929

GLOSS WHITE/HOLOGRAM BLACK



MTB HARDTAIL / RACE

BENEFITS

- Carbon MTB Race Pro Mid Modulus top stiffness and comfort frame, BOOST standard hubs, and inner routing
- Lightweight and strong complete lockout RockShox Recon Silver RL R fork with a travel of 100 mm
- BlockLock headset: frame protected against damage by handlebars
- Integrated guide to secure chain stability on the ring
- 1x12 Shimano drivetrain with a large range of gears to suit various terrain patterns

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	595	620	640	655
REACH (MM)	425	428	465	477
STACK HEIGHT (MM)	591	602	611	620
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	432	432	432	432
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1107	1133	1154	1169
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Carbon MTB Race Pro Mid Modulus, Race Geometry, Tapered Head Tube, BB92, SR dropout, Boost Thru Axle 12x148 mm, Inner Cable Routing
HEAD SET	ACROS AZX-220 R4, ZS44/28.6 ZS56/40, BlockLock 150°
FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
COLOUR	GLOSS WHITE/HOLOGRAM BLACK
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100 Shadow Plus
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SEAT POST	ONE1 Race Alloy, SP 218, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	Sapim Laser, Stainless Black/ Sapim Laser/ Sapim Race, Stainless Black

XP 939

MATTE BLACK/STEALTH CHROME



GRAPHIC SIMULATION ONLY / REAL PICTURE SOON

MTB HARDTAIL / RACE

BENEFITS

- A new generation of triple-butted, cutting-edge aluminium frame, BOOST standard hubs, tapered headset, and completely inner routing
- Lightweight and strong remote lockout RockShox Recon Silver RL R fork with a travel of 100 mm
- 1x12 Shimano drivetrain with a large range of gears to suit various terrain patterns
- Schwalbe Racing Ralph tires for a safer and more comfortable ride

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	585	610	630	650
REACH (MM)	415	437	455	472
STACK HEIGHT (MM)	591	600	609	619
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	440	440	440	440
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1105	1130	1151	1172
HANDLEBAR WIDTH (MM)	760/720	760/720	760/720	760/720
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Conical Head Tube, BB92, Boost Thru axle 148x12mm, Inner cable routing
HEAD SET	ACROS AZX-212 R5,ZS44/28.6 ZS56/40
FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
COLOUR	MATTE BLACK/STEALTH CHROME
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO SLX SL-M7100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100 Shadow Plus
CRANKSET	SHIMANO XT FC-M8100 Hollowtech II, 34T
CASSETTE	SHIMANO CS-M7100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SEAT POST	ONE1 Race Alloy, SP 218, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	Sapim Laser, Stainless Black/ Sapim Laser/ Sapim Race, Stainless Black

XP 939

BRUSHED ALU/HOLOGRAM CHROME



MTB HARDTAIL / RACE

BENEFITS

- A new generation of triple-butted, cutting-edge aluminium frame, BOOST standard hubs, tapered headset, and completely inner routing
- Lightweight and strong remote lockout RockShox Recon Silver RL R fork with a travel of 100 mm
- 1x12 Shimano drivetrain with a large range of gears to suit various terrain patterns
- Schwalbe Racing Ralph tires for a safer and more comfortable ride

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	585	610	630	650
REACH (MM)	415	437	455	472
STACK HEIGHT (MM)	591	600	609	619
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	440	440	440	440
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1105	1130	1151	1172
HANDLEBAR WIDTH (MM)	760/720	760/720	760/720	760/720
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Conical Head Tube, BB92, Boost Thru axle 148x12mm, Inner cable routing
HEAD SET	ACROS AZX-212 R5,ZS44/28.6 ZS56/40
FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
COLOUR	BRUSHED ALU/HOLOGRAM CHROME
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO SLX SL-M7100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100 Shadow Plus
CRANKSET	SHIMANO XT FC-M8100 Hollowtech II, 34T
CASSETTE	SHIMANO CS-M7100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SEAT POST	ONE1 Race Alloy, SP 218, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	Sapim Laser, Stainless Black/ Sapim Laser/ Sapim Race, Stainless Black

XP 939

MATTE LIME METALLIC/CHROME SILVER



GRAPHIC SIMULATION ONLY / REAL PICTURE SOON

MTB HARDTAIL / RACE

BENEFITS

- A new generation of triple-butted, cutting-edge aluminium frame, BOOST standard hubs, tapered headset, and completely inner routing
- Lightweight and strong remote lockout RockShox Recon Silver RL R fork with a travel of 100 mm
- 1x12 Shimano drivetrain with a large range of gears to suit various terrain patterns
- Schwalbe Racing Ralph tires for a safer and more comfortable ride

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	585	610	630	650
REACH (MM)	415	437	455	472
STACK HEIGHT (MM)	591	600	609	619
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	440	440	440	440
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1105	1130	1151	1172
HANDLEBAR WIDTH (MM)	760/720	760/720	760/720	760/720
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Conical Head Tube, BB92, Boost Thru axle 148x12mm, Inner cable routing
HEAD SET	ACROS AZX-212 R5,ZS44/28.6 ZS56/40
FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
COLOUR	MATTE LIME METALLIC/CHROME SILVER
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO SLX SL-M7100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100 Shadow Plus
CRANKSET	SHIMANO XT FC-M8100 Hollowtech II, 34T
CASSETTE	SHIMANO CS-M7100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SEAT POST	ONE1 Race Alloy, SP 218, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	Sapim Laser, Stainless Black/ Sapim Laser/ Sapim Race, Stainless Black

XP 919

GLOSS NIGHT GREEN/CHROME SILVER/RED



MTB HARDTAIL / RACE

BENEFITS

- A new generation of triple butted, cutting-edge aluminium frame, BOOST standard hubs, tapered headset, and inner routing
- Lightweight, remote lockout RockShox Judy Silver TK R BOOST fork with a travel of 100 mm
- 1x12 Shimano drivetrain with a large range of gears to suit various terrain patterns
- Schwalbe Racing Ralph tires for a safer and more comfortable ride in rough terrain

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	585	610	630	650
REACH (MM)	415	437	455	472
STACK HEIGHT (MM)	591	600	609	619
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	440	440	440	440
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1105	1130	1151	1172
HANDLEBAR WIDTH (MM)	760/720	760/720	760/720	760/720
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Conical Head Tube, BB92, Boost Thru axle 148x12mm, Inner cable routing
HEAD SET	ACROS AZX-212 R5,ZS44/28.6 ZS56/40
FORK	RockShox Judy Silver TK R, Tapered, SoloAir, 15x110mm axle, 100mm travel
COLOUR	GLOSS NIGHT GREEN/CHROME SILVER/RED
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100 Shadow Plus
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SEAT POST	ONE1 Race Alloy, SP 218, 27.2mm
WHEELS	
FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	Sapim Laser, Stainless Black/ Sapim Laser/ Sapim Race, Stainless Black

XP 919

GLOSS DARK RED/HOLOGRAM CHROME



MTB HARDTAIL / RACE

BENEFITS

- A new generation of triple butted, cutting-edge aluminium frame, BOOST standard hubs, tapered headset, and inner routing
- Lightweight, remote lockout RockShox Judy Silver TK R BOOST fork with a travel of 100 mm
- 1x12 Shimano drivetrain with a large range of gears to suit various terrain patterns
- Schwalbe Racing Ralph tires for a safer and more comfortable ride in rough terrain

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	585	610	630	650
REACH (MM)	415	437	455	472
STACK HEIGHT (MM)	591	600	609	619
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	440	440	440	440
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1105	1130	1151	1172
HANDLEBAR WIDTH (MM)	760/720	760/720	760/720	760/720
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Conical Head Tube, BB92, Boost Thru axle 148x12mm, Inner cable routing
HEAD SET	ACROS AZX-212 R5,ZS44/28.6 ZS56/40
FORK	RockShox Judy Silver TK R, Tapered, SoloAir, 15x110mm axle, 100mm travel
COLOUR	GLOSS DARK RED/HOLOGRAM CHROME
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100 Shadow Plus
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SEAT POST	ONE1 Race Alloy, SP 218, 27.2mm
WHEELS	
FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	Sapim Laser, Stainless Black/ Sapim Laser/ Sapim Race, Stainless Black

XP 919

MATTE BLACK/STEALTH CHROME



GRAPHIC SIMULATION ONLY / REAL PICTURE SOON

MTB HARDTAIL / RACE

BENEFITS

- A new generation of triple butted, cutting-edge aluminium frame, BOOST standard hubs, tapered headset, and inner routing
- Lightweight, remote lockout RockShox Judy Silver TK R BOOST fork with a travel of 100 mm
- 1x12 Shimano drivetrain with a large range of gears to suit various terrain patterns
- Schwalbe Racing Ralph tires for a safer and more comfortable ride in rough terrain

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	585	610	630	650
REACH (MM)	415	437	455	472
STACK HEIGHT (MM)	591	600	609	619
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	440	440	440	440
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1105	1130	1151	1172
HANDLEBAR WIDTH (MM)	760/720	760/720	760/720	760/720
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Conical Head Tube, BB92, Boost Thru axle 148x12mm, Inner cable routing
HEAD SET	ACROS AZX-212 R5,ZS44/28.6 ZS56/40
FORK	RockShox Judy Silver TK R, Tapered, SoloAir, 15x110mm axle, 100mm travel
COLOUR	MATTE BLACK/STEALTH CHROME
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100 Shadow Plus
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 Race Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SEAT POST	ONE1 Race Alloy, SP 218, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	Sapim Laser, Stainless Black/ Sapim Laser/ Sapim Race, Stainless Black

XP 909

MATTE BLACK/CHROMESILVER



GRAPHIC SIMULATION ONLY / REAL PICTURE SOON

MTB HARDTAIL / RACE

BENEFITS

- A new generation of triple-butted, cutting-edge aluminium frame, BOOST standard hubs, tapered headset, and completely inner routing
- Lightweight, remote lockout RockShox Judy Silver TK R BOOST fork with a travel of 100 mm
- 1x11 Shimano drivetrain with a large range of gears to suit various terrain patterns
- Schwalbe Racing Ralph tires for a safer and more comfortable ride in rough terrain
- Thru-axles improve the stiffness and stability in terrain rides or intensive braking

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	585	610	630	650
REACH (MM)	415	437	455	472
STACK HEIGHT (MM)	591	600	609	619
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	440	440	440	440
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1105	1130	1151	1172
HANDLEBAR WIDTH (MM)	760/720	760/720	760/720	760/720
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Conical Head Tube, BB92, Boost Thru axle 148x12mm, Inner cable routing
HEAD SET	ACROS AZX-212 R5,ZS44/28.6 ZS56/40
FORK	RockShox Judy Silver TK R, Tapered, SoloAir, 15x110mm axle, 100mm travel
COLOUR	MATTE BLACK/CHROMESILVER
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M5100-IR RapidFire Plus, 11-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5100 Shadow Plus
CASSETTE	SHIMANO CS-M5100-11, 11-51T
BOTTOM BRACKET CHAIN	BB-MT500PA PressFit, shell 41x92mm KMC X11

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 TDS-D507 Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SEAT POST	ONE1 Race Alloy, SP 218, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT400-B, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Rapid Rob KevlarGuard, 29x2.10"
SPOKES	Sapim Leader, Stainless Black

XP 909

GLOSS WHITE/HOLOGRAM BLACK/RED



MTB HARDTAIL / RACE

BENEFITS

- A new generation of triple-butted, cutting-edge aluminium frame, BOOST standard hubs, tapered headset, and completely inner routing
- Lightweight, remote lockout RockShox Judy Silver TK R BOOST fork with a travel of 100 mm
- 1x11 Shimano drivetrain with a large range of gears to suit various terrain patterns
- Schwalbe Racing Ralph tires for a safer and more comfortable ride in rough terrain
- Thru-axles improve the stiffness and stability in terrain rides or intensive braking

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	585	610	630	650
REACH (MM)	415	437	455	472
STACK HEIGHT (MM)	591	600	609	619
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	440	440	440	440
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1105	1130	1151	1172
HANDLEBAR WIDTH (MM)	760/720	760/720	760/720	760/720
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Conical Head Tube, BB92, Boost Thru axle 148x12mm, Inner cable routing
HEAD SET	ACROS AZX-212 R5,ZS44/28.6 ZS56/40
FORK	RockShox Judy Silver TK R, Tapered, SoloAir, 15x110mm axle, 100mm travel
COLOUR	GLOSS WHITE/HOLOGRAM BLACK/RED
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M5100-IR RapidFire Plus, 11-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5100 Shadow Plus
CASSETTE	SHIMANO CS-M5100-11, 11-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	KMC X11

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 TDS-D507 Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SEAT POST	ONE1 Race Alloy, SP 218, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT400-B, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Rapid Rob KevlarGuard, 29x2.10"
SPOKES	Sapim Leader, Stainless Black

XP 909

GLOSS VIOLET/HOLOGRAM CHROME



GRAPHIC SIMULATION ONLY / REAL PICTURE SOON

MTB HARDTAIL / RACE

BENEFITS

- A new generation of triple-butted, cutting-edge aluminium frame, BOOST standard hubs, tapered headset, and completely inner routing
- Lightweight, remote lockout RockShox Judy Silver TK R BOOST fork with a travel of 100 mm
- 1x11 Shimano drivetrain with a large range of gears to suit various terrain patterns
- Schwalbe Racing Ralph tires for a safer and more comfortable ride in rough terrain
- Thru-axles improve the stiffness and stability in terrain rides or intensive braking

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74	74	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	585	610	630	650
REACH (MM)	415	437	455	472
STACK HEIGHT (MM)	591	600	609	619
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	69	69	69	69
CHAINSTAY LENGTH (MM)	440	440	440	440
BB DROP (MM)	55	55	55	55
WHEELBASE (MM)	1105	1130	1151	1172
HANDLEBAR WIDTH (MM)	760/720	760/720	760/720	760/720
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	400	400	400	400

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Conical Head Tube, BB92, Boost Thru axle 148x12mm, Inner cable routing
HEAD SET	ACROS AZX-212 R5,ZS44/28.6 ZS56/40
FORK	RockShox Judy Silver TK R, Tapered, SoloAir, 15x110mm axle, 100mm travel
COLOUR	GLOSS VIOLET/HOLOGRAM CHROME
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M5100-IR RapidFire Plus, 11-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5100 Shadow Plus
CASSETTE	SHIMANO CS-M5100-11, 11-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	KMC X11

COMPONENTS

HANDLEBAR	ONE1 Race, Horizon Bow, 9° backsweep, 5mm rise, 760mm, 31.8mm
STEM	ONE1 TDS-D507 Alloy, 31.8mm, -7°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SEAT POST	ONE1 Race Alloy, SP 218, 27.2mm
WHEELS	
FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT400-B, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Rapid Rob KevlarGuard, 29x2.10"
SPOKES	Sapim Leader, Stainless Black

XC 899

MATTE BLACK/SILVER/OLIVE



MTB HARDTAIL / SPORT

BENEFITS

- Air suspension fork for sensitive settings and responsive function
- Schwalbe tires with universal thread for speed on tarmac and safety of roads
- Shimano Deore 1x11 with a huge gear ratio for easy and intuitive shifting
- Powerful hydraulic disc brakes with 180/160mm rotors
- Ready to City: mounting points for accessories (mudguards, kickstand etc.)

GEOMETRY

FRAME SIZE	16.0" (S)	18.0" (M)	20" (L)	22" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	406	457	508	559
SEAT TUBE ANGLE (DEGREE)	72.4	72	72	72.4
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
REACH (MM)	372	387	407	421
STACK HEIGHT (MM)	620	639	639	657
HEAD TUBE LENGTH (MM)	100	120	120	140
HEAD TUBE ANGLE (DEGREE)	70	70	70	70
CHAINSTAY LENGTH (MM)	445	445	445	445
BB DROP (MM)	60	60	60	60
WHEELBASE (MM)	1066	1087	1107	1128
HANDLEBAR WIDTH (MM)	720	720	740	740
STEM LENGTH (MM)	70	70	90	90
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	350	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Conical Head Tube, BB BSA 73 mm, IDK dropout, Smooth Welding, Inner cable routing
COLOUR	MATTE BLACK/SILVER/OLIVE
SIZES	16.0" (S), 18.0" (M), 20" (L), 22" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M5100-R RapidFire Plus, 11-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5100 Shadow Plus
CASSETTE	SHIMANO CS-M5100-11, 11-51T
CHAIN	KMC X11
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 740mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Sport Alloy, SP C255, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Smart Sam KevlarGuard, 29x2.10"
SPOKES	Sapim Galvanized Black

XC 899

MATTE LIME METALLIC/CHROME SILVER



MTB HARDTAIL / SPORT

BENEFITS

- Air suspension fork for sensitive settings and responsive function
- Schwalbe tires with universal thread for speed on tarmac and safety of roads
- Shimano Deore 1x11 with a huge gear ratio for easy and intuitive shifting
- Powerful hydraulic disc brakes with 180/160mm rotors
- Ready to City: mounting points for accessories (mudguards, kickstand etc.)

GEOMETRY

FRAME SIZE	16.0" (S)	18.0" (M)	20" (L)	22" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	406	457	508	559
SEAT TUBE ANGLE (DEGREE)	72.4	72	72	72.4
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
REACH (MM)	372	387	407	421
STACK HEIGHT (MM)	620	639	639	657
HEAD TUBE LENGTH (MM)	100	120	120	140
HEAD TUBE ANGLE (DEGREE)	70	70	70	70
CHAINSTAY LENGTH (MM)	445	445	445	445
BB DROP (MM)	60	60	60	60
WHEELBASE (MM)	1066	1087	1107	1128
HANDLEBAR WIDTH (MM)	720	720	740	740
STEM LENGTH (MM)	70	70	90	90
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	350	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Conical Head Tube, BB BSA 73 mm, IDK dropout, Smooth Welding, Inner cable routing
COLOUR	MATTE LIME METALLIC/CHROME SILVER
SIZES	16.0" (S), 18.0" (M), 20" (L), 22" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M5100-R RapidFire Plus, 11-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5100 Shadow Plus
CASSETTE	SHIMANO CS-M5100-11, 11-51T
CHAIN	KMC X11
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 740mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Sport Alloy, SP C255, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Smart Sam KevlarGuard, 29x2.10"
SPOKES	Sapim Galvanized Black

XC 899 W

MATTE CRIMSON/WHITE/PURPLE



BENEFITS

- Air suspension fork for sensitive settings and responsive function
- Schwalbe tires with universal thread for speed on tarmac and safety off-road
- Shimano Deore 1x11 with a huge gear ratio for easy and intuitive shifting
- Powerful hydraulic disc brakes with 180/160mm rotors
- Ready to City: mounting points for accessories (mudguards, kickstand etc.)

GEOMETRY

FRAME SIZE	16.0" (S)	18.0" (M)
WHEEL SIZE	29	29
SEAT TUBE LENGTH (MM)	406	457
SEAT TUBE ANGLE (DEGREE)	72.4	72
EFFECTIVE TOP TUBE LENGTH (MM)	570	590
REACH (MM)	372	387
STACK HEIGHT (MM)	620	639
HEAD TUBE LENGTH (MM)	100	120
HEAD TUBE ANGLE (DEGREE)	70	70
CHAINSTAY LENGTH (MM)	445	445
BB DROP (MM)	60	60
WHEELBASE (MM)	1066	1087
HANDLEBAR WIDTH (MM)	740/720	740/720
STEM LENGTH (MM)	70	70
CRANK LENGTH (MM)	170	175
SEAT POST LENGTH (MM)	350	350

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Woman Geometry, Conical Head Tube, BB BSA 73 mm, IDK dropout, Smooth Welding, Inner cable routing
COLOUR	MATTE CRIMSON/WHITE/PURPLE
SIZES	16.0" (S), 18.0" (M)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M5100-R RapidFire Plus, 11-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5100 Shadow Plus
CASSETTE	SHIMANO CS-M5100-11, 11-51T
CHAIN	KMC X11
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 720mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo DRN
SEAT POST	ONE1 Sport Alloy, SP C255, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Smart Sam 29x2.10"
SPOKES	Sapim Galvanized Black

XC 889

GLOSS GREY/ORANGE



MTB HARDTAIL / SPORT

BENEFITS

- Double butted aluminium frame with a sports geometry and internal cable routing
- Adjustable Suntour remote lockout air fork
- Universal pattern Schwalbe tires
- 2x11 Shimano drivetrain for a wide range of gears
- High performance, gradual pressure Shimano brakes
- Mudguards, kickstand, and cargo rack options

GEOMETRY

FRAME SIZE	16.0" (S)	18.0" (M)	20" (L)	22" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	406	457	508	559
SEAT TUBE ANGLE (DEGREE)	72.4	72	72	72.4
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
REACH (MM)	372	387	407	421
STACK HEIGHT (MM)	620	639	639	657
HEAD TUBE LENGTH (MM)	100	120	120	140
HEAD TUBE ANGLE (DEGREE)	70	70	70	70
CHAINSTAY LENGTH (MM)	445	445	445	445
BB DROP (MM)	60	60	60	60
WHEELBASE (MM)	1066	1087	1107	1128
HANDLEBAR WIDTH (MM)	720	720	740	740
STEM LENGTH (MM)	70	70	90	90
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	350	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Conical Head Tube, BB BSA 73 mm, IDK dropout, Smooth Welding, Inner cable routing
COLOUR	GLOSS GREY/ORANGE
SIZES	16.0" (S), 18.0" (M), 20" (L), 22" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M5100-L RapidFire Plus, 2-speed, SHIMANO DEORE SL-M5100-R RapidFire Plus, 11-speed
FRONT DERAILLEUR	SHIMANO FD-M5100-M, SIDE SWING, FRONT-PULL
REAR DERAILLEUR	SHIMANO DEORE RD-M4120 Shadow
CRANKSET	SHIMANO FC-M5100-2 36-26T
CASSETTE	SHIMANO CS-M5100-11, 11-42T
CHAIN	KMC X11
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 740mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Sport Alloy, SP C255, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Smart Sam KevlarGuard, 29x2.10"
SPOKES	Sapim Galvanized Black

XC 889

MATTE PETROL/SILVER



MTB HARDTAIL / SPORT

BENEFITS

- Double butted aluminium frame with a sports geometry and internal cable routing
- Adjustable Suntour remote lockout air fork
- Universal pattern Schwalbe tires
- 2x11 Shimano drivetrain for a wide range of gears
- High performance, gradual pressure Shimano brakes
- Mudguards, kickstand, and cargo rack options

GEOMETRY

FRAME SIZE	16.0" (S)	18.0" (M)	20" (L)	22" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	406	457	508	559
SEAT TUBE ANGLE (DEGREE)	72.4	72	72	72.4
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
REACH (MM)	372	387	407	421
STACK HEIGHT (MM)	620	639	639	657
HEAD TUBE LENGTH (MM)	100	120	120	140
HEAD TUBE ANGLE (DEGREE)	70	70	70	70
CHAINSTAY LENGTH (MM)	445	445	445	445
BB DROP (MM)	60	60	60	60
WHEELBASE (MM)	1066	1087	1107	1128
HANDLEBAR WIDTH (MM)	720	720	740	740
STEM LENGTH (MM)	70	70	90	90
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	350	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Conical Head Tube, BB BSA 73 mm, IDK dropout, Smoot Welding, Inner cable routing
COLOUR	MATTE PETROL/SILVER
SIZES	16.0" (S), 18.0" (M), 20" (L), 22" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M5100-L RapidFire Plus, 2-speed, SHIMANO DEORE SL-M5100-R RapidFire Plus, 11-speed
FRONT DERAILLEUR	SHIMANO FD-M5100-M, SIDE SWING, FRONT-PULL
REAR DERAILLEUR	SHIMANO DEORE RD-M4120 Shadow
CRANKSET	SHIMANO FC-M5100-2 36-26T
CASSETTE	SHIMANO CS-M5100-11, 11-42T
CHAIN	KMC X11
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 740mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Sport Alloy, SP C255, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Smart Sam KevlarGuard, 29x2.10"
SPOKES	Sapim Galvanized Black

XC 889 W

GLOSS WHITE/BLUE/LIME



MTB HARDTAIL / SPORT

BENEFITS

- Double-butted aluminium frame with a comfortable sports geometry and internal cable routing
- Adjustable Suntour remote lockout air fork
- Universal thread Schwalbe tires
- 2x11 Shimano drivetrain for a wide range of gears
- High performance, gradual pressure Shimano brakes
- Mudguards, kickstand, and cargo rack options

GEOMETRY

FRAME SIZE	16.0" (S)	18.0" (M)
WHEEL SIZE	29	29
SEAT TUBE LENGTH (MM)	406	457
SEAT TUBE ANGLE (DEGREE)	72.4	72
EFFECTIVE TOP TUBE LENGTH (MM)	570	590
REACH (MM)	372	387
STACK HEIGHT (MM)	620	639
HEAD TUBE LENGTH (MM)	100	120
HEAD TUBE ANGLE (DEGREE)	70	70
CHAINSTAY LENGTH (MM)	445	445
BB DROP (MM)	60	60
WHEELBASE (MM)	1066	1087
HANDLEBAR WIDTH (MM)	740/720	740/720
STEM LENGTH (MM)	70	70
CRANK LENGTH (MM)	170	175
SEAT POST LENGTH (MM)	350	350

SPECIFICATION

FRAMESET

FRAME Alu 6061 T6 Double Butted, Smooth Welding, Sport Woman Geometry, Conical Head Tube, BB BSA 73 mm, IDK dropout, Smooth Welding, Inner cable routing

COLOUR GLOSS WHITE/BLUE/LIME
SIZES 16.0" (S), 18.0" (M)

DRIVETRAIN

SHIFTER SHIMANO DEORE SL-M5100-L RapidFire Plus, 2-speed, SHIMANO DEORE SL-M5100-R RapidFire Plus, 11-speed
FRONT DERAILLEUR SHIMANO FD-M5100-M, SIDE SWING, FRONT-PULL
REAR DERAILLEUR SHIMANO DEORE RD-M4120 Shadow
CRANKSET SHIMANO FC-M5100-2 36-26T
CASSETTE SHIMANO CS-M5100-11, 11-42T
CHAIN KMC X11
PEDALS Marwi SP-610

COMPONENTS

HANDLEBAR ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 720mm, 31.8mm
STEM ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS ONE1 VLG-1661D2N, Lock-On
BRAKES SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE Selle Royal Vivo DRN
SEAT POST ONE1 Sport Alloy, SP C255, 30.9mm

WHEELS

FRONT HUB SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS Stars J25DH, 32H
TIRES Schwalbe Smart Sam Performance, 29x1.75", ADDIX
SPOKES Sapim Galvanized Black

XC 879

MATTE BLACK/SILVER/OLIVE



MTB HARDTAIL / SPORT

BENEFITS

- Double butted, sports geometry aluminium frame with internal cable routing
- Adjustable Suntour remote lockout air fork
- Universal thread Schwalbe tires
- 2x10 Shimano drivetrain for easy control
- High performance, gradual pressure Shimano brakes
- Mudguards, kickstand, and cargo rack options

GEOMETRY

FRAME SIZE	16.0" (S)	18.0" (M)	20" (L)	22" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	406	457	508	559
SEAT TUBE ANGLE (DEGREE)	72.4	72	72	72.4
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
REACH (MM)	372	387	407	421
STACK HEIGHT (MM)	620	639	639	657
HEAD TUBE LENGTH (MM)	100	120	120	140
HEAD TUBE ANGLE (DEGREE)	70	70	70	70
CHAINSTAY LENGTH (MM)	445	445	445	445
BB DROP (MM)	60	60	60	60
WHEELBASE (MM)	1066	1087	1107	1128
HANDLEBAR WIDTH (MM)	720	720	740	740
STEM LENGTH (MM)	70	70	90	90
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	350	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Conical Head Tube, BB BSA 73 mm, IDK dropout, Smooth Welding, Inner cable routing
COLOUR	MATTE BLACK/SILVER/OLIVE
SIZES	16.0" (S), 18.0" (M), 20" (L), 22" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M4100-R RapidFire Plus, 10-speed, SHIMANO DEORE SL-M5100-L RapidFire Plus, 2-speed
FRONT DERAILLEUR	SHIMANO FD-M4100-M, SIDE SWING, FRONT-PULL
REAR DERAILLEUR	SHIMANO DEORE RD-M4120 Shadow
CRANKSET	ONE1 TAF38-239SS, 36-26T
CASSETTE	SHIMANO CS-M4100-10, 11-42T
BOTTOM BRACKET	SHIMANO SM-BB52, BSA, shell 68/73mm
CHAIN	KMC X10
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 740mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Smart Sam KevlarGuard, 29x2.10"
SPOKES	Sapim Galvanized Black

XC 879

GLOSS WHITE/BLACK METALLIC



MTB HARDTAIL / SPORT

BENEFITS

- Double butted, sports geometry aluminium frame with internal cable routing
- Adjustable Suntour remote lockout air fork
- Universal thread Schwalbe tires
- 2x10 Shimano drivetrain for easy control
- High performance, gradual pressure Shimano brakes
- Mudguards, kickstand, and cargo rack options

GEOMETRY

FRAME SIZE	16.0" (S)	18.0" (M)	20" (L)	22" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	406	457	508	559
SEAT TUBE ANGLE (DEGREE)	72.4	72	72	72.4
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
REACH (MM)	372	387	407	421
STACK HEIGHT (MM)	620	639	639	657
HEAD TUBE LENGTH (MM)	100	120	120	140
HEAD TUBE ANGLE (DEGREE)	70	70	70	70
CHAINSTAY LENGTH (MM)	445	445	445	445
BB DROP (MM)	60	60	60	60
WHEELBASE (MM)	1066	1087	1107	1128
HANDLEBAR WIDTH (MM)	720	720	740	740
STEM LENGTH (MM)	70	70	90	90
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	350	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Conical Head Tube, BB BSA 73 mm, IDK dropout, Smooth Welding, Inner cable routing
COLOUR	GLOSS WHITE/BLACK METALLIC
SIZES	16.0" (S), 18.0" (M), 20" (L), 22" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M4100-R RapidFire Plus, 10-speed, SHIMANO DEORE SL-M5100-L RapidFire Plus, 2-speed
FRONT DERAILLEUR	SHIMANO FD-M4100-M, SIDE SWING, FRONT-PULL
REAR DERAILLEUR	SHIMANO DEORE RD-M4120 Shadow
CRANKSET	ONE1 TAF38-239SS, 36-26T
CASSETTE	SHIMANO CS-M4100-10, 11-42T
BOTTOM BRACKET	SHIMANO SM-BB52, BSA, shell 68/73mm
CHAIN	KMC X10
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 740mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Smart Sam KevlarGuard, 29x2.10"
SPOKES	Sapim Galvanized Black

XC 879 W

MATTE BLACK/CHROME SILVER



MTB HARDTAIL / SPORT

BENEFITS

- Double-butted, sports geometry aluminium frame with internal cable routing
- Adjustable Suntour remote lockout air fork
- Universal pattern Schwalbe tires
- 2x10 Shimano drivetrain for easy control
- High performance, gradual pressure Shimano brakes
- Mudguards, kickstand, and cargo rack options

GEOMETRY

FRAME SIZE	16.0" (S)	18.0" (M)	20.0" (L)
WHEEL SIZE	29	29	29
SEAT TUBE LENGTH (MM)	406	457	508
SEAT TUBE ANGLE (DEGREE)	72.4	72	72
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610
REACH (MM)	372	387	407
STACK HEIGHT (MM)	620	639	639
HEAD TUBE LENGTH (MM)	100	120	120
HEAD TUBE ANGLE (DEGREE)	70	70	70
CHAINSTAY LENGTH (MM)	445	445	445
BB DROP (MM)	60	60	60
WHEELBASE (MM)	1066	1087	1107
HANDLEBAR WIDTH (MM)	720	720	720
STEM LENGTH (MM)	70	70	90
CRANK LENGTH (MM)	170	175	175
SEAT POST LENGTH (MM)	350	350	350

SPECIFICATION

FRAMESET

FRAME Alu 6061 T6 Double Butted, Smooth Welding, Sport Woman Geometry, Conical Head Tube, BB BSA 73 mm, IDK dropout, Smooth Welding, Inner cable routing

COLOUR MATTE BLACK/CHROME SILVER
SIZES 16.0" (S), 18.0" (M), 20.0" (L)

DRIVETRAIN

SHIFTER SHIMANO DEORE SL-M4100-R RapidFire Plus, 10-speed, SHIMANO DEORE SL-M5100-L RapidFire Plus, 2-speed
FRONT DERAILLEUR SHIMANO FD-M4100-M, SIDE SWING, FRONT-PULL
REAR DERAILLEUR SHIMANO DEORE RD-M4120 Shadow
CRANKSET ONE1 TAF38-239SS, 36-26T
CASSETTE SHIMANO CS-M4100-10, 11-42T
BOTTOM BRACKET SHIMANO SM-BB52, BSA, shell 68/73mm
CHAIN KMC X10
PEDALS Marwi SP-610

COMPONENTS

HANDLEBAR ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 720mm, 31.8mm
STEM ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS ONE1 VLG-1661D2N, Lock-On
BRAKES SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE Selle Royal Vivo DRN
SEAT POST ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS Stars J25DH, 32H
TIRES Schwalbe Smart Sam Performance, 29x1.75", ADDIX
SPOKES Sapim Galvanized Black

XC 859

GLOSS GREY/ORANGE



MTB HARDTAIL / SPORT

BENEFITS

- Double-butted aluminium frame with comfortable sports geometry and internal cable routing
- Suntour hydraulic lockout coil fork
- Universal thread Schwalbe tires
- Shimano 2x9 drivetrain for easy control
- High-performance, gradual pressure Shimano brakes
- Cargo rack, kickstand, and mudguards optional

GEOMETRY

FRAME SIZE	16.0" (S)	18.0" (M)	20" (L)	22" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	406	457	508	559
SEAT TUBE ANGLE (DEGREE)	72.4	72	72	72.4
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
REACH (MM)	372	387	407	421
STACK HEIGHT (MM)	620	639	639	657
HEAD TUBE LENGTH (MM)	100	120	120	140
HEAD TUBE ANGLE (DEGREE)	70	70	70	70
CHAINSTAY LENGTH (MM)	445	445	445	445
BB DROP (MM)	60	60	60	60
WHEELBASE (MM)	1066	1087	1107	1128
HANDLEBAR WIDTH (MM)	720	720	740	740
STEM LENGTH (MM)	70	70	90	90
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	350	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Conical Head Tube, BB BSA 73 mm, IDK dropout, Smooth Welding, Inner cable routing
COLOUR	GLOSS GREY/ORANGE
SIZES	16.0" (S), 18.0" (M), 20" (L), 22" (XL)

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-2L RapidFire Plus, 2-speed, SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
FRONT DERAILLEUR	SHIMANO FD-M3120-M, SIDE SWING, FRONT-PULL
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	SHIMANO FC-MT101, 36-22T
CASSETTE	SHIMANO CS-HG200-9, 11-36T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC X9
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 740mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Smart Sam KevlarGuard, 29x2.10"
SPOKES	Sapim Galvanized Black

XC 859

MATTE LIME METALLIC/CHROME SILVER



MTB HARDTAIL / SPORT

BENEFITS

- Double-butted aluminium frame with comfortable sports geometry and internal cable routing
- Suntour hydraulic lockout coil fork
- Universal thread Schwalbe tires
- Shimano 2x9 drivetrain for easy control
- High-performance, gradual pressure Shimano brakes
- Cargo rack, kickstand, and mudguards optional

GEOMETRY

FRAME SIZE	16.0" (S)	18.0" (M)	20" (L)	22" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	406	457	508	559
SEAT TUBE ANGLE (DEGREE)	72.4	72	72	72.4
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
REACH (MM)	372	387	407	421
STACK HEIGHT (MM)	620	639	639	657
HEAD TUBE LENGTH (MM)	100	120	120	140
HEAD TUBE ANGLE (DEGREE)	70	70	70	70
CHAINSTAY LENGTH (MM)	445	445	445	445
BB DROP (MM)	60	60	60	60
WHEELBASE (MM)	1066	1087	1107	1128
HANDLEBAR WIDTH (MM)	720	720	740	740
STEM LENGTH (MM)	70	70	90	90
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	350	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Conical Head Tube, BB BSA 73 mm, IDK dropout, Smooth Welding, Inner cable routing
COLOUR	MATTE LIME METALLIC/CHROME SILVER
SIZES	16.0" (S), 18.0" (M), 20" (L), 22" (XL)

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-2L RapidFire Plus, 2-speed, SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
FRONT DERAILLEUR	SHIMANO FD-M3120-M, SIDE SWING, FRONT-PULL
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	SHIMANO FC-MT101, 36-22T
CASSETTE	SHIMANO CS-HG200-9, 11-36T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC X9
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 740mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Smart Sam KevlarGuard, 29x2.10"
SPOKES	Sapim Galvanized Black

XC 859 W

MATTE DARK PETROL/TURQUOISE



MTB HARDTAIL / SPORT

BENEFITS

- Double-butted aluminium frame with comfortable sports geometry and internal cable routing
- Components and shapes made to fit women
- Suntour hydraulic lockout coil fork
- Universal pattern Schwalbe tires
- Shimano 2x9 drivetrain for easy control
- High-performance, gradual pressure Shimano brakes
- Cargo rack, kickstand, and mudguards optional

GEOMETRY

FRAME SIZE	16.0" (S)	18.0" (M)
WHEEL SIZE	29	29
SEAT TUBE LENGTH (MM)	406	457
SEAT TUBE ANGLE (DEGREE)	72.4	72
EFFECTIVE TOP TUBE LENGTH (MM)	570	590
REACH (MM)	372	387
STACK HEIGHT (MM)	620	639
HEAD TUBE LENGTH (MM)	100	120
HEAD TUBE ANGLE (DEGREE)	70	70
CHAINSTAY LENGTH (MM)	445	445
BB DROP (MM)	60	60
WHEELBASE (MM)	1066	1087
HANDLEBAR WIDTH (MM)	740/720	740/720
STEM LENGTH (MM)	70	70
CRANK LENGTH (MM)	170	175
SEAT POST LENGTH (MM)	350	350

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Woman Geometry, Conical Head Tube, BB BSA 73 mm, IDK dropout, Smooth Welding, Inner cable routing
COLOUR	MATTE DARK PETROL/TURQUOISE
SIZES	16.0" (S), 18.0" (M)

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-2L RapidFire Plus, 2-speed, SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
FRONT DERAILLEUR	SHIMANO FD-M3120-M, SIDE SWING, FRONT-PULL
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	SHIMANO FC-MT101, 36-22T
CASSETTE	SHIMANO CS-HG200-9, 11-36T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC X9
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 720mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo DRN
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Smart Sam Performance, 29x1.75", ADDIX
SPOKES	Sapim Galvanized Black

XC 819

MATTE BLACK/WHITE/TEAM RED



MTB HARDTAIL / SPORT

BENEFITS

- Double-butted aluminium frame with comfortable sports geometry and internal cable routing
- Suntour coil fork
- Universal thread Schwalbe tires
- Shimano 2x8 drivetrain for easy control
- High-performance, gradual pressure Shimano brakes
- Cargo rack, kickstand, and mudguards optional

GEOMETRY

FRAME SIZE	16.0" (S)	18.0" (M)	20" (L)	22" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	406	457	508	559
SEAT TUBE ANGLE (DEGREE)	72.4	72	72	72.4
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
REACH (MM)	372	387	407	421
STACK HEIGHT (MM)	620	639	639	657
HEAD TUBE LENGTH (MM)	100	120	120	140
HEAD TUBE ANGLE (DEGREE)	70	70	70	70
CHAINSTAY LENGTH (MM)	445	445	445	445
BB DROP (MM)	60	60	60	60
WHEELBASE (MM)	1066	1087	1107	1128
HANDLEBAR WIDTH (MM)	720	720	740	740
STEM LENGTH (MM)	70	70	90	90
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	350	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Conical Head Tube, BB BSA 73 mm, IDK dropout, Smooth Welding, Inner cable routing
COLOUR	MATTE BLACK/WHITE/TEAM RED
SIZES	16.0" (S), 18.0" (M), 20" (L), 22" (XL)

DRIVETRAIN

SHIFTER	SHIMANO ALTUS SL-M315-2L RapidFire Plus, 2-speed, SHIMANO ALTUS SL-M315-8R RapidFire Plus, 8-speed
FRONT DERAILLEUR	SHIMANO FD-M315-TS, TOP SWING, DUAL-PULL
REAR DERAILLEUR	SHIMANO ALTUS RD-M310-L
CRANKSET	SHIMANO FC-M315, 36-22T
CASSETTE	SHIMANO CS-HG31-8, 11-34T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 740mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Smart Sam 29x2.10"
SPOKES	Sapim Galvanized Black

XC 819

GLOSS DARK RED/SILVER



MTB HARDTAIL / SPORT

BENEFITS

- Double-butted aluminium frame with comfortable sports geometry and internal cable routing
- Suntour coil fork
- Universal thread Schwalbe tires
- Shimano 2x8 drivetrain for easy control
- High-performance, gradual pressure Shimano brakes
- Cargo rack, kickstand, and mudguards optional

GEOMETRY

FRAME SIZE	16.0" (S)	18.0" (M)	20" (L)	22" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	406	457	508	559
SEAT TUBE ANGLE (DEGREE)	72.4	72	72	72.4
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
REACH (MM)	372	387	407	421
STACK HEIGHT (MM)	620	639	639	657
HEAD TUBE LENGTH (MM)	100	120	120	140
HEAD TUBE ANGLE (DEGREE)	70	70	70	70
CHAINSTAY LENGTH (MM)	445	445	445	445
BB DROP (MM)	60	60	60	60
WHEELBASE (MM)	1066	1087	1107	1128
HANDLEBAR WIDTH (MM)	720	720	740	740
STEM LENGTH (MM)	70	70	90	90
CRANK LENGTH (MM)	170	175	175	175
SEAT POST LENGTH (MM)	350	350	350	350

SPECIFICATION

FRAMESET

FRAME Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Conical Head Tube, BB BSA 73 mm, IDK dropout, Smooth Welding, Inner cable routing

COLOUR GLOSS DARK RED/SILVER
SIZES 16.0" (S), 18.0" (M), 20" (L), 22" (XL)

DRIVETRAIN

SHIFTER SHIMANO ALTUS SL-M315-2L RapidFire Plus, 2-speed, SHIMANO ALTUS SL-M315-8R RapidFire Plus, 8-speed
FRONT DERAILLEUR SHIMANO FD-M315-TS, TOP SWING, DUAL-PULL
REAR DERAILLEUR SHIMANO ALTUS RD-M310-L
CRANKSET SHIMANO FC-M315, 36-22T
CASSETTE SHIMANO CS-HG31-8, 11-34T
BOTTOM BRACKET SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN KMC Z8.3
PEDALS Marwi SP-610

COMPONENTS

HANDLEBAR ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 740mm, 31.8mm
STEM ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS ONE1 VLG-1661D2N, Lock-On
BRAKES SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE Selle Royal Vivo HRN
SEAT POST ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS Stars J25DH, 32H
TIRES Schwalbe Smart Sam 29x2.10"
SPOKES Sapim Galvanized Black

XC 819 W

GLOSS WHITE/VIOLET/PURPLE



MTB HARDTAIL / SPORT

BENEFITS

- Double-butted aluminium frame with comfortable sports geometry and internal cable routing
- Components and shapes made to fit relaxed ride needs
- Suntour coil spring
- Universal thread Schwalbe tires
- Shimano 2x8 drivetrain for easy control
- High-performance, gradual pressure Shimano brakes
- Cargo rack, kickstand, and mudguards optional

GEOMETRY

FRAME SIZE	16.0" (S)	18.0" (M)
WHEEL SIZE	29	29
SEAT TUBE LENGTH (MM)	406	457
SEAT TUBE ANGLE (DEGREE)	72.4	72
EFFECTIVE TOP TUBE LENGTH (MM)	570	590
REACH (MM)	372	387
STACK HEIGHT (MM)	620	639
HEAD TUBE LENGTH (MM)	100	120
HEAD TUBE ANGLE (DEGREE)	70	70
CHAINSTAY LENGTH (MM)	445	445
BB DROP (MM)	60	60
WHEELBASE (MM)	1066	1087
HANDLEBAR WIDTH (MM)	740/720	740/720
STEM LENGTH (MM)	70	70
CRANK LENGTH (MM)	170	175
SEAT POST LENGTH (MM)	350	350

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Woman Geometry, Conical Head Tube, BB BSA 73 mm, IDK dropout, Smooth Welding, Inner cable routing
COLOUR	GLOSS WHITE/VIOLET/PURPLE
SIZES	16.0" (S), 18.0" (M)

DRIVETRAIN

SHIFTER	SHIMANO ALTUS SL-M315-2L RapidFire Plus, 2-speed, SHIMANO ALTUS SL-M315-8R RapidFire Plus, 8-speed
FRONT DERAILLEUR	SHIMANO FD-M315-TS, TOP SWING, DUAL-PULL
REAR DERAILLEUR	SHIMANO ALTUS RD-M310-L
CRANKSET	SHIMANO FC-M315, 36-22T
CASSETTE	SHIMANO CS-HG31-8, 11-34T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 720mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo DRN
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J25DH, 32H
TIRES	Schwalbe Smart Sam Performance, 29x1.75", ADDIX
SPOKES	Sapim Galvanized Black

X-ROAD Team Issue R

MATTE BLACK/STEALTH CHROME



ROAD & GRAVEL / GRAN FONDO

BENEFITS

- Internal Cable Routing for perfect integration: clean, modern looks without outside tubing or cabling
- 40 mm tires optional
- Schwalbe Tubeless Easy: fast tires with low rolling resistance and higher traction for safe turns and corners
- Quick and precise new electronic groupset Shimano Ultegra Di2 2x12
- DT Swiss ERC 1400 SPLINE®: 47 mm rim high-speed tubeless carbon wheelset
- Aero carbon cockpit combo
- Concealed mounting points to fit mudguards

GEOMETRY

FRAME SIZE	52 cm (S)	54 cm (M)	56 cm (L)	58 cm (XL)
WHEEL SIZE	28	28	28	28
SEAT TUBE LENGTH (MM)	462	482	502	522
SEAT TUBE ANGLE (DEGREE)	73.8	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	531	544	568	590
REACH (MM)	376	379	392	408
STACK HEIGHT (MM)	536	557	578	597
HEAD TUBE LENGTH (MM)	120	140	160	180
HEAD TUBE ANGLE (DEGREE)	71	71.5	72	72
CHAINSTAY LENGTH (MM)	412	412	412	412
BB DROP (MM)	70	70	70	70
WHEELBASE (MM)	990	996	1010	1032
HANDLEBAR WIDTH (MM)	420	420	440	440
STEM LENGTH (MM)	80	90	100	110
CRANK LENGTH (MM)	172.5	172.5	175	175
SEAT POST LENGTH (MM)	380	380	380	380

SPECIFICATION

FRAMESET

FRAME Carbon X-Road Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB865, SH dropout, Thru Axle 12x142 mm, Inner cable routing, Di2 compatible, mudguards ready

HEAD SET ACROS AIX-525, OD56, IS52/28.6, ICR-IS52/40IPS
COLOUR MATTE BLACK/STEALTH CHROME
SIZES 52 cm (S), 54 cm (M), 56 cm (L), 58 cm (XL)

DRIVETRAIN

BOTTOM BRACKET Shimano SM-BB72-41B, BB accessories
CHAIN SHIMANO CN-M8100

COMPONENTS

GRIPS Velo VLF-8111
BRAKES SHIMANO ST-R8170/BR-R8170, hydraulic disc brake
SEAT POST ONE1 Carbon, SP0225380AERO

WHEELS

TIRES Schwalbe Pro One Evo, 28x1.20", ADDIX

X-ROAD Team Issue Di2

GLOSS WHITE/HOLOGRAM BLACK



ROAD & GRAVEL / GRAN FONDO

BENEFITS

- Internal Cable Routing for perfect integration: clean, modern looks without outside tubing or cabling
- 40 mm tires optional
- Schwalbe Tubeless Easy: fast tires with low rolling resistance and higher traction for safe turns and corners
- A brand-new quick and precise electronic shifter set Shimano Ultegra Di2 2x12
- DT Swiss ER 1600 Spline DB32: a 32 mm rim lightweight tubeless-ready wheelset
- ONE1 carbon seat post and carbon cockpit combo
- Concealed mounting points to fit mudguards

GEOMETRY

FRAME SIZE	52 cm (S)	54 cm (M)	56 cm (L)	58 cm (XL)
WHEEL SIZE	28	28	28	28
SEAT TUBE LENGTH (MM)	462	482	502	522
SEAT TUBE ANGLE (DEGREE)	73.8	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	531	544	568	590
REACH (MM)	376	379	392	408
STACK HEIGHT (MM)	536	557	578	597
HEAD TUBE LENGTH (MM)	120	140	160	180
HEAD TUBE ANGLE (DEGREE)	71	71.5	72	72
CHAINSTAY LENGTH (MM)	412	412	412	412
BB DROP (MM)	70	70	70	70
WHEELBASE (MM)	990	996	1010	1032
HANDLEBAR WIDTH (MM)	420	420	440	440
STEM LENGTH (MM)	80	90	100	110
CRANK LENGTH (MM)	172.5	172.5	175	175
SEAT POST LENGTH (MM)	380	380	380	380

SPECIFICATION

FRAMESET

FRAME Carbon X-Road Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB865, SH dropout, Thru Axle 12x142 mm, Inner cable routing, Di2 compatible, mudguards ready

HEAD SET ACROS AIX-525, OD56, IS52/28.6, ICR-IS52/40IPS
COLOUR GLOSS WHITE/HOLOGRAM BLACK
SIZES 52 cm (S), 54 cm (M), 56 cm (L), 58 cm (XL)

DRIVETRAIN

BOTTOM BRACKET BB accessories, Shimano SM-BB72-41B
CHAIN SHIMANO CN-M8100

COMPONENTS

GRIPS Velo VLF-8111
BRAKES SHIMANO ST-R8170/BR-R8170, hydraulic disc brake
SEAT POST ONE1 Carbon, SP0225380AERO

WHEELS

TIRES Schwalbe Pro One Evo, 28x1.20", ADDIX
WHEELSET DT Swiss ER 1600 Spline DB32; 12x100mm, CENTER LOCK, Tubeless, DT Swiss ER 1600 Spline DB32; 12x142mm, CENTER LOCK, Tubeless

X-ROAD Issue

GLOSS BLACK METALLIC/CHROME SILVER/TEAM RED



ROAD & GRAVEL / GRAN FONDO

BENEFITS

- Triple butted aluminium alloy X6; internal cable routing
- 40mm tires optional
- Reliable mechanical groupset Shimano 105 with a broad gear range (2x11)
- ONE1 aluminium seat post aero handlebars
- Concealed mounting points to fit mudguards

GEOMETRY

FRAME SIZE	52 cm (S)	54 cm (M)	56 cm (L)	58 cm (XL)
WHEEL SIZE	28	28	28	28
SEAT TUBE LENGTH (MM)	490	510	530	550
SEAT TUBE ANGLE (DEGREE)	73.8	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	530	540	570	590
REACH (MM)	367	371	384	401
STACK HEIGHT (MM)	558	569	606	616
HEAD TUBE LENGTH (MM)	135	145	180	190
HEAD TUBE ANGLE (DEGREE)	71.5	72	73	73
CHAINSTAY LENGTH (MM)	420	420	420	420
BB DROP (MM)	70	70	70	70
WHEELBASE (MM)	992	989	1009	1029
HANDLEBAR WIDTH (MM)	420	420	440	440
STEM LENGTH (MM)	80	90	100	110
CRANK LENGTH (MM)	172.5	172.5	175	175
SEAT POST LENGTH (MM)	350	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race, Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, SH dropout, Inner cable routing, mudguards ready
FORK	X-Road Issue 28", Carbon/alloy rigid, Ahead 1-1/8x1.5", 12x100mm axle
COLOUR	GLOSS BLACK METALLIC/CHROME SILVER/TEAM RED
SIZES	52 cm (S), 54 cm (M), 56 cm (L), 58 cm (XL)

DRIVETRAIN

FRONT DERAILLEUR	SHIMANO 105 FD-R7000-L, DOWN SWING, BRAZED-ON Type
REAR DERAILLEUR	SHIMANO 105 RD-R7000 Shadow
CRANKSET	SHIMANO 105 FC-R7000 Hollowtech II, 52-34T
CASSETTE	SHIMANO CS-HG700-11, 11-34T
BOTTOM BRACKET	SHIMANO BB-R60, BSA, shell 68mm
CHAIN	KMC X11

COMPONENTS

HANDLEBAR	ONE1 Alloy, X-Race Aero, 16° flared, 70mm reach, 31.8mm
STEM	ONE1 Race RAS-D62938 Alloy, 31.8mm, -8°
GRIPS	Velo VLF-8111
BRAKES	SHIMANO 105 ST-R7025/BR-R7070, hydraulic disc brake
SADDLE	Fizik Aliante R5
SEAT POST	ONE1 Race Alloy, SP C255, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-RS470, 28H, CENTER LOCK, 12x100mm THRU Type AXLE
REAR HUB	SHIMANO FH-RS470, 28H, CENTER LOCK, 12x142mm THRU Type AXLE
TIRES	Schwalbe One Performance RaceGuard, 28x1.20", ADDIX Sapim Race, Stainless Black
SPOKES	

X-ROAD Team Elite

GLOSS DARK RED/CHROME



ROAD & GRAVEL / GRAN FONDO

BENEFITS

- Internal Cable Routing for perfect integration: clean, modern looks without outside tubing or cabling
- 40 mm tires optional
- Schwalbe Pro One Evo 30-622 Addix higher traction tires for safe turns and corners
- Reliable mechanical groupset Shimano 105
- DT Swiss C 1800 Spline DB23 tubeless ready wheelset
- ONE1 carbon seat post and aluminium aero handlebars
- Concealed mounting points to fit mudguards

GEOMETRY

FRAME SIZE	52 cm (S)	54 cm (M)	56 cm (L)	58 cm (XL)
WHEEL SIZE	28	28	28	28
SEAT TUBE LENGTH (MM)	462	482	502	522
SEAT TUBE ANGLE (DEGREE)	73.8	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	531	544	568	590
REACH (MM)	376	379	392	408
STACK HEIGHT (MM)	536	557	578	597
HEAD TUBE LENGTH (MM)	120	140	160	180
HEAD TUBE ANGLE (DEGREE)	71	71.5	72	72
CHAINSTAY LENGTH (MM)	412	412	412	412
BB DROP (MM)	70	70	70	70
WHEELBASE (MM)	990	996	1010	1032
HANDLEBAR WIDTH (MM)	420	420	440	440
STEM LENGTH (MM)	80	90	100	110
CRANK LENGTH (MM)	172.5	172.5	175	175
SEAT POST LENGTH (MM)	380	380	380	380

SPECIFICATION

FRAMESET

FRAME	Carbon X-Road Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB865, SH dropout, Thru Axle 12x142 mm, Inner cable routing, Di2 compatible, mudguards ready
HEAD SET	ACROS AIX-525, OD56, IS52/28.6, ICR-IS52/40IPS
COLOUR	GLOSS DARK RED/CHROME
SIZES	52 cm (S), 54 cm (M), 56 cm (L), 58 cm (XL)

DRIVETRAIN

FRONT DERAILLEUR	SHIMANO 105 FD-R7000-L, DOWN SWING, BRAZED-ON Type
REAR DERAILLEUR	SHIMANO 105 RD-R7000 Shadow
CRANKSET	SHIMANO 105 FC-R7000 Hollowtech II, 52-34T
CASSETTE	SHIMANO CS-HG700-11, 11-34T
BOTTOM BRACKET	SHIMANO BB-RS500 PressFit, shell 41x86.5mm, BB accessories
CHAIN	KMC X11

COMPONENTS

HANDLEBAR	ONE1 Alloy, X-Race Aero, 16° flared, 70mm reach, 31.8mm
STEM	ONE1 TDS-660 Alloy, 31.8mm, 7°, 80MM
GRIPS	Velo VLF-8111
BRAKES	SHIMANO ST-R7025/BR-R7070, hydraulic disc brake
SADDLE	Fizik Aliante R5
SEAT POST	ONE1 Carbon, SP0225380AERO

WHEELS

TIRES	Schwalbe Pro One Evo, 28x1.20", ADDIX
WHEELSET	DT Swiss C 1800 Spline DB23; 12x142mm, CENTER LOCK, Tubeless, DT Swiss C 1800 Spline DB23; 12x100mm, CENTER LOCK, Tubeless

X-ROAD Team Issue

GLOSS BLACK RAINBOW/HOLOGRAM CHROME



ROAD & GRAVEL / GRAN FONDO

BENEFITS

- Internal Cable Routing for perfect integration: clean, modern looks without outside tubing or cabling
- 40 mm tires optional
- Schwalbe Pro One Evo 30-622 Addix higher traction tires for safe turns and corners
- Shimano Ultegra racing-style mechanical groupset
- DT Swiss ER 1600 Spline DB32: a 32 mm rim lightweight tubeless-ready wheelset
- ONE1 carbon seat post and carbon cockpit combo
- Concealed mounting points to fit mudguards

GEOMETRY

FRAME SIZE	52 cm (S)	54 cm (M)	56 cm (L)	58 cm (XL)
WHEEL SIZE	28	28	28	28
SEAT TUBE LENGTH (MM)	462	482	502	522
SEAT TUBE ANGLE (DEGREE)	73.8	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	531	544	568	590
REACH (MM)	376	379	392	408
STACK HEIGHT (MM)	536	557	578	597
HEAD TUBE LENGTH (MM)	120	140	160	180
HEAD TUBE ANGLE (DEGREE)	71	71.5	72	72
CHAINSTAY LENGTH (MM)	412	412	412	412
BB DROP (MM)	70	70	70	70
WHEELBASE (MM)	990	996	1010	1032
HANDLEBAR WIDTH (MM)	420	420	440	440
STEM LENGTH (MM)	80	90	100	110
CRANK LENGTH (MM)	172.5	172.5	175	175
SEAT POST LENGTH (MM)	380	380	380	380

SPECIFICATION

FRAMESET

FRAME Carbon X-Road Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB865, SH dropout, Thru Axle 12x142 mm, Inner cable routing, Di2 compatible, mudguards ready

HEAD SET ACROS AIX-525, OD56, IS52/28.6, ICR-IS52/40IPS
COLOUR GLOSS BLACK RAINBOW/HOLOGRAM CHROME
SIZES 52 cm (S), 54 cm (M), 56 cm (L), 58 cm (XL)

DRIVETRAIN

FRONT DERAILLEUR SHIMANO ULTEGRA FD-R8000, DOWN SWING, BRAZED-ON Type

REAR DERAILLEUR SHIMANO GRX RD-RX810 Shadow Plus

CRANKSET SHIMANO ULTEGRA FC-R8000 Hollowtech II 50-34T

CASSETTE SHIMANO CS-HG700-11, 11-34T

BOTTOM BRACKET SHIMANO BB-RS500 PressFit, shell 41x86.5mm, BB accessories

CHAIN KMC X11L

COMPONENTS

GRIPS Velo VLF-8111

BRAKES SHIMANO ST-R8020/BR-R8070, hydraulic disc brake

SEAT POST ONE1 Carbon, SP0225380AERO

WHEELS

TIRES Schwalbe Pro One Evo, 28x1.20", ADDIX
WHEELSET DT Swiss ER 1600 Spline DB32; 12x142mm, CENTER LOCK, Tubeless, DT Swiss ER 1600 Spline DB32; 12x100mm, CENTER LOCK, Tubeless

X-ROAD Comp

GLOSS WHITE/HOLOGRAM BLACK



ROAD & GRAVEL / GRAN FONDO

BENEFITS

- Triple butted aluminium alloy X6; internal cable routing
- Carbon fork for less weight and more comfort
- 40 mm tires optional
- Durable tires: Schwalbe Lugano II KevlarGuard, 700x32c
- Shimano Tiagra 2x10 road groupset
- Lightweight aluminium accessories ONE1; aero handlebars
- Concealed mounting points to fit mudguards

GEOMETRY

FRAME SIZE	52 cm (S)	54 cm (M)	56 cm (L)	58 cm (XL)
WHEEL SIZE	28	28	28	28
SEAT TUBE LENGTH (MM)	490	510	530	550
SEAT TUBE ANGLE (DEGREE)	73.8	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	530	540	570	590
REACH (MM)	367	371	384	401
STACK HEIGHT (MM)	558	569	606	616
HEAD TUBE LENGTH (MM)	135	145	180	190
HEAD TUBE ANGLE (DEGREE)	71.5	72	73	73
CHAINSTAY LENGTH (MM)	420	420	420	420
BB DROP (MM)	70	70	70	70
WHEELBASE (MM)	992	989	1009	1029
HANDLEBAR WIDTH (MM)	420	420	440	440
STEM LENGTH (MM)	80	90	100	110
CRANK LENGTH (MM)	172.5	172.5	175	175
SEAT POST LENGTH (MM)	350	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race, Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, SH dropout, Inner cable routing, mudguards ready
FORK	X-Road Comp 28", Carbon/alloy rigid, Ahead 1-1/8x1.5", 12x100mm axle
COLOUR	GLOSS WHITE/HOLOGRAM BLACK
SIZES	52 cm (S), 54 cm (M), 56 cm (L), 58 cm (XL)

DRIVETRAIN

FRONT DERAILLEUR	Shimano Tiagra 4700
REAR DERAILLEUR	Shimano Tiagra 4700 GS
CASSETTE	SHIMANO CS-HG500-10, 11-34T
CHAIN	KMC X10

COMPONENTS

HANDLEBAR	ONE1 Alloy, X-Race Aero, 16° flared, 70mm reach, 31.8mm
STEM	ONE1 Race RAS-D62938 Alloy, 31.8mm, -8°
GRIPS	Velo VLF-8111
SADDLE	Fizik Aliante R5
SEAT POST	ONE1 Race Alloy, SP C255, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-RS470, 28H, CENTER LOCK, 12x100mm THRU Type AXLE
REAR HUB	SHIMANO FH-RS470, 28H, CENTER LOCK, 12x142mm THRU Type AXLE
TIRES	Schwalbe Lugano II KevlarGuard, 700x32C
SPOKES	Sapim Race, Stainless Black

X-Road Team Issue Di2 GR

MATTE BLACK/OLIVE METALLIC



GRAPHIC SIMULATION/DHXL / REAL PICTURE.S00H

ROAD & GRAVEL / GRAVEL

BENEFITS

- Internal Cable Routing for perfect integration: clean, modern looks without outside tubing or cabling
- Carbon handlebar&stem cockpit combo
- Concealed mounting points to fit mudguards
- Schwalbe G-One tires: fast on tarmac, safe on gravel roads
- Wide gear range: 1x11 with 11-42t cassette

GEOMETRY

FRAME SIZE	52 cm (S)	54 cm (M)	56 cm (L)	58 cm (XL)
WHEEL SIZE	28	28	28	28
SEAT TUBE LENGTH (MM)	462	482	502	522
SEAT TUBE ANGLE (DEGREE)	73.8	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	531	544	568	590
REACH (MM)	376	379	392	408
STACK HEIGHT (MM)	536	557	578	597
HEAD TUBE LENGTH (MM)	120	140	160	180
HEAD TUBE ANGLE (DEGREE)	71	71.5	72	72
CHAINSTAY LENGTH (MM)	412	412	412	412
BB DROP (MM)	70	70	70	70
WHEELBASE (MM)	990	996	1010	1032
HANDLEBAR WIDTH (MM)	420	420	440	440
STEM LENGTH (MM)	80	90	100	110
CRANK LENGTH (MM)	172.5	172.5	175	175
SEAT POST LENGTH (MM)	380	380	380	380

SPECIFICATION

FRAMESET

FRAME	Carbon X-Road Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB865, SH dropout, Thru Axle 12x142 mm, Inner cable routing, Di2 compatible, mudguards ready
HEAD SET	ACROS AIX-525, OD56, IS52/28.6, ICR-IS52/40IPS
COLOUR	MATTE BLACK/OLIVE METALLIC
SIZES	52 cm (S), 54 cm (M), 56 cm (L), 58 cm (XL)

DRIVETRAIN

CRANKSET	SHIMANO GRX FC-RX810 Hollowtech II, 42T
CASSETTE	SHIMANO CS-M7000-11, 11-42T
BOTTOM BRACKET	SHIMANO BB-RS500 PressFit, shell 41x86.5mm, BB accessories
CHAIN	KMC X11

COMPONENTS

GRIPS	Velo VLF-8111
BRAKES	SHIMANO ST-RX815/BR-RX810, hydraulic disc brake
SEAT POST	ONE1 Carbon, SP0225380AERO

WHEELS

TIRES	Schwalbe G-One Allround RaceGuard, 28x1.50"
-------	---

X-ROAD Comp GR

MATTE OLIVE METALLIC



ROAD & GRAVEL / GRAVEL

BENEFITS

- Concealed mounting points to fit mudguards
- 40mm tires frame clearance
- Wide range of gears for fast asphalt rides and off-road climbs
- Comfortable bar tape with perfect grip even in wet conditions
- Ergonomic aero-shaped handlebars for long spins

GEOMETRY

FRAME SIZE	52 cm (S)	54 cm (M)	56 cm (L)	58 cm (XL)
WHEEL SIZE	28	28	28	28
SEAT TUBE LENGTH (MM)	490	510	530	550
SEAT TUBE ANGLE (DEGREE)	73.8	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	530	540	570	590
REACH (MM)	367	371	384	401
STACK HEIGHT (MM)	558	569	606	616
HEAD TUBE LENGTH (MM)	135	145	180	190
HEAD TUBE ANGLE (DEGREE)	71.5	72	73	73
CHAINSTAY LENGTH (MM)	420	420	420	420
BB DROP (MM)	70	70	70	70
WHEELBASE (MM)	992	989	1009	1029
HANDLEBAR WIDTH (MM)	420	420	440	440
STEM LENGTH (MM)	80	90	100	110
CRANK LENGTH (MM)	172.5	172.5	175	175
SEAT POST LENGTH (MM)	350	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race, Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, SH dropout, Inner cable routing, mudguards ready
FORK	X-Road Comp GR 28", Carbon/alloy rigid, Ahead 1-1/8x1.5", 12x100mm axle
COLOUR	MATTE OLIVE METALLIC
SIZES	52 cm (S), 54 cm (M), 56 cm (L), 58 cm (XL)

DRIVETRAIN

REAR DERAILLEUR	SHIMANO GRX RD-RX400 Shadow Plus
CRANKSET	SHIMANO GRX FC-RX600, 40T
CASSETTE	SHIMANO CS-M4100-10, 11-42T
CHAIN	KMC X10

COMPONENTS

HANDLEBAR	ONE1 Alloy, X-Race Aero, 16° flared, 70mm reach, 31.8mm
GRIPS	Velo VLF-8111
BRAKES	SHIMANO ST-RX400/BR-RX400, hydraulic disc brake
SADDLE	Fizik Aliante R5
SEAT POST	ONE1 Race Alloy, SP C255, 27.2mm
FRONT HUB	SHIMANO HB-RS470, 28H, CENTER LOCK, 12x100mm THRU Type AXLE
REAR HUB	SHIMANO FH-RS470, 28H, CENTER LOCK, 12x142mm THRU Type AXLE
TIRES	Schwalbe G-One Allround RaceGuard, 28x1.50"
SPOKES	Sapim Race, Stainless Black

X-ROAD Team Comp GR

MATTE TROOPER GREEN



ROAD & GRAVEL / GRAVEL

BENEFITS

- Internal Cable Routing for perfect integration: clean, modern looks without outside tubing or cabling
- Schwalbe G-One 40mm tubeless tires with a pattern fast on tarmac and safe in the woods and fields
- Broad gear range, with the single-chainring setup and a 11x42 cassette to climb the steepest hills
- ONE1 carbon seat post and aluminium aero handlebars
- DT Swiss C 1800 Spline DB23 tubeless ready wheelset
- Concealed mounting points to fit mudguards

GEOMETRY

FRAME SIZE	52 cm (S)	54 cm (M)	56 cm (L)	58 cm (XL)
WHEEL SIZE	28	28	28	28
SEAT TUBE LENGTH (MM)	462	482	502	522
SEAT TUBE ANGLE (DEGREE)	73.8	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	531	544	568	590
REACH (MM)	376	379	392	408
STACK HEIGHT (MM)	536	557	578	597
HEAD TUBE LENGTH (MM)	120	140	160	180
HEAD TUBE ANGLE (DEGREE)	71	71.5	72	72
CHAINSTAY LENGTH (MM)	412	412	412	412
BB DROP (MM)	70	70	70	70
WHEELBASE (MM)	990	996	1010	1032
HANDLEBAR WIDTH (MM)	420	420	440	440
STEM LENGTH (MM)	80	90	100	110
CRANK LENGTH (MM)	172.5	172.5	175	175
SEAT POST LENGTH (MM)	380	380	380	380

SPECIFICATION

FRAMESET

FRAME	Carbon X-Road Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB865, SH dropout, Thru Axle 12x142 mm, Inner cable routing, Di2 compatible, mudguards ready
HEAD SET	ACROS AIX-525, OD56, IS52/28.6, ICR-IS52/40IPS
COLOUR	MATTE TROOPER GREEN
SIZES	52 cm (S), 54 cm (M), 56 cm (L), 58 cm (XL)

DRIVETRAIN

REAR DERAILLEUR	SHIMANO GRX RD-RX812 Shadow Plus
CRANKSET	SHIMANO GRX FC-RX600, 40T
CASSETTE	SunRace CS-MS7-11, 11-42T
BOTTOM BRACKET	SHIMANO BB-RS500 PressFit, shell 41x86.5mm, BB accessories
CHAIN	KMC X11

COMPONENTS

HANDLEBAR	ONE1 Alloy, X-Race Aero, 16° flared, 70mm reach, 31.8mm
STEM	ONE1 TDS-660 Alloy, 31.8mm, 7°, 80MM
GRIPS	Velo VLF-8111
BRAKES	SHIMANO ST-RX600/BR-RX400, hydraulic disc brake, SHIMANO BL-RX600-L/BR-RX400, hydraulic disc brake
SADDLE	Fizik Aliante R5
SEAT POST	ONE1 Carbon, SP0225380AERO
WHEELS	
TIRES	Schwalbe G-One Allround RaceGuard, 28x1.50"
WHEELSET	DT Swiss G 1800 Spline DB25; 12x142mm, CENTER LOCK, Tubeless, DT Swiss G 1800 Spline DB25; 12x100mm, CENTER LOCK, Tubeless

X-ROAD Elite GR

MATTE BLACK/TROOPER GREEN



ROAD & GRAVEL / GRAVEL

BENEFITS

- Triple butted aluminium alloy X6; internal cable routing
- Fast tread Schwalbe G-One Allround RaceGuard 40 mm tires
- Shimano GRX 1x11 broad gear range groupset
- Aluminium aero handlebars ONE1
- Concealed mounting points to fit mudguards

GEOMETRY

FRAME SIZE	52 cm (S)	54 cm (M)	56 cm (L)	58 cm (XL)
WHEEL SIZE	28	28	28	28
SEAT TUBE LENGTH (MM)	490	510	530	550
SEAT TUBE ANGLE (DEGREE)	73.8	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	530	540	570	590
REACH (MM)	367	371	384	401
STACK HEIGHT (MM)	558	569	606	616
HEAD TUBE LENGTH (MM)	135	145	180	190
HEAD TUBE ANGLE (DEGREE)	71.5	72	73	73
CHAINSTAY LENGTH (MM)	420	420	420	420
BB DROP (MM)	70	70	70	70
WHEELBASE (MM)	992	989	1009	1029
HANDLEBAR WIDTH (MM)	420	420	440	440
STEM LENGTH (MM)	80	90	100	110
CRANK LENGTH (MM)	172.5	172.5	175	175
SEAT POST LENGTH (MM)	350	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race, Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, SH dropout, Inner cable routing, mudguards ready
FORK	X-Road Elite 28", Carbon/alloy rigid, Ahead 1-1/8x1.5", 12x100mm axle
COLOUR	MATTE BLACK/TROOPER GREEN
SIZES	52 cm (S), 54 cm (M), 56 cm (L), 58 cm (XL)

DRIVETRAIN

REAR DERAILLEUR	SHIMANO GRX RD-RX812 Shadow Plus
CRANKSET	SHIMANO GRX FC-RX600, 40T
CASSETTE	SunRace CS-MS7-11, 11-42T
CHAIN	KMC X11

COMPONENTS

HANDLEBAR	ONE1 Alloy, X-Race Aero, 16° flared, 70mm reach, 31.8mm
STEM	ONE1 Race RAS-D62938 Alloy, 31.8mm, -8°
GRIPS	Velo VLF-8111
BRAKES	SHIMANO ST-RX600/BR-RX400, hydraulic disc brake, SHIMANO BL-RX600/BR-RX400, hydraulic disc brake
SADDLE	Fizik Aliante R5
SEAT POST	ONE1 Race Alloy, SP C255, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-RS470, 28H, CENTER LOCK, 12x100mm THRU Type AXLE
REAR HUB	SHIMANO FH-RS470, 28H, CENTER LOCK, 12x142mm THRU Type AXLE
TIRES	Schwalbe G-One Allround RaceGuard, 28x1.50"
SPOKES	Sapim Race, Stainless Black

STK 700

GLOSS BLACK



URBAN

BENEFITS

- Lightweight aluminium frame with internal cable routing
- Front hub Shimano-made dynamo
- Full equipment: mudguards, lights, cargo rack, kickstand, chain guard, suspension seat post
- Shimano Deore and XT groupsets 3x10 speed
- Schwalbe Road Cruiser 700x40c tires
- Comfortable, Italian-made Selle Royal Ariel saddle

GEOMETRY

FRAME SIZE	19.0"(L)	21.0"(XL)	23.0" (XXL)
WHEEL SIZE	28	28	28
SEAT TUBE LENGTH (MM)	483	533	584
SEAT TUBE ANGLE (DEGREE)	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	600	610	630
REACH (MM)	420	423	437
STACK HEIGHT (MM)	606	609	630
HEAD TUBE LENGTH (MM)	160	160	180
HEAD TUBE ANGLE (DEGREE)	70	71	71.5
CHAINSTAY LENGTH (MM)	445	445	445
BB DROP (MM)	65	65	65
WHEELBASE (MM)	1115	1093	1124
HANDLEBAR WIDTH (MM)	620	620	620
STEM LENGTH (MM)	90	110	110
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Gentleman, Trekking Geometry, Disc Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA TH-807ST Semi-Cartridge, 1-1/8"
FORK	ZOOM 187D AMS, 1-1/8", Coil, QR Type, 60mm travel
COLOUR	GLOSS BLACK
SIZES	19.0"(L), 21.0"(XL), 23.0" (XXL)

DRIVETRAIN

SHIFTER	SHIMANO XT SL-T8000 RapidFire Plus, 3-speed, SHIMANO XT SL-T8000 RapidFire Plus, 10-speed
FRONT DERAILLEUR	SHIMANO DEORE FD-T6000-L-3, TOP SWING, DOWN-PULL
REAR DERAILLEUR	SHIMANO XT RD-T8000 Shadow
CRANKSET	SHIMANO FC-T521L 48-36-26T
CASSETTE	SHIMANO CS-HG500-10, 11-34T
BOTTOM BRACKET	SHIMANO BB-ES300, BSA, shell 73mm
CHAIN	KMC X10
PEDALS	Marwi SP-823

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-320BT, 9° backsweep, 20mm rise, 620mm, 31.8mm
STEM	ONE1 CQS-JD660 Alloy, 31.8mm, -10°/+80°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT401/BR-MT410, hydraulic disc brake
SADDLE	Selle Royal Ariel
SEAT POST	ONE1 Alloy, SPS 405, 27.2mm
WHEELS	
FRONT HUB	SHIMANO DH-3D37-QR, 36H, CENETR LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 36H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J19DC, 36H
TIRES	Schwalbe Road Cruiser, 700x40C, Reflective tape
SPOKES	Sapim Leader, Stainless Black

STK 700 L

GLOSS BLACK



URBAN

BENEFITS

- Lightweight aluminium frame with internal cable routing
- Front hub Shimano-made dynamo
- Full equipment: mudguards, lights, cargo rack, kickstand, chain guard, suspension seat post
- Shimano Deore and XT groupsets
- Schwalbe Road Cruiser 700x40c tires
- Comfortable, Italian-made saddle Selle Royal Ariel

GEOMETRY

FRAME SIZE	19.0"(L)	21.0"(XL)	23.0" (XXL)
WHEEL SIZE	28	28	28
SEAT TUBE LENGTH (MM)	483	533	584
SEAT TUBE ANGLE (DEGREE)	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	600	610	630
REACH (MM)	420	423	437
STACK HEIGHT (MM)	606	609	630
HEAD TUBE LENGTH (MM)	160	160	180
HEAD TUBE ANGLE (DEGREE)	70	71	71.5
CHAINSTAY LENGTH (MM)	445	445	445
BB DROP (MM)	65	65	65
WHEELBASE (MM)	1115	1093	1124
HANDLEBAR WIDTH (MM)	620	620	620
STEM LENGTH (MM)	90	110	110
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Lady Low Entry, Trekking Geometry, Disc Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA TH-807ST Semi-Cartridge, 1-1/8"
FORK	ZOOM 187D AMS, 1-1/8", Coil, QR Type, 60mm travel
COLOUR	GLOSS BLACK
SIZES	19.0"(L), 21.0"(XL), 23.0" (XXL)

DRIVETRAIN

SHIFTER	SHIMANO XT SL-T8000 RapidFire Plus, 3-speed, SHIMANO XT SL-T8000 RapidFire Plus, 10-speed
FRONT DERAILLEUR	SHIMANO DEORE FD-T6000-L-3, TOP SWING, DOWN-PULL
REAR DERAILLEUR	SHIMANO XT RD-T8000 Shadow
CRANKSET	SHIMANO FC-T521L 48-36-26T
CASSETTE	SHIMANO CS-HG500-10, 11-34T
BOTTOM BRACKET	SHIMANO BB-ES300, BSA, shell 73mm
CHAIN	KMC X10
PEDALS	Marwi SP-823

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-320BT, 9° backsweep, 20mm rise, 620mm, 31.8mm
STEM	ONE1 CQS-JD660 Alloy, 31.8mm, -10°/+80°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT401/BR-MT410, hydraulic disc brake
SADDLE	Selle Royal Ariel
SEAT POST	ONE1 Alloy, SPS 405, 27.2mm
WHEELS	
FRONT HUB	SHIMANO DH-3D37-QR, 36H, CENETR LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 36H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J19DC, 36H
TIRES	Schwalbe Road Cruiser, 700x40C, Reflective tape
SPOKES	Sapim Leader, Stainless Black

STK 500

MATTE GREY/GREEN



BENEFITS

- Lightweight aluminium frame with internal cable routing
- Front hub Shimano-made dynamo
- Full equipment: mudguards, lights, cargo rack, kickstand, chain guard, suspension seat post
- Shimano Deore/Acera 3x9
- Schwalbe Road Cruiser 700x40c tires
- Comfortable, Italian-made saddle Selle Royal Rio Plus

GEOMETRY

FRAME SIZE	19.0"(L)	21.0"(XL)	23.0" (XXL)
WHEEL SIZE	28	28	28
SEAT TUBE LENGTH (MM)	483	533	584
SEAT TUBE ANGLE (DEGREE)	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	600	610	630
REACH (MM)	420	423	437
STACK HEIGHT (MM)	606	609	630
HEAD TUBE LENGTH (MM)	160	160	180
HEAD TUBE ANGLE (DEGREE)	70	71	71.5
CHAINSTAY LENGTH (MM)	445	445	445
BB DROP (MM)	65	65	65
WHEELBASE (MM)	1115	1093	1124
HANDLEBAR WIDTH (MM)	620	620	620
STEM LENGTH (MM)	90	110	110
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Gentleman, Trekking Geometry, Disc Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA TH-807ST Semi-Cartridge, 1-1/8"
FORK	ZOOM 187D AMS, 1-1/8", Coil, QR Type, 60mm travel
COLOUR	MATTE GREY/GREEN
SIZES	19.0"(L), 21.0"(XL), 23.0" (XXL)

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
FRONT DERAILLEUR	SHIMANO ACERA FD-T3000, TOP SWING, DUAL-PULL
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	SHIMANO ACERA FC-M371, 48-36-26T
CASSETTE	SHIMANO CS-HG200-9, 11-34T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC X9
PEDALS	Marwi SP-823

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-153BT, 10° backsweep, 30mm rise, 620mm, 25.4mm
STEM	ONE1 MTSC2975 Alloy, 25.4mm, -10°/+50°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Rio Plus
SEAT POST	ONE1 Alloy, SPS 405, 27.2mm

WHEELS

FRONT HUB	SHIMANO DH-3D37-QR, 36H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 36H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J19DC, 36H
TIRES	Schwalbe Road Cruiser, 700x40C, Reflective tape
SPOKES	Sapim Leader, Stainless Black

STK 500 L

MATTE GREY/GREEN



URBAN

BENEFITS

- Lightweight aluminium frame with internal cable routing
- Front hub Shimano-made dynamo
- Full equipment: mudguards, lights, cargo rack, kickstand, chain guard, suspension seat post
- Shimano Deore/Acera 3x9
- Schwalbe Road Cruiser 700x40c tires
- Comfortable, Italian-made saddle Selle Royal Rio Plus

GEOMETRY

FRAME SIZE	19.0"(L)	21.0"(XL)	23.0" (XXL)
WHEEL SIZE	28	28	28
SEAT TUBE LENGTH (MM)	483	533	584
SEAT TUBE ANGLE (DEGREE)	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	600	610	630
REACH (MM)	420	423	437
STACK HEIGHT (MM)	606	609	630
HEAD TUBE LENGTH (MM)	160	160	180
HEAD TUBE ANGLE (DEGREE)	70	71	71.5
CHAINSTAY LENGTH (MM)	445	445	445
BB DROP (MM)	65	65	65
WHEELBASE (MM)	1115	1093	1124
HANDLEBAR WIDTH (MM)	620	620	620
STEM LENGTH (MM)	90	110	110
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Lady Low Entry, Trekking Geometry, Disc Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA TH-807ST Semi-Cartridge, 1-1/8"
FORK	ZOOM 187D AMS, 1-1/8", Coil, QR Type, 60mm travel
COLOUR	MATTE GREY/GREEN
SIZES	19.0"(L), 21.0"(XL), 23.0" (XXL)

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
FRONT DERAILLEUR	SHIMANO ACERA FD-T3000, TOP SWING, DUAL-PULL
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	SHIMANO ACERA FC-M371, 48-36-26T
CASSETTE	SHIMANO CS-HG200-9, 11-34T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC X9
PEDALS	Marwi SP-823

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-153BT, 10° backsweep, 30mm rise, 620mm, 25.4mm
STEM	ONE1 MTSC2975 Alloy, 25.4mm, -10°/+50°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Rio
SEAT POST	ONE1 Alloy, SPS 405, 27.2mm

WHEELS

FRONT HUB	SHIMANO DH-3D37-QR, 36H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 36H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J19DC, 36H
TIRES	Schwalbe Road Cruiser, 700x40C, Reflective tape
SPOKES	Sapim Leader, Stainless Black

STK 400

GLOSS WHITE/SILVER



URBAN

BENEFITS

- Lightweight aluminium frame with internal cable routing
- Front hub Shimano-made dynamo
- Full equipment: mudguards, lights, cargo rack, kickstand, chain guard, suspension seat post
- Shimano 3x8
- Schwalbe Road Cruiser 700x40c tires
- Comfortable, Italian-made saddle Selle Royal Rio Plus

GEOMETRY

FRAME SIZE	19.0"(L)	21.0"(XL)	23.0" (XXL)
WHEEL SIZE	28	28	28
SEAT TUBE LENGTH (MM)	483	533	584
SEAT TUBE ANGLE (DEGREE)	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	600	610	630
REACH (MM)	420	423	437
STACK HEIGHT (MM)	606	609	630
HEAD TUBE LENGTH (MM)	160	160	180
HEAD TUBE ANGLE (DEGREE)	70	71	71.5
CHAINSTAY LENGTH (MM)	445	445	445
BB DROP (MM)	65	65	65
WHEELBASE (MM)	1115	1093	1124
HANDLEBAR WIDTH (MM)	620	620	620
STEM LENGTH (MM)	90	110	110
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Gentleman, Trekking Geometry, Disc Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA TH-807ST Semi-Cartridge, 1-1/8"
FORK	ZOOM 187D AMS, 1-1/8", Coil, QR Type, 60mm travel
COLOUR	GLOSS WHITE/SILVER
SIZES	19.0"(L), 21.0"(XL), 23.0" (XXL)

DRIVETRAIN

FRONT DERAILLEUR	SHIMANO TX FD-TX800-TS3, TOP SWING, DUAL-PULL
CRANKSET	SHIMANO FC-TY501, 48-38-28T
CASSETTE	SHIMANO CS-HG31-8, 11-34T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-872N

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-153BT, 10° backsweep, 30mm rise, 620mm, 25.4mm
STEM	ONE1 MTSC2975 Alloy, 25.4mm, -10°/+50°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO ST-EF505/BR-MT200, hydraulic disc brake, SHIMANO ST-EF505-8R/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Rio Plus
SEAT POST	ONE1 Alloy, SP SC372, 27.2

WHEELS

FRONT HUB	SHIMANO DH-3D37-QR, 36H, CENETR LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 36H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J19DC, 36H
TIRES	Schwalbe Road Cruiser, 700x40C, Reflective tape
SPOKES	Sapim Leader, Stainless Black

STK 400 L

GLOSS WHITE/SILVER



URBAN

BENEFITS

- Lightweight aluminium frame with internal cable routing
- Front hub Shimano-made dynamo
- Full equipment: mudguards, lights, cargo rack, kickstand, chain guard, suspension seat post
- Shimano 3x9 setup
- Schwalbe Road Cruiser 700x40c tires
- Comfortable, Italian-made saddle Selle Royal Rio Plus

GEOMETRY

FRAME SIZE	19.0"(L)	21.0"(XL)	23.0" (XXL)
WHEEL SIZE	28	28	28
SEAT TUBE LENGTH (MM)	483	533	584
SEAT TUBE ANGLE (DEGREE)	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	600	610	630
REACH (MM)	420	423	437
STACK HEIGHT (MM)	606	609	630
HEAD TUBE LENGTH (MM)	160	160	180
HEAD TUBE ANGLE (DEGREE)	70	71	71.5
CHAINSTAY LENGTH (MM)	445	445	445
BB DROP (MM)	65	65	65
WHEELBASE (MM)	1115	1093	1124
HANDLEBAR WIDTH (MM)	620	620	620
STEM LENGTH (MM)	90	110	110
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Lady Low Entry, Trekking Geometry, Disc Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA TH-807ST Semi-Cartridge, 1-1/8"
FORK	ZOOM 187D AMS, 1-1/8", Coil, QR Type, 60mm travel
COLOUR	GLOSS WHITE/SILVER
SIZES	19.0"(L), 21.0"(XL), 23.0" (XXL)

DRIVETRAIN

FRONT DERAILLEUR	SHIMANO TX FD-TX800-TS3, TOP SWING, DUAL-PULL
CRANKSET	SHIMANO FC-TY501, 48-38-28T
CASSETTE	SHIMANO CS-HG31-8, 11-34T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-872N

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-153BT, 10° backsweep, 30mm rise, 620mm, 25.4mm
STEM	ONE1 MTSC2975 Alloy, 25.4mm, -10°/+50°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO ST-EF505/BR-MT200, hydraulic disc brake, SHIMANO ST-EF505-8R/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Rio
SEAT POST	ONE1 Alloy, SP SC372, 27.2

WHEELS

FRONT HUB	SHIMANO DH-3D37-QR, 36H, CENETR LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 36H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J19DC, 36H
TIRES	Schwalbe Road Cruiser, 700x40C, Reflective tape
SPOKES	Sapim Leader, Stainless Black

STK 100

MATTE DARK BLUE



URBAN

BENEFITS

- Lightweight aluminium frame with internal cable routing
- Front hub Shimano-made dynamo
- Full equipment: mudguards, lights, cargo rack, kickstand, chain guard, suspension seat post
- Shimano 3x7 setup
- Schwalbe Road Cruiser 700x40c tires
- Comfortable, Italian-made saddle Selle Royal Rio

GEOMETRY

FRAME SIZE	19.0"(L)	21.0"(XL)	23.0" (XXL)
WHEEL SIZE	28	28	28
SEAT TUBE LENGTH (MM)	483	533	584
SEAT TUBE ANGLE (DEGREE)	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	600	610	630
REACH (MM)	420	423	437
STACK HEIGHT (MM)	606	609	630
HEAD TUBE LENGTH (MM)	160	160	180
HEAD TUBE ANGLE (DEGREE)	70	71	71.5
CHAINSTAY LENGTH (MM)	445	445	445
BB DROP (MM)	65	65	65
WHEELBASE (MM)	1115	1093	1124
HANDLEBAR WIDTH (MM)	620	620	620
STEM LENGTH (MM)	90	110	110
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Gentleman, Trekking Geometry, V-Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA TH-807ST Semi-Cartridge, 1-1/8"
FORK	STK 100 28", Hi-ten rigid, Ahead 1-1/8", V-Brake, QR Type
COLOUR	MATTE DARK BLUE
SIZES	19.0"(L), 21.0"(XL), 23.0" (XXL)

DRIVETRAIN

SHIFTER	SHIMANO ALTUS ST-EF500-L EZ-Fire Plus, 3-speed, SHIMANO ALTUS ST-EF500-7R EZ-Fire Plus, 7-speed
FRONT DERAILLEUR	SHIMANO TY FD-TY510-TS3, TOP SWING, DUAL-PULL
REAR DERAILLEUR	SHIMANO ALTUS RD-M310-L
CRANKSET	SHIMANO FC-TY501, 48-38-28T
CASSETTE	SHIMANO MF-TZ500-7, 14-28T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-872N

COMPONENTS

HANDLEBAR	ONE1 Hi-ten, MTB-153, 10° backsweep, 30mm rise, 620mm, 25.4mm
STEM	ONE1 MTSC2975 Alloy, 25.4mm, -10°/+50°
GRIPS	Velo VLG-1777D2
SADDLE	Selle Royal Rio Plus
SEAT POST	ONE1 Alloy, SP SC372, 27.2

WHEELS

FRONT HUB	SHIMANO NEXUS DH-C3000-3N-NT, 36H, 100x140mm
REAR HUB	ONE1 KTA51R, 36H, M10x135, FREEWHEEL, NUT Type
RIMS	Stars J19SZ, 36H
TIRES	Schwalbe Road Cruiser, 700x40C, Reflective tape
SPOKES	Sapim Leader, Stainless Black

STK 100 L

MATTE DARK BLUE



URBAN

BENEFITS

- Lightweight aluminium frame with internal cable routing
- Front hub Shimano dynamo
- Full equipment: mudguards, lights, cargo rack, kickstand, chain guard, suspension seat post
- Shimano 3x7 setup
- Schwalbe Road Cruiser 700x40c tires
- Comfortable, Italian-made saddle Selle Royal Rio

GEOMETRY

FRAME SIZE	19.0"(L)	21.0"(XL)	23.0" (XXL)
WHEEL SIZE	28	28	28
SEAT TUBE LENGTH (MM)	483	533	584
SEAT TUBE ANGLE (DEGREE)	73.5	73	73
EFFECTIVE TOP TUBE LENGTH (MM)	600	610	630
REACH (MM)	420	423	437
STACK HEIGHT (MM)	606	609	630
HEAD TUBE LENGTH (MM)	160	160	180
HEAD TUBE ANGLE (DEGREE)	70	71	71.5
CHAINSTAY LENGTH (MM)	445	445	445
BB DROP (MM)	65	65	65
WHEELBASE (MM)	1115	1093	1124
HANDLEBAR WIDTH (MM)	620	620	620
STEM LENGTH (MM)	90	110	110
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	350

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Lady Trapez, Trekking Geometry, V-Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA TH-807ST Semi-Cartridge, 1-1/8"
FORK	STK 100 28", Hi-ten rigid, Ahead 1-1/8", V-Brake, QR Type
COLOUR	MATTE DARK BLUE
SIZES	19.0"(L), 21.0"(XL), 23.0" (XXL)

DRIVETRAIN

SHIFTER	SHIMANO ALTUS ST-EF500-L EZ-Fire Plus, 3-speed, SHIMANO ALTUS ST-EF500-7R EZ-Fire Plus, 7-speed
FRONT DERAILLEUR	SHIMANO TY FD-TY510-TS3, TOP SWING, DUAL-PULL
REAR DERAILLEUR	SHIMANO ALTUS RD-M310-L
CRANKSET	SHIMANO FC-TY501, 48-38-28T
CASSETTE	SHIMANO MF-TZ500-7, 14-28T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-872N

COMPONENTS

HANDLEBAR	ONE1 Hi-ten, MTB-153, 10° backsweep, 30mm rise, 620mm, 25.4mm
STEM	ONE1 MTSC2975 Alloy, 25.4mm, -10°/+50°
GRIPS	Velo VLG-1777D2
SADDLE	Selle Royal Rio
SEAT POST	ONE1 Alloy, SP SC372, 27.2

WHEELS

FRONT HUB	SHIMANO NEXUS DH-C3000-3N-NT, 36H, 100x140mm
REAR HUB	ONE1 KTA51R, 36H, M10x135, FREEWHEEL, NUT Type
RIMS	Stars J19SZ, 36H
TIRES	Schwalbe Road Cruiser, 700x40C, Reflective tape
SPOKES	Sapim Leader, Stainless Black

Team 27 Issue

MATTE BLACK/HOLOGRAM CHROME/TEAM RED



JUNIOR / TEAM

BENEFITS

- New frame from triple-butted aluminium alloy with internal routing and BOOST standard
- Sensitive air suspension fork with easy setting even for very light riders, with remote suspension lockout
- Large range of gears for optimal and healthy progress and riding style
- Lightweight wheelset with butted spokes and high-quality tires with a Kevlar bead
- The new ergonomic cockpit combo and the other components meet the style and height of the young riders
- 1x12 Shimano drivetrain with a large range of gears – also used by professionals
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	13" (XS)	15.5" (S)
WHEEL SIZE	27.5	27.5
SEAT TUBE LENGTH (MM)	330	393
SEAT TUBE ANGLE (DEGREE)	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	545	586
REACH (MM)	381	422
STACK HEIGHT (MM)	569	569
HEAD TUBE LENGTH (MM)	90	90
HEAD TUBE ANGLE (DEGREE)	69	69
CHAINSTAY LENGTH (MM)	420	420
BB DROP (MM)	40	40
WHEELBASE (MM)	1048	1089
HANDLEBAR WIDTH (MM)	660	660
STEM LENGTH (MM)	40	40
CRANK LENGTH (MM)	160	165
SEAT POST LENGTH (MM)	350	350

SPECIFICATION

FRAMESET

HEAD SET	ACROS AZX-212 R5,ZS44/28.6 ZS56/40
COLOUR	MATTE BLACK/HOLOGRAM CHROME/TEAM RED
SIZES	13" (XS), 15.5" (S)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100 Shadow Plus
CRANKSET	ONE1 TAM38J-D32NC, 32T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Race Carbon, PMP12, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-MT410-B, 28H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410-B, 28H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J20S, 28H
TIRES	Schwalbe Racing Ralph Performance TwinSkin TL-Ready, 27.5x2.25", ADDIX/ Schwalbe Racing Ray Performance TwinSkin TL-Ready, 27.5x2.25", ADDIX
SPOKES	Sapim Laser, Stainless Black/ Sapim Laser/ Sapim Race

Team 27 Issue

GLOSS DARK RED/HOLOGRAM CHROME



JUNIOR / TEAM

BENEFITS

- New frame from triple-butted aluminium alloy with internal routing and BOOST standard
- Sensitive air suspension fork with easy setting even for very light riders, with remote suspension lockout
- Large range of gears for optimal and healthy progress and riding style
- Lightweight wheelset with butted spokes and high-quality tires with a Kevlar bead
- The new ergonomic cockpit combo and the other components meet the style and height of the young riders
- 1x12 Shimano drivetrain with a large range of gears – also used by professionals
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	13" (XS)	15.5" (S)
WHEEL SIZE	27.5	27.5
SEAT TUBE LENGTH (MM)	330	393
SEAT TUBE ANGLE (DEGREE)	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	545	586
REACH (MM)	381	422
STACK HEIGHT (MM)	569	569
HEAD TUBE LENGTH (MM)	90	90
HEAD TUBE ANGLE (DEGREE)	69	69
CHAINSTAY LENGTH (MM)	420	420
BB DROP (MM)	40	40
WHEELBASE (MM)	1048	1089
HANDLEBAR WIDTH (MM)	660	660
STEM LENGTH (MM)	40	40
CRANK LENGTH (MM)	160	165
SEAT POST LENGTH (MM)	350	350

SPECIFICATION

FRAMESET

HEAD SET	ACROS AZX-212 R5,ZS44/28.6 ZS56/40
COLOUR	GLOSS DARK RED/HOLOGRAM CHROME
SIZES	13" (XS), 15.5" (S)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100 Shadow Plus
CRANKSET	ONE1 TAM38J-D32NC, 32T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
BOTTOM BRACKET	BB-MT500PA PressFit, shell 41x92mm
CHAIN	SHIMANO CN-M6100

COMPONENTS

GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Race Carbon, PMP12, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-MT410-B, 28H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410-B, 28H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J20S, 28H
TIRES	Schwalbe Racing Ralph Performance TwinSkin TL-Ready, 27.5x2.25", ADDIX/ Schwalbe Racing Ray Performance TwinSkin TL-Ready, 27.5x2.25", ADDIX
SPOKES	Sapim Laser, Stainless Black/ Sapim Laser/ Sapim Race

Team 27 Elite

MATTE BLACK/HOLOGRAM CHROME/TEAM RED



JUNIOR / TEAM

BENEFITS

- A new aluminium frame with a sport geometry, internal routing and integrated headset
- Air suspension fork Suntour with remote suspension lockout
- 1x10 Shimano Deore gear set with a large range of gears for easy intuitive handling
- Lightweight wheelset with butted spokes and quality kevlar tires
- A new aluminium cockpit combo for kids ergonomics
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	13" (XS)	15.5" (S)
WHEEL SIZE	27.5	27.5
SEAT TUBE LENGTH (MM)	330	393
SEAT TUBE ANGLE (DEGREE)	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	545	586
REACH (MM)	381	422
STACK HEIGHT (MM)	569	569
HEAD TUBE LENGTH (MM)	90	90
HEAD TUBE ANGLE (DEGREE)	69	69
CHAINSTAY LENGTH (MM)	420	420
BB DROP (MM)	40	40
WHEELBASE (MM)	1048	1089
HANDLEBAR WIDTH (MM)	660	660
STEM LENGTH (MM)	40	40
CRANK LENGTH (MM)	160	165
SEAT POST LENGTH (MM)	350	350

SPECIFICATION

FRAMESET

COLOUR	MATTE BLACK/HOLOGRAM CHROME/TEAM RED
SIZES	13" (XS), 15.5" (S)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M4100-R RapidFire Plus, 10-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5120 Shadow Plus
CRANKSET	Wheel Top SXB4BL-WM, 32T
CASSETTE	SHIMANO CS-M4100-10, 11-46T
BOTTOM BRACKET	Thun Ibex 120mm, BSA, shell 68mm
CHAIN	KMC X10

COMPONENTS

GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Race Alloy, 27.2mm

WHEELS

FRONT HUB	ONE1 KTTC7F, 28H, M9x100mm, QR Type
REAR HUB	ONE1 KTTC7R, 28H, M10x135, CASSETTE, QR Type
RIMS	Stars J20S, 28H
TIRES	Schwalbe Racing Ralph Performance TwinSkin TL-Ready, 27.5x2.25", ADDIX/ Schwalbe Racing Ray Performance TwinSkin TL-Ready, 27.5x2.25", ADDIX
SPOKES	Sapim Race/ Sapim Laser, Stainless Black/ Sapim Laser

Team 27 Elite

GLOSS DARK RED/HOLOGRAM CHROME



JUNIOR / TEAM

BENEFITS

- A new aluminium frame with a sport geometry, internal routing and integrated headset
- Air suspension fork Suntour with remote suspension lockout
- 1x10 Shimano Deore gear set with a large range of gears for easy intuitive handling
- Lightweight wheelset with butted spokes and quality kevlar tires
- A new aluminium cockpit combo for kids ergonomics
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	13" (XS)	15.5" (S)
WHEEL SIZE	27.5	27.5
SEAT TUBE LENGTH (MM)	330	393
SEAT TUBE ANGLE (DEGREE)	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	545	586
REACH (MM)	381	422
STACK HEIGHT (MM)	569	569
HEAD TUBE LENGTH (MM)	90	90
HEAD TUBE ANGLE (DEGREE)	69	69
CHAINSTAY LENGTH (MM)	420	420
BB DROP (MM)	40	40
WHEELBASE (MM)	1048	1089
HANDLEBAR WIDTH (MM)	660	660
STEM LENGTH (MM)	40	40
CRANK LENGTH (MM)	160	165
SEAT POST LENGTH (MM)	350	350

SPECIFICATION

FRAMESET

COLOUR	GLOSS DARK RED/HOLOGRAM CHROME
SIZES	13" (XS), 15.5" (S)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M4100-R RapidFire Plus, 10-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5120 Shadow Plus
CRANKSET	Wheel Top SXB4BL-WM, 32T
CASSETTE	SHIMANO CS-M4100-10, 11-46T
BOTTOM BRACKET	Thun Ibex 120mm, BSA, shell 68mm
CHAIN	KMC X10

COMPONENTS

GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Race Alloy, 27.2mm

WHEELS

FRONT HUB	ONE1 KTTC7F, 28H, M9x100mm, QR Type
REAR HUB	ONE1 KTTC7R, 28H, M10x135, CASSETTE, QR Type
RIMS	Stars J20S, 28H
TIRES	Schwalbe Racing Ralph Performance TwinSkin TL-Ready, 27.5x2.25", ADDIX/ Schwalbe Racing Ray Performance TwinSkin TL-Ready, 27.5x2.25", ADDIX
SPOKES	Sapim Race/ Sapim Laser, Stainless Black/ Sapim Laser

Team 24

MATTE BLACK/HOLOGRAM CHROME/TEAM RED



JUNIOR / TEAM

BENEFITS

- A new aluminium lightweight frame with a sport geometry and internal routing
- Lightweight Suntour air suspension fork with lockout
- Hydraulic disc brakes for an easy stop on the spot
- A new cockpit combo and other components adjusted for kids
- Lightweight wheels for easy start and control
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	11
WHEEL SIZE	24
SEAT TUBE LENGTH (MM)	280
SEAT TUBE ANGLE (DEGREE)	73
EFFECTIVE TOP TUBE LENGTH (MM)	500
REACH (MM)	347
STACK HEIGHT (MM)	499
HEAD TUBE LENGTH (MM)	90
HEAD TUBE ANGLE (DEGREE)	68
CHAINSTAY LENGTH (MM)	390
BB DROP (MM)	25
WHEELBASE (MM)	971
HANDLEBAR WIDTH (MM)	540
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	140
SEAT POST LENGTH (MM)	300

SPECIFICATION

FRAMESET

COLOUR	MATTE BLACK/HOLOGRAM CHROME/TEAM RED
SIZES	11

DRIVETRAIN

SHIFTER	SRAM X5 Trigger Shifter, 9-speed
REAR DERAILLEUR	SRAM X7
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO CS-HG201-9, 11-36T
BOTTOM BRACKET	Thun Topaz, shell BSA
CHAIN	KMC X9
PEDALS	Marwi SP-400

COMPONENTS

GRIPS	Velo VLG-311
BRAKES	Alhonga HJ-372, Hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTTC7F, 20H, M9x100mm, QR Type
REAR HUB	ONE1 KTTC7R, 20H, M10x135, CASSETTE, QR Type
RIMS	Stars J18SF, 20H
TIRES	Schwalbe Rocket Ron Performance, 24x2.10", ADDIX
SPOKES	Sapim Laser, Stainless Black

Team 24

GLOSS DARK RED/HOLOGRAM CHROME



JUNIOR / TEAM

BENEFITS

- A new aluminium lightweight frame with a sport geometry and internal routing
- Lightweight Suntour air suspension fork with lockout
- Hydraulic disc brakes for an easy stop on the spot
- A new cockpit combo and other components adjusted for kids
- Lightweight wheels for easy start and control
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	11
WHEEL SIZE	24
SEAT TUBE LENGTH (MM)	280
SEAT TUBE ANGLE (DEGREE)	73
EFFECTIVE TOP TUBE LENGTH (MM)	500
REACH (MM)	347
STACK HEIGHT (MM)	499
HEAD TUBE LENGTH (MM)	90
HEAD TUBE ANGLE (DEGREE)	68
CHAINSTAY LENGTH (MM)	390
BB DROP (MM)	25
WHEELBASE (MM)	971
HANDLEBAR WIDTH (MM)	540
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	140
SEAT POST LENGTH (MM)	300

SPECIFICATION

FRAMESET

COLOUR	GLOSS DARK RED/HOLOGRAM CHROME
SIZES	11

DRIVETRAIN

SHIFTER	SRAM X5 Trigger Shifter, 9-speed
REAR DERAILLEUR	SRAM X7
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO CS-HG201-9, 11-36T
BOTTOM BRACKET	Thun Topaz, shell BSA
CHAIN	KMC X9
PEDALS	Marwi SP-400

COMPONENTS

GRIPS	Velo VLG-311
BRAKES	Alhonga HJ-372, Hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTTC7F, 20H, M9x100mm, QR Type
REAR HUB	ONE1 KTTC7R, 20H, M10x135, CASSETTE, QR Type
RIMS	Stars J18SF, 20H
TIRES	Schwalbe Rocket Ron Performance, 24x2.10", ADDIX
SPOKES	Sapim Laser, Stainless Black

Team 20

MATTE BLACK/HOLOGRAM CHROME/TEAM RED



JUNIOR / TEAM

BENEFITS

- A new aluminium frame with a sport geometry and internal routing
- Minimum weight thanks to lightweight aluminium fork and the right choice of components
- Fast Schwalbe tires with a large contact surface for safe riding
- Intuitive 1x7 gear set
- A new cockpit combo for kids ergonomics
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	9"
WHEEL SIZE	20
SEAT TUBE LENGTH (MM)	230
SEAT TUBE ANGLE (DEGREE)	70
EFFECTIVE TOP TUBE LENGTH (MM)	450
REACH (MM)	323
STACK HEIGHT (MM)	389
HEAD TUBE LENGTH (MM)	100
HEAD TUBE ANGLE (DEGREE)	67
CHAINSTAY LENGTH (MM)	330
BB DROP (MM)	10
WHEELBASE (MM)	855
HANDLEBAR WIDTH (MM)	500
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	127
SEAT POST LENGTH (MM)	230

SPECIFICATION

FRAMESET

COLOUR	MATTE BLACK/HOLOGRAM CHROME/TEAM RED
SIZES	9"

DRIVETRAIN

SHIFTER	SHIMANO CLARIS SL-R2000 RapidFire Plus, 8-speed
REAR DERAILLEUR	SHIMANO CLARIS RD-R2000
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO CS-HG31-8, 11-32T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-202

COMPONENTS

GRIPS	Velo VLG-311
BRAKES	Alhonga HJ-372, Hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTTC7F, 20H, M9x100mm, QR Type
REAR HUB	ONE1 KTTC7R, 20H, M10x135, CASSETTE, QR Type
RIMS	Stars J18SF, 20H
SPOKES	Sapim Laser, Stainless Black

Team 20

GLOSS DARK RED/HOLOGRAM CHROME



JUNIOR / TEAM

BENEFITS

- A new aluminium frame with a sport geometry and internal routing
- Minimum weight thanks to lightweight aluminium fork and the right choice of components
- Fast Schwalbe tires with a large contact surface for safe riding
- Intuitive 1x7 gear set
- A new cockpit combo for kids ergonomics
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	9"
WHEEL SIZE	20
SEAT TUBE LENGTH (MM)	230
SEAT TUBE ANGLE (DEGREE)	70
EFFECTIVE TOP TUBE LENGTH (MM)	450
REACH (MM)	323
STACK HEIGHT (MM)	389
HEAD TUBE LENGTH (MM)	100
HEAD TUBE ANGLE (DEGREE)	67
CHAINSTAY LENGTH (MM)	330
BB DROP (MM)	10
WHEELBASE (MM)	855
HANDLEBAR WIDTH (MM)	500
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	127
SEAT POST LENGTH (MM)	230

SPECIFICATION

FRAMESET

COLOUR	GLOSS DARK RED/HOLOGRAM CHROME
SIZES	9"

DRIVETRAIN

SHIFTER	SHIMANO CLARIS SL-R2000 RapidFire Plus, 8-speed
REAR DERAILLEUR	SHIMANO CLARIS RD-R2000
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO CS-HG31-8, 11-32T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-202

COMPONENTS

GRIPS	Velo VLG-311
BRAKES	Alhonga HJ-372, Hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTTC7F, 20H, M9x100mm, QR Type
REAR HUB	ONE1 KTTC7R, 20H, M10x135, CASSETTE, QR Type
RIMS	Stars J18SF, 20H
SPOKES	Sapim Laser, Stainless Black

F.L.Y. 27

MATTE OLIVE METALLIC/HOLOGRAM CHROME



JUNIOR / F.L.Y.

BENEFITS

- A new aluminium frame with a sport geometry and a rigid fork for low weight
- 1x9 Shimano Deore and Alivio gear shifting with simple handling
- Geometry adjusted for easy handling and a comfortable seating position
- A new cockpit combo for kids ergonomics
- Light Schwalbe Smart Sam tires with all-purpose pattern
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	13.0" (XS)
WHEEL SIZE	27.5
SEAT TUBE LENGTH (MM)	330
SEAT TUBE ANGLE (DEGREE)	74
EFFECTIVE TOP TUBE LENGTH (MM)	545
REACH (MM)	402
STACK HEIGHT (MM)	499
HEAD TUBE LENGTH (MM)	90
HEAD TUBE ANGLE (DEGREE)	69
CHAINSTAY LENGTH (MM)	435
BB DROP (MM)	40
WHEELBASE (MM)	1056
HANDLEBAR WIDTH (MM)	600
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	160
SEAT POST LENGTH (MM)	350

SPECIFICATION

FRAMESET

COLOUR	MATTE OLIVE METALLIC/HOLOGRAM CHROME
SIZES	13.0" (XS)

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	Wheel Top SXB4BL-WM, 32T
CASSETTE	SHIMANO CS-HG201-9, 11-36T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC X9
PEDALS	Marwi SP-400

COMPONENTS

GRIPS	Velo VLG-311
BRAKES	Alhonga HJ-372, Hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTTC7F, 28H, M9x100mm, QR Type
REAR HUB	ONE1 KTTC7R, 28H, M10x135, CASSETTE, QR Type
RIMS	Stars J20S, 28H
TIRES	Schwalbe Smart Sam Performance, 27.5x2.10", ADDIX
SPOKES	Sapim Galvanized Black

F.L.Y. 27

MATTE TROOPER GREEN/HOLOGRAM CHROME



JUNIOR / F.L.Y.

BENEFITS

- A new aluminium frame with a sport geometry and a rigid fork for low weight
- 1x9 Shimano Deore and Alivio gear shifting with simple handling
- Geometry adjusted for easy handling and a comfortable seating position
- A new cockpit combo for kids ergonomics
- Light Schwalbe Smart Sam tires with all-purpose pattern
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	13.0" (XS)
WHEEL SIZE	27.5
SEAT TUBE LENGTH (MM)	330
SEAT TUBE ANGLE (DEGREE)	74
EFFECTIVE TOP TUBE LENGTH (MM)	545
REACH (MM)	402
STACK HEIGHT (MM)	499
HEAD TUBE LENGTH (MM)	90
HEAD TUBE ANGLE (DEGREE)	69
CHAINSTAY LENGTH (MM)	435
BB DROP (MM)	40
WHEELBASE (MM)	1056
HANDLEBAR WIDTH (MM)	600
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	160
SEAT POST LENGTH (MM)	350

SPECIFICATION

FRAMESET

COLOUR	MATTE TROOPER GREEN/HOLOGRAM CHROME
SIZES	13.0" (XS)

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	Wheel Top SXB4BL-WM, 32T
CASSETTE	SHIMANO CS-HG201-9, 11-36T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC X9
PEDALS	Marwi SP-400

COMPONENTS

GRIPS	Velo VLG-311
BRAKES	Alhonga HJ-372, Hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTTC7F, 28H, M9x100mm, QR Type
REAR HUB	ONE1 KTTC7R, 28H, M10x135, CASSETTE, QR Type
RIMS	Stars J20S, 28H
TIRES	Schwalbe Smart Sam Performance, 27.5x2.10", ADDIX
SPOKES	Sapim Galvanized Black

F.L.Y. 24 DB

MATTE OLIVE METALLIC/HOLOGRAM CHROME



JUNIOR / F.L.Y.

BENEFITS

- A new lightweight aluminium frame with a sport geometry and disc brakes
- 1x8 Shimano Alivio and Acera gear set with simple handling
- Geometry adjusted for easy handling and a comfortable seating position
- Light Schwalbe Smart Sam tires with all-purpose pattern
- A new cockpit combo for kids ergonomics
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	11
WHEEL SIZE	24
SEAT TUBE LENGTH (MM)	280
SEAT TUBE ANGLE (DEGREE)	73
EFFECTIVE TOP TUBE LENGTH (MM)	500
REACH (MM)	362
STACK HEIGHT (MM)	448
HEAD TUBE LENGTH (MM)	100
HEAD TUBE ANGLE (DEGREE)	68
CHAINSTAY LENGTH (MM)	390
BB DROP (MM)	25
WHEELBASE (MM)	939
HANDLEBAR WIDTH (MM)	540
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	140
SEAT POST LENGTH (MM)	300

SPECIFICATION

FRAMESET

COLOUR	MATTE OLIVE METALLIC/HOLOGRAM CHROME
SIZES	11

DRIVETRAIN

SHIFTER	SHIMANO ALTUS SL-M315-8R RapidFire Plus, 8-speed
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO CS-HG31-8, 11-34T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-400

COMPONENTS

GRIPS	Velo VLG-311
BRAKES	Alhonga HJ-372, Hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTTC7F, 20H, M9x100mm, QR Type
REAR HUB	ONE1 KTTC7R, 20H, M10x135, CASSETTE, QR Type
RIMS	Stars J18SF, 20H
SPOKES	Sapim Galvanized Black

F.L.Y. 24 DB

MATTE TROOPER GREEN/HOLOGRAM CHROME



JUNIOR / F.L.Y.

BENEFITS

- A new lightweight aluminium frame with a sport geometry and disc brakes
- 1x8 Shimano Alivio and Acera gear set with simple handling
- Geometry adjusted for easy handling and a comfortable seating position
- Light Schwalbe Smart Sam tires with all-purpose pattern
- A new cockpit combo for kids ergonomics
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	11
WHEEL SIZE	24
SEAT TUBE LENGTH (MM)	280
SEAT TUBE ANGLE (DEGREE)	73
EFFECTIVE TOP TUBE LENGTH (MM)	500
REACH (MM)	362
STACK HEIGHT (MM)	448
HEAD TUBE LENGTH (MM)	100
HEAD TUBE ANGLE (DEGREE)	68
CHAINSTAY LENGTH (MM)	390
BB DROP (MM)	25
WHEELBASE (MM)	939
HANDLEBAR WIDTH (MM)	540
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	140
SEAT POST LENGTH (MM)	300

SPECIFICATION

FRAMESET

COLOUR	MATTE TROOPER GREEN/HOLOGRAM CHROME
SIZES	11

DRIVETRAIN

SHIFTER	SHIMANO ALTUS SL-M315-8R RapidFire Plus, 8-speed
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO CS-HG31-8, 11-34T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-400

COMPONENTS

GRIPS	Velo VLG-311
BRAKES	Alhonga HJ-372, Hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTTC7F, 20H, M9x100mm, QR Type
REAR HUB	ONE1 KTTC7R, 20H, M10x135, CASSETTE, QR Type
RIMS	Stars J18SF, 20H
SPOKES	Sapim Galvanized Black

F.L.Y. 24

MATTE OLIVE METALLIC/HOLOGRAM CHROME



JUNIOR / F.L.Y.

BENEFITS

- A new lightweight aluminium frame with a sport geometry
- 1x8 Shimano Alivio and Acera gear set with simple handling
- Geometry adjusted for easy handling and a comfortable seating position
- Light Schwalbe Smart Sam tires with all-purpose pattern
- A new cockpit combo for kids ergonomics
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	11
WHEEL SIZE	24
SEAT TUBE LENGTH (MM)	280
SEAT TUBE ANGLE (DEGREE)	73
EFFECTIVE TOP TUBE LENGTH (MM)	500
REACH (MM)	362
STACK HEIGHT (MM)	448
HEAD TUBE LENGTH (MM)	100
HEAD TUBE ANGLE (DEGREE)	68
CHAINSTAY LENGTH (MM)	390
BB DROP (MM)	25
WHEELBASE (MM)	939
HANDLEBAR WIDTH (MM)	540
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	140
SEAT POST LENGTH (MM)	300

SPECIFICATION

FRAMESET

COLOUR	MATTE OLIVE METALLIC/HOLOGRAM CHROME
SIZES	11

DRIVETRAIN

SHIFTER	SHIMANO ALTUS SL-M315-8R RapidFire Plus, 8-speed
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO CS-HG31-8, 11-34T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-400

COMPONENTS

GRIPS	Velo VLG-311
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTA55F, 24H, M9x100mm, QR Type
REAR HUB	ONE1 KTAZER, 24H, M10x130, CASSETTE, QR Type
RIMS	Stars J19SZ, 24H
TIRES	Schwalbe CX Comp, 24x1.75", Reflective tape
SPOKES	Sapim Galvanized Black

F.L.Y. 24

MATTE TROOPER GREEN/HOLOGRAM CHROME



JUNIOR / F.L.Y.

BENEFITS

- A new lightweight aluminium frame with a sport geometry
- 1x8 Shimano Alivio and Acera gear set with simple handling
- Geometry adjusted for easy handling and a comfortable seating position
- Light Schwalbe Smart Sam tires with all-purpose pattern
- A new cockpit combo for kids ergonomics
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	11
WHEEL SIZE	24
SEAT TUBE LENGTH (MM)	280
SEAT TUBE ANGLE (DEGREE)	73
EFFECTIVE TOP TUBE LENGTH (MM)	500
REACH (MM)	362
STACK HEIGHT (MM)	448
HEAD TUBE LENGTH (MM)	100
HEAD TUBE ANGLE (DEGREE)	68
CHAINSTAY LENGTH (MM)	390
BB DROP (MM)	25
WHEELBASE (MM)	939
HANDLEBAR WIDTH (MM)	540
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	140
SEAT POST LENGTH (MM)	300

SPECIFICATION

FRAMESET

COLOUR	MATTE TROOPER GREEN/HOLOGRAM CHROME
SIZES	11

DRIVETRAIN

SHIFTER	SHIMANO ALTUS SL-M315-8R RapidFire Plus, 8-speed
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO CS-HG31-8, 11-34T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-400

COMPONENTS

GRIPS	Velo VLG-311
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTA55F, 24H, M9x100mm, QR Type
REAR HUB	ONE1 KTAZER, 24H, M10x130, CASSETTE, QR Type
RIMS	Stars J19SZ, 24H
TIRES	Schwalbe CX Comp, 24x1.75", Reflective tape
SPOKES	Sapim Galvanized Black

F.L.Y. 20 DB

MATTE OLIVE METALLIC/HOLOGRAM CHROME



GRAPHIC SIMULATION ONLY / REAL PICTURE: 500H

JUNIOR / F.L.Y.

BENEFITS

- A new aluminium frame with a sport geometry and rigid fork for low weight
- 1x7 Shimano gear set for easy handling
- A new cockpit combo for comfortable position and joy of riding
- Schwalbe CX Comp tires with reflective lines which make a cyclist easily seen
- Comfortable Selle Royal saddle
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	9
WHEEL SIZE	20
SEAT TUBE LENGTH (MM)	230
SEAT TUBE ANGLE (DEGREE)	72
EFFECTIVE TOP TUBE LENGTH (MM)	450
REACH (MM)	326
STACK HEIGHT (MM)	378
HEAD TUBE LENGTH (MM)	100
HEAD TUBE ANGLE (DEGREE)	67
CHAINSTAY LENGTH (MM)	330
BB DROP (MM)	0
WHEELBASE (MM)	859
HANDLEBAR WIDTH (MM)	500
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	127
SEAT POST LENGTH (MM)	230

SPECIFICATION

FRAMESET

COLOUR	MATTE OLIVE METALLIC/HOLOGRAM CHROME
SIZES	9

DRIVETRAIN

SHIFTER	SHIMANO SL-RV200-7R RevoShift, 7-speed
REAR DERAILLEUR	SHIMANO TY RD-TY200
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO CS-HG200-7, 12-32T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-202

COMPONENTS

GRIPS	Velo VLG-311, ONE1 VLG-311-6, DUAL DENSITY KRATON-GEL
BRAKES	Alhonga HJ-372, Hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTTC7F, 20H, M9x100mm, QR Type
REAR HUB	ONE1 KTTCCR, 20H, M10x135, CASSETTE, QR Type
RIMS	Stars J18SF, 20H
SPOKES	Sapim Galvanized Black

F.L.Y. 20 DB

MATTE TROOPER GREEN/HOLOGRAM CHROME



JUNIOR / F.L.Y.

BENEFITS

- A new aluminium frame with a sport geometry and rigid fork for low weight
- 1x7 Shimano gear set for easy handling
- A new cockpit combo for comfortable position and joy of riding
- Schwalbe CX Comp tires with reflective lines which make a cyclist easily seen
- Comfortable Selle Royal saddle
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	9
WHEEL SIZE	20
SEAT TUBE LENGTH (MM)	230
SEAT TUBE ANGLE (DEGREE)	72
EFFECTIVE TOP TUBE LENGTH (MM)	450
REACH (MM)	326
STACK HEIGHT (MM)	378
HEAD TUBE LENGTH (MM)	100
HEAD TUBE ANGLE (DEGREE)	67
CHAINSTAY LENGTH (MM)	330
BB DROP (MM)	0
WHEELBASE (MM)	859
HANDLEBAR WIDTH (MM)	500
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	127
SEAT POST LENGTH (MM)	230

SPECIFICATION

FRAMESET

COLOUR	MATTE TROOPER GREEN/HOLOGRAM CHROME
SIZES	9

DRIVETRAIN

SHIFTER	SHIMANO SL-RV200-7R RevoShift, 7-speed
REAR DERAILLEUR	SHIMANO TY RD-TY200
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO CS-HG200-7, 12-32T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-202

COMPONENTS

GRIPS	Velo VLG-311, ONE1 VLG-311-6, DUAL DENSITY KRATON-GEL
BRAKES	Alhonga HJ-372, Hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTTC7F, 20H, M9x100mm, QR Type
REAR HUB	ONE1 KTTCCR, 20H, M10x135, CASSETTE, QR Type
RIMS	Stars J18SF, 20H
SPOKES	Sapim Galvanized Black

F.L.Y. 20

MATTE OLIVE METALLIC/HOLOGRAM CHROME



JUNIOR / F.L.Y.

BENEFITS

- A new aluminium frame with a sport geometry and rigid fork for low weight
- 1x7 Shimano gear set for easy handling
- A new cockpit combo for comfortable position and joy of riding
- Schwalbe CX Comp tires with reflective lines which make a cyclist easily seen
- Comfortable Selle Royal saddle
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	9
WHEEL SIZE	20
SEAT TUBE LENGTH (MM)	230
SEAT TUBE ANGLE (DEGREE)	72
EFFECTIVE TOP TUBE LENGTH (MM)	450
REACH (MM)	326
STACK HEIGHT (MM)	378
HEAD TUBE LENGTH (MM)	100
HEAD TUBE ANGLE (DEGREE)	67
CHAINSTAY LENGTH (MM)	330
BB DROP (MM)	0
WHEELBASE (MM)	859
HANDLEBAR WIDTH (MM)	500
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	127
SEAT POST LENGTH (MM)	230

SPECIFICATION

FRAMESET

COLOUR	MATTE OLIVE METALLIC/HOLOGRAM CHROME
SIZES	9

DRIVETRAIN

SHIFTER	SHIMANO SL-RV200-7R RevoShift, 7-speed
REAR DERAILLEUR	SHIMANO TY RD-TY200
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO CS-HG200-7, 12-32T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-202

COMPONENTS

GRIPS	Velo VLG-311, ONE1 VLG-311-6, DUAL DENSITY KRATON-GEL
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTA55F, 20H, M9x100mm, QR Type
REAR HUB	ONE1 KTAZ2R, 20H, M10x130, CASSETTE, QR Type
RIMS	Stars J19SZ, 20H
TIRES	Schwalbe CX Comp, 20x1.75", Reflective tape
SPOKES	Sapim Galvanized Black

F.L.Y. 20

MATTE TROOPER GREEN/HOLOGRAM CHROME



JUNIOR / F.L.Y.

BENEFITS

- A new aluminium frame with a sport geometry and rigid fork for low weight
- 1x7 Shimano gear set for easy handling
- A new cockpit combo for comfortable position and joy of riding
- Schwalbe CX Comp tires with reflective lines which make a cyclist easily seen
- Comfortable Selle Royal saddle
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	9
WHEEL SIZE	20
SEAT TUBE LENGTH (MM)	230
SEAT TUBE ANGLE (DEGREE)	72
EFFECTIVE TOP TUBE LENGTH (MM)	450
REACH (MM)	326
STACK HEIGHT (MM)	378
HEAD TUBE LENGTH (MM)	100
HEAD TUBE ANGLE (DEGREE)	67
CHAINSTAY LENGTH (MM)	330
BB DROP (MM)	0
WHEELBASE (MM)	859
HANDLEBAR WIDTH (MM)	500
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	127
SEAT POST LENGTH (MM)	230

SPECIFICATION

FRAMESET

COLOUR	MATTE TROOPER GREEN/HOLOGRAM CHROME
SIZES	9

DRIVETRAIN

SHIFTER	SHIMANO SL-RV200-7R RevoShift, 7-speed
REAR DERAILLEUR	SHIMANO TY RD-TY200
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO CS-HG200-7, 12-32T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-202

COMPONENTS

GRIPS	Velo VLG-311, ONE1 VLG-311-6, DUAL DENSITY KRATON-GEL
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTA55F, 20H, M9x100mm, QR Type
REAR HUB	ONE1 KTAZ2R, 20H, M10x130, CASSETTE, QR Type
RIMS	Stars J19SZ, 20H
TIRES	Schwalbe CX Comp, 20x1.75", Reflective tape
SPOKES	Sapim Galvanized Black

Racer XC 27 DB

MATTE LIME/RED



JUNIOR / RACER

BENEFITS

- A new aluminium frame with internal routing and a comfortable geometry
- Suntour coil fork with 100 mm travel
- Shimano 1x8 gears for easy handling
- Light Schwalbe Smart Sam tires with fast all-purpose pattern
- Comfortable Selle Royal saddle
- ONE1 accessories tailor-made for children's anatomy
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	13" (XS)	15.5" (S)
WHEEL SIZE	27.5	27.5
SEAT TUBE LENGTH (MM)	343	393
SEAT TUBE ANGLE (DEGREE)	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	547	586
REACH (MM)	382	423
STACK HEIGHT (MM)	566	566
HEAD TUBE LENGTH (MM)	90	90
HEAD TUBE ANGLE (DEGREE)	69	69
CHAINSTAY LENGTH (MM)	435	435
BB DROP (MM)	40	40
WHEELBASE (MM)	1064	1103
HANDLEBAR WIDTH (MM)	600	600
STEM LENGTH (MM)	35	35
CRANK LENGTH (MM)	160	160
SEAT POST LENGTH (MM)	350	350

SPECIFICATION

FRAMESET

FORK	SR Suntour XCT30, 1-1/8", Coil, QR Type, 100mm travel
COLOUR	MATTE LIME/RED
SIZES	13" (XS), 15.5" (S)

DRIVETRAIN

SHIFTER	SHIMANO ALTUS SL-M315-8R RapidFire Plus, 8-speed
CRANKSET	Wheel Top SXB4BL-WM, 32T
CASSETTE	SHIMANO CS-HG31-8, 11-34T
BOTTOM BRACKET	Thun Ibex 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-718BT, 34mm rise, 600mm, 25.4mm
STEM	ONE1 MAS-MD60368 Alloy, 25.4mm, 15°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Sport Alloy, SP C208, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J20S, 32H
TIRES	Schwalbe Smart Sam KevlarGuard, 27.5x2.10"
SPOKES	Sapim Galvanized Black

Racer XC 27 DB

GLOSS WHITE/BLUE/NEON YELLOW



JUNIOR / RACER

BENEFITS

- A new aluminium frame with internal routing and a comfortable geometry
- Suntour coil fork with 100 mm travel
- Shimano 1x8 gears for easy handling
- Light Schwalbe Smart Sam tires with fast all-purpose pattern
- Comfortable Selle Royal saddle
- ONE1 accessories tailor-made for children's anatomy
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	13" (XS)	15.5" (S)
WHEEL SIZE	27.5	27.5
SEAT TUBE LENGTH (MM)	343	393
SEAT TUBE ANGLE (DEGREE)	74	74
EFFECTIVE TOP TUBE LENGTH (MM)	547	586
REACH (MM)	382	423
STACK HEIGHT (MM)	566	566
HEAD TUBE LENGTH (MM)	90	90
HEAD TUBE ANGLE (DEGREE)	69	69
CHAINSTAY LENGTH (MM)	435	435
BB DROP (MM)	40	40
WHEELBASE (MM)	1064	1103
HANDLEBAR WIDTH (MM)	600	600
STEM LENGTH (MM)	35	35
CRANK LENGTH (MM)	160	160
SEAT POST LENGTH (MM)	350	350

SPECIFICATION

FRAMESET

FORK	SR Suntour XCT30, 1-1/8", Coil, QR Type, 100mm travel
COLOUR	GLOSS WHITE/BLUE/NEON YELLOW
SIZES	13" (XS), 15.5" (S)

DRIVETRAIN

SHIFTER	SHIMANO ALTUS SL-M315-8R RapidFire Plus, 8-speed
CRANKSET	Wheel Top SXB4BL-WM, 32T
CASSETTE	SHIMANO CS-HG31-8, 11-34T
BOTTOM BRACKET	Thun Ibox 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-718BT, 34mm rise, 600mm, 25.4mm
STEM	ONE1 MAS-MD60368 Alloy, 25.4mm, 15°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Sport Alloy, SP C208, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J20S, 32H
TIRES	Schwalbe Smart Sam KevlarGuard, 27.5x2.10"
SPOKES	Sapim Galvanized Black

Racer XC 24

MATTE LIME/BLACK/RED



JUNIOR / RACER

BENEFITS

- Double-buttet aluminium frame with a comfortable geometry
- Ergonomics and size of the components meet the style and height of the young riders
- Fast tires for cycle paths and mild off-road tracks
- Light aluminium fork
- 1x8 Shimano gears for intuitive handling
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	11"
WHEEL SIZE	24
SEAT TUBE LENGTH (MM)	280
SEAT TUBE ANGLE (DEGREE)	73
EFFECTIVE TOP TUBE LENGTH (MM)	500
REACH (MM)	356
STACK HEIGHT (MM)	469
HEAD TUBE LENGTH (MM)	100
HEAD TUBE ANGLE (DEGREE)	68
CHAINSTAY LENGTH (MM)	390
BB DROP (MM)	25
WHEELBASE (MM)	993
HANDLEBAR WIDTH (MM)	540
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	140
SEAT POST LENGTH (MM)	300

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, SR dropout
HEAD SET	CH290TBW, 1-1/8"
FORK	SR Suntour XCT JR24, 1-1/8", Soft Spring, QR Type, 50mm travel
COLOUR	MATTE LIME/BLACK/RED
SIZES	11"

DRIVETRAIN

SHIFTER	SHIMANO TY SL-RS45-8R RevoShift, 8-speed
REAR DERAILLEUR	SHIMANO TY RD-TX800
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO CS-HG31-8, 11-34T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-400

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB-110PP, 10° backsweep, 540mm, 25.4mm
STEM	ONE1 MAS-MD60368 Alloy, 25.4mm, 15°
GRIPS	ONE1 VLG-311-6, DUAL DENSITY KRATON-GEL, Velo VLG-311
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C208, 27.2mm

WHEELS

FRONT HUB	ONE1 KTA55F, 24H, M9x100mm, QR Type
REAR HUB	ONE1 KTAZER, 24H, M10x135, CASSETTE, QR Type
RIMS	Stars J19SZ, 24H
SPOKES	Sapim Zinc

Racer XC 24

GLOSS WHITE/BLUE/NEON YELLOW



JUNIOR / RACER

BENEFITS

- Double-butted aluminium frame with a comfortable geometry
- Ergonomics and size of the components meet the style and height of the young riders
- Fast tires for cycle paths and mild off-road tracks
- Light aluminium fork
- 1x8 Shimano gears for intuitive handling
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	11"
WHEEL SIZE	24
SEAT TUBE LENGTH (MM)	280
SEAT TUBE ANGLE (DEGREE)	73
EFFECTIVE TOP TUBE LENGTH (MM)	500
REACH (MM)	356
STACK HEIGHT (MM)	469
HEAD TUBE LENGTH (MM)	100
HEAD TUBE ANGLE (DEGREE)	68
CHAINSTAY LENGTH (MM)	390
BB DROP (MM)	25
WHEELBASE (MM)	993
HANDLEBAR WIDTH (MM)	540
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	140
SEAT POST LENGTH (MM)	300

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, SR dropout
HEAD SET	CH290TBW, 1-1/8"
FORK	SR Suntour XCT JR24, 1-1/8", Soft Spring, QR Type, 50mm travel
COLOUR	GLOSS WHITE/BLUE/NEON YELLOW
SIZES	11"

DRIVETRAIN

SHIFTER	SHIMANO TY SL-RS45-8R RevoShift, 8-speed
REAR DERAILLEUR	SHIMANO TY RD-TX800
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO CS-HG31-8, 11-34T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-400

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB-110PP, 10° backsweep, 540mm, 25.4mm
STEM	ONE1 MAS-MD60368 Alloy, 25.4mm, 15°
GRIPS	ONE1 VLG-311-6, DUAL DENSITY KRATON-GEL, Velo VLG-311
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C208, 27.2mm

WHEELS

FRONT HUB	ONE1 KTA55F, 24H, M9x100mm, QR Type
REAR HUB	ONE1 KTAZER, 24H, M10x135, CASSETTE, QR Type
RIMS	Stars J19SZ, 24H
SPOKES	Sapim Zinc

Racer XC 20

MATTE LIME/BLACK/RED



JUNIOR / RACER

BENEFITS

- Double-butted aluminium frame with a comfortable geometry
- Ergonomics and size of the components meet the style and height of the young riders
- Fast tires for cycle paths and mild off-road tracks
- Light aluminium fork
- 1x7 Shimano gears for intuitive handling
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	9"
WHEEL SIZE	20
SEAT TUBE LENGTH (MM)	230
SEAT TUBE ANGLE (DEGREE)	73
EFFECTIVE TOP TUBE LENGTH (MM)	450
REACH (MM)	328
STACK HEIGHT (MM)	375
HEAD TUBE LENGTH (MM)	100
HEAD TUBE ANGLE (DEGREE)	67
CHAINSTAY LENGTH (MM)	330
BB DROP (MM)	0
WHEELBASE (MM)	827
HANDLEBAR WIDTH (MM)	500
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	127
SEAT POST LENGTH (MM)	230

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, SR dropout
HEAD SET	CH290TBW, 1-1/8"
FORK	Racer XC20" U-Big, Hi-ten rigid, Ahead 1-1/8", V-Brake, QR Type
COLOUR	MATTE LIME/BLACK/RED
SIZES	9"

DRIVETRAIN

SHIFTER	SHIMANO SL-RV200-7R RevoShift, 7-speed
REAR DERAILLEUR	SHIMANO TY RD-TY200
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO MF-TZ500-7, 14-28T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-202

COMPONENTS

HANDLEBAR	ONE1 Hi-ten, MTB-110PP, 10° backsweep, 500mm, 25.4mm
STEM	ONE1 MAS-MD60368 Alloy, 25.4mm, 15°
GRIPS	Velo VLG-311, ONE1 VLG-311-6, DUAL DENSITY KRATON-GEL
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C208, 27.2mm

WHEELS

FRONT HUB	ONE1 KTA55F, 24H, M9x100mm, QR Type
REAR HUB	ONE1 KTA52R, 24H, M10x135, FREEWHEEL, QR Type
RIMS	Stars J19SZ, 24H
TIRES	Schwalbe Black Jack 20x1.90"
SPOKES	Sapim Zinc

Racer XC 20

GLOSS WHITE/BLUE/NEON YELLOW



JUNIOR / RACER

BENEFITS

- Double-butted aluminium frame with a comfortable geometry
- Ergonomics and size of the components meet the style and height of the young riders
- Fast tires for cycle paths and mild off-road tracks
- Light aluminium fork
- 1x7 Shimano gears for intuitive handling
- Set of stickers for bike personalization according to a taste of the small biker

GEOMETRY

FRAME SIZE	9"
WHEEL SIZE	20
SEAT TUBE LENGTH (MM)	230
SEAT TUBE ANGLE (DEGREE)	73
EFFECTIVE TOP TUBE LENGTH (MM)	450
REACH (MM)	328
STACK HEIGHT (MM)	375
HEAD TUBE LENGTH (MM)	100
HEAD TUBE ANGLE (DEGREE)	67
CHAINSTAY LENGTH (MM)	330
BB DROP (MM)	0
WHEELBASE (MM)	827
HANDLEBAR WIDTH (MM)	500
STEM LENGTH (MM)	35
CRANK LENGTH (MM)	127
SEAT POST LENGTH (MM)	230

SPECIFICATION

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, SR dropout
HEAD SET	CH290TBW, 1-1/8"
FORK	Racer XC20" U-Big, Hi-ten rigid, Ahead 1-1/8", V-Brake, QR Type
COLOUR	GLOSS WHITE/BLUE/NEON YELLOW
SIZES	9"

DRIVETRAIN

SHIFTER	SHIMANO SL-RV200-7R RevoShift, 7-speed
REAR DERAILLEUR	SHIMANO TY RD-TY200
CRANKSET	Wheel Top SXB4BL-WM, 28T
CASSETTE	SHIMANO MF-TZ500-7, 14-28T
BOTTOM BRACKET	Thun Topaz 120mm, BSA, shell 68mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-202

COMPONENTS

HANDLEBAR	ONE1 Hi-ten, MTB-110PP, 10° backsweep, 500mm, 25.4mm
STEM	ONE1 MAS-MD60368 Alloy, 25.4mm, 15°
GRIPS	Velo VLG-311, ONE1 VLG-311-6, DUAL DENSITY KRATON-GEL
SADDLE	Selle Royal Junior
SEAT POST	ONE1 Alloy, SP C208, 27.2mm

WHEELS

FRONT HUB	ONE1 KTA55F, 24H, M9x100mm, QR Type
REAR HUB	ONE1 KTA52R, 24H, M10x135, FREEWHEEL, QR Type
RIMS	Stars J19SZ, 24H
TIRES	Schwalbe Black Jack 20x1.90"
SPOKES	Sapim Zinc

eXF 9049 R

MATTE TROOPER GREEN/CHROME SILVER



E-MTB / TRAIL

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS EP800, 36V, 250W, 85Nm
BATTERY	DARFON, 36V, 630 Wh, frame mount
DISPLAY	SHIMANO SC-EM800, Clamp band
CHARGER	DARFON 4A Smart Plus charger

BENEFITS

- Shimano EP8 motor: 85 Nm, low noise, high performance
- Full integrated 630 Wh battery ensures a range over 150 km*
- Progressive geometry shared with the carbon racing bikes
- E-TUBE PROJECT: customized motor setting via the E-Tube Shimano application
- Total battery integration, and internal cable routing
- 140/130 mm travel of the DT Swiss dampers
- DT Swiss H1900 SPLINE wheelset designed for e-bikes
- Dropper post with travel values of 125 mm (S and M frame sizes) and 150 mm (L and XL sizes)
- Lightweight tires Schwalbe Nobby Nic SnakeSkin 29x2.60"

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74.5	74.5	74.5	74.5
EFFECTIVE TOP TUBE LENGTH (MM)	599	625	635	650
REACH (MM)	438	459	466	479
STACK HEIGHT (MM)	590	599	608	618
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	66	66	66	66
CHAINSTAY LENGTH (MM)	433	433	433	433
BB DROP (MM)	20	20	20	20
WHEELBASE (MM)	1168	1196	1207	1224
HANDLEBAR WIDTH (MM)	760	780	780	780
STEM LENGTH (MM)	60	60	60	80
CRANK LENGTH (MM)	165	165	165	170
SEAT POST LENGTH (MM)	390/125	390/125	390/125	440/150

FRAMESET

FRAME	Alu X6 Ultralite MTB Trail SUE03-EP8, Advanced e-MTB Geometry, Travel 130 mm, SHIMANO STEPS ready, Prepared to 630Wh integrated battery, 3D alloy one piece link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-1051, ICR, ZS56/28.6 ZS56/40; BlockLock 120°
FORK	DT Swiss DT-F535 Tapered, 15x110mm axle, 140mm travel
REAR SHOCK	DT Swiss R 535 ONE, Lockout, size 210x50mm, Bushing body for DT Swiss
COLOUR	MATTE TROOPER GREEN/CHROME SILVER
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE XT SL-M8100 RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100 Shadow Plus
CRANKSET	SHIMANO FC-E8000, 34T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
CHAIN	SHIMANO CN-M6100

COMPONENTS

STEM	ONE1 TDS-661 Alloy, 31.8mm, 0°
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO XT BL-M8100/BR-M8120, hydraulic disc brake
SEAT POST	ONE1 Alloy, MT171, dropper post, 30.9mm

WHEELS

TIRES	Schwalbe Nobby Nic Evo Super Trail, 29x2.60", ADDIX Speedgrip
-------	---

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXF 9039

GLOSS WHITE/CHROME SILVER



E-MTB / TRAIL

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS EP800, 36V, 250W, 85Nm
BATTERY	DARFON, 36V, 630 Wh, frame mount
DISPLAY	SHIMANO SC-EM800, Clamp band
CHARGER	DARFON 4A Smart Plus charger

BENEFITS

- Shimano EP8 250 W Motor: 85 Nm, low noise, high performance
- Full integrated 630 Wh battery ensures a range over 150 km*
- Progressive geometry shared with the carbon racing bikes
- E-TUBE PROJECT: customized motor setting via the E-Tube Shimano application
- Total battery integration, and internal cable routing
- 140/130 mm travel of the Rock Shox dampers
- DT Swiss H1900 SPLINE wheelset designed for e-bikes
- Dropper post with travel values of 125 mm (M frame sizes) and 150 mm (L and XL sizes)
- Lightweight tires Schwalbe Nobby Nic SnakeSkin 29x2.60"

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19.0" (L)	21.0" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74.5	74.5	74.5	74.5
EFFECTIVE TOP TUBE LENGTH (MM)	599	625	635	650
REACH (MM)	438	459	466	479
STACK HEIGHT (MM)	590	599	608	618
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	66	66	66	66
CHAINSTAY LENGTH (MM)	433	433	433	433
BB DROP (MM)	20	20	20	20
WHEELBASE (MM)	1168	1196	1207	1224
HANDLEBAR WIDTH (MM)	760	780	780	780
STEM LENGTH (MM)	60	60	60	60
CRANK LENGTH (MM)	165	165	165	170
SEAT POST LENGTH (MM)	390/125	390/125	390/125	440/150

FRAMESET

FRAME	Alu X6 Ultralite MTB Trail SUE03-EP8, Advanced e-MTB Geometry, Travel 130 mm, SHIMANO STEPS ready, Prepared to 630Wh integrated battery, 3D alloy one piece link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-1051, ICR, ZS56/28.6 ZS56/40; BlockLock 120°
FORK	RockShox Revelation RC, Tapered, DebonAir, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select Plus, remote Lockout, external rebound, 2 position compression (Open/Lock), size 210x50mm, Bushing body for RockShox
COLOUR	GLOSS WHITE/CHROME SILVER
SIZES	15.5" (S), 17.5" (M), 19.0" (L), 21.0" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO SLX RD-M7100 Shadow Plus
CRANKSET	SHIMANO FC-E6000, 34T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
CHAIN	SHIMANO CN-M6100

COMPONENTS

STEM	ONE1 TDS-661 Alloy, 31.8mm, 0°
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO BL-M6100/BR-M6120, hydraulic disc brake
SEAT POST	ONE1 Alloy, MT171, dropper post, 30.9mm

WHEELS

TIRES	Schwalbe Nobby Nic Evo Super Trail, 29x2.60", ADDIX Speedgrip
-------	---

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXF 9019

MATTE PETROL/CHROME SILVER



E-MTB / TRAIL

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS EP800, 36V, 250W, 85Nm
BATTERY	DARFON, 36V, 630 Wh, frame mount
DISPLAY	SHIMANO SC-EM800, Clamp band
CHARGER	DARFON 4A Smart Plus charger

BENEFITS

- Shimano EP8 250 W Motor: 85 Nm, low noise, high performance
- Fully integrated 504 Wh battery ensures a range over 100 km*
- E-TUBE PROJECT: customized motor setting via the E-Tube Shimano application
- 1x11 gear setup for fluent pedaling frequency adjustment
- Responsive 120 mm Rock Shox air fork
- ICR (Internal Cable Routing): clean, modern looks without visible cables
- BlockLock headset: frame protected against damage by handlebars

GEOMETRY

FRAME SIZE	15.5" (S)	17" (M)	19" (L)	21" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	482	482	533
SEAT TUBE ANGLE (DEGREE)	74.5	74.5	74.5	74.5
EFFECTIVE TOP TUBE LENGTH (MM)	599	625	635	650
REACH (MM)	438	459	466	479
STACK HEIGHT (MM)	590	599	466	618
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	66	66	66	66
CHAINSTAY LENGTH (MM)	433	433	433	433
BB DROP (MM)	20	20	20	20
WHEELBASE (MM)	1168	1196	1207	1224
HANDLEBAR WIDTH (MM)	760	780	780	780
STEM LENGTH (MM)	60	60	80	80
CRANK LENGTH (MM)	165	165	165	170
SEAT POST LENGTH (MM)	390/125	390/125	390/125	440/150

FRAMESET

FRAME	Alu X6 Ultralite MTB Trail SUE03-EP8, Advanced e-MTB Geometry, Travel 130 mm, SHIMANO STEPS ready, Prepared to 630Wh integrated battery, 3D alloy one piece link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-1051, ICR, ZS56/28.6 ZS56/40; BlockLock 120°
FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select Plus, remote Lockout, external rebound, 2 position compression (Open/Lock), size 210x50mm, Bushing body for RockShox
COLOUR	MATTE PETROL/CHROME SILVER
SIZES	15.5" (S), 17" (M), 19" (L), 21" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100 Shadow Plus
CRANKSET	SHIMANO FC-E8000, 34T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
CHAIN	SHIMANO CN-M6100

COMPONENTS

STEM	ONE1 TDS-661 Alloy, 31.8mm, 0°
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT420, hydraulic disc brake
SEAT POST	ONE1 Alloy, MT171, dropper post, 30.9mm
WHEELS	
FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J30D, 32H
TIRES	Schwalbe Nobby Nic Evo Super Trail, 29x2.60", ADDIX Speedgrip
SPOKES	Sapim Leader, Stainless Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXF 8089

MATTE BLACK/CHROME SILVER



E-MTB / TRAIL

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS EP800, 36V, 250W, 85Nm
BATTERY	DARFON, 36V, 504 Wh, integrated
DISPLAY	SHIMANO SC-E5000, Clamp band
CHARGER	DARFON 2A Smart Plus charger

BENEFITS

- Shimano EP8 250 W Motor: 85 Nm, low noise, high performance
- Fully integrated 504 Wh battery ensures a range of more than 120 km*
- E-TUBE PROJECT: customized motor setting via the E-Tube Shimano application
- 1x11 gear setup for fluent pedaling frequency adjustment
- Responsive Rock Shox and Suntour air suspension
- ICR (Internal Cable Routing): clean, modern looks without visible cables
- Four-piston brakes and larger rotors to produce higher braking power

GEOMETRY

FRAME SIZE	15.5" (S)	17" (M)	19" (L)	21" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	490	533
SEAT TUBE ANGLE (DEGREE)	74.5	74.5	74.5	74.5
EFFECTIVE TOP TUBE LENGTH (MM)	599	625	635	650
REACH (MM)	438	459	466	479
STACK HEIGHT (MM)	590	599	608	618
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	66	66	66	66
CHAINSTAY LENGTH (MM)	433	433	433	433
BB DROP (MM)	20	20	20	20
WHEELBASE (MM)	1168	1196	1207	1224
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	60	80
CRANK LENGTH (MM)	170	170	170	170
SEAT POST LENGTH (MM)	400	400	400	400

FRAMESET

FRAME	Alu X6 Ultralite MTB Trail SUE03-EP8, Advanced e-MTB Geometry, Travel 130 mm, SHIMANO STEPS ready, Prepared to 630Wh integrated battery, 3D alloy one piece link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-1051, ICR, ZS56/28.6 ZS56/40; BlockLock 120°
REAR SHOCK	RockShox Deluxe Select R, remote Lockout, external rebound, 2 position compression (Open/Lock), size 210x50mm, Bushing body for RockShox
COLOUR	MATTE BLACK/CHROME SILVER
SIZES	15.5" (S), 17" (M), 19" (L), 21" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M5100-IR RapidFire Plus, 11-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5100 Shadow Plus
CRANKSET	SHIMANO FC-E6000, 34T
CASSETTE	SHIMANO CS-M5100-11, 11-51T
CHAIN	KMC e11T

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-320BT, 3° upsweep, 9° backsweep, 20mm rise, 760mm, 31.8mm
STEM	ONE1 TDS-661 Alloy, 31.8mm, 0°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT420, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Race Alloy, SP 218, 30.9mm
WHEELS	
FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT400-B, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J30D, 32H
TIRES	Schwalbe Smart Sam KevlarGuard, 29x2.60"
SPOKES	Sapim Galvanized Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXF 8089

MATTE OLIVE METALLIC/CHROME SILVER



E-MTB / TRAIL

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS EP800, 36V, 250W, 85Nm
BATTERY	DARFON, 36V, 504 Wh, integrated
DISPLAY	SHIMANO SC-E5000, Clamp band
CHARGER	DARFON 2A Smart Plus charger

BENEFITS

- Shimano EP8 250 W Motor: 85 Nm, low noise, high performance
- Fully integrated 504 Wh battery ensures a range of more than 120 km*
- E-TUBE PROJECT: customized motor setting via the E-Tube Shimano application
- 1x11 gear setup for fluent pedaling frequency adjustment
- Responsive Rock Shox and Suntour air suspension
- ICR (Internal Cable Routing): clean, modern looks without visible cables
- Four-piston brakes and larger rotors to produce higher braking power

GEOMETRY

FRAME SIZE	15.5" (S)	17" (M)	19" (L)	21" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	490	533
SEAT TUBE ANGLE (DEGREE)	74.5	74.5	74.5	74.5
EFFECTIVE TOP TUBE LENGTH (MM)	599	625	635	650
REACH (MM)	438	459	466	479
STACK HEIGHT (MM)	590	599	608	618
HEAD TUBE LENGTH (MM)	90	100	110	120
HEAD TUBE ANGLE (DEGREE)	66	66	66	66
CHAINSTAY LENGTH (MM)	433	433	433	433
BB DROP (MM)	20	20	20	20
WHEELBASE (MM)	1168	1196	1207	1224
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	60	80
CRANK LENGTH (MM)	170	170	170	170
SEAT POST LENGTH (MM)	400	400	400	400

FRAMESET

FRAME	Alu X6 Ultralite MTB Trail SUE03-EP8, Advanced e-MTB Geometry, Travel 130 mm, SHIMANO STEPS ready, Prepared to 630Wh integrated battery, 3D alloy one piece link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-1051, ICR, ZS56/28.6 ZS56/40; BlockLock 120°
REAR SHOCK	RockShox Deluxe Select R, remote Lockout, external rebound, 2 position compression (Open/Lock), size 210x50mm, Bushing body for RockShox
COLOUR	MATTE OLIVE METALLIC/CHROME SILVER
SIZES	15.5" (S), 17" (M), 19" (L), 21" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M5100-IR RapidFire Plus, 11-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5100 Shadow Plus
CRANKSET	SHIMANO FC-E6000, 34T
CASSETTE	SHIMANO CS-M5100-11, 11-51T
CHAIN	KMC e11T

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-320BT, 3° upsweep, 9° backsweep, 20mm rise, 760mm, 31.8mm
STEM	ONE1 TDS-661 Alloy, 31.8mm, 0°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT420, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Race Alloy, SP 218, 30.9mm
WHEELS	
FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT400-B, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J30D, 32H
TIRES	Schwalbe Smart Sam KevlarGuard, 29x2.60"
SPOKES	Sapim Galvanized Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXP 9019

MATTE PETROL/CHROME SILVER



E-MTB / SPORT

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS EP800, 36V, 250W, 85Nm
BATTERY	DARFON, 36V, 630 Wh, frame mount
DISPLAY	SHIMANO SC-EM800, Clamp band
CHARGER	DARFON 4A Smart Plus charger

BENEFITS

- Shimano EP8 250 W Motor: 85 Nm, low noise, high performance
- Fully integrated 504 Wh battery ensures a range over 100 km*
- E-TUBE PROJECT: customized motor setting via the E-Tube Shimano application
- 1x11 gear setup for fluent pedaling frequency adjustment
- Responsive 120 mm Rock Shox air fork
- ICR (Internal Cable Routing): clean, modern looks without visible cables
- BlockLock headset: frame protected against damage by handlebars

GEOMETRY

FRAME SIZE	15.5" (S)	17" (M)	19" (L)	21" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74.5	74.5	74.5	74.5
EFFECTIVE TOP TUBE LENGTH (MM)	594	620	640	660
REACH (MM)	419	444	463	483
STACK HEIGHT (MM)	631	634	640	640
HEAD TUBE LENGTH (MM)	120	120	120	120
HEAD TUBE ANGLE (DEGREE)	66	66	67	67
CHAINSTAY LENGTH (MM)	445	445	445	445
BB DROP (MM)	54	54	54	54
WHEELBASE (MM)	1173	1190	1198	1218
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	60	80
CRANK LENGTH (MM)	165	165	165	170
SEAT POST LENGTH (MM)	400	400	400	400

FRAMESET

FRAME	Alu X6 Ultralite, Advanced eMTB Geometry, SHIMANO STEPS ready, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-1051, ICR, ZS56/28.6 ZS56/40; BlockLock 120°
FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 120mm travel
COLOUR	MATTE PETROL/CHROME SILVER
SIZES	15.5" (S), 17" (M), 19" (L), 21" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100 Shadow Plus
CRANKSET	SHIMANO FC-E8000, 34T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-320BT, 3° upsweep, 9° backsweep, 20mm rise, 760mm, 31.8mm
STEM	ONE1 TDS-661 Alloy, 31.8mm, 0°
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT420, hydraulic disc brake
SEAT POST	ONE1 Race Alloy, SP 218, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J30D, 32H
TIRES	Schwalbe Nobby Nic Evo Super Trail, 29x2.60", ADDIX Speedgrip
SPOKES	Sapim Leader, Stainless Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXP 9019

GLOSS WHITE/CHROME SILVER



E-MTB / SPORT

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS EP800, 36V, 250W, 85Nm
BATTERY	DARFON, 36V, 630 Wh, frame mount
DISPLAY	SHIMANO SC-EM800, Clamp band
CHARGER	DARFON 4A Smart Plus charger

BENEFITS

- Shimano EP8 250 W Motor: 85 Nm, low noise, high performance
- Fully integrated 504 Wh battery ensures a range over 100 km*
- E-TUBE PROJECT: customized motor setting via the E-Tube Shimano application
- 1x11 gear setup for fluent pedaling frequency adjustment
- Responsive 120 mm Rock Shox air fork
- ICR (Internal Cable Routing): clean, modern looks without visible cables
- BlockLock headset: frame protected against damage by handlebars

GEOMETRY

FRAME SIZE	15.5" (S)	17" (M)	19" (L)	21" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74.5	74.5	74.5	74.5
EFFECTIVE TOP TUBE LENGTH (MM)	594	620	640	660
REACH (MM)	419	444	463	483
STACK HEIGHT (MM)	631	634	640	640
HEAD TUBE LENGTH (MM)	120	120	120	120
HEAD TUBE ANGLE (DEGREE)	66	66	67	67
CHAINSTAY LENGTH (MM)	445	445	445	445
BB DROP (MM)	54	54	54	54
WHEELBASE (MM)	1173	1190	1198	1218
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	60	80
CRANK LENGTH (MM)	165	165	165	170
SEAT POST LENGTH (MM)	400	400	400	400

FRAMESET

FRAME	Alu X6 Ultralite, Advanced eMTB Geometry, SHIMANO STEPS ready, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-1051, ICR, ZS56/28.6 ZS56/40; BlockLock 120°
FORK	RockShox 35 Silver TK, Tapered, SoloAir, 15x110mm axle, 120mm travel
COLOUR	GLOSS WHITE/CHROME SILVER
SIZES	15.5" (S), 17" (M), 19" (L), 21" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100 Shadow Plus
CRANKSET	SHIMANO FC-E8000, 34T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
CHAIN	SHIMANO CN-M6100

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-320BT, 3° upsweep, 9° backsweep, 20mm rise, 760mm, 31.8mm
STEM	ONE1 TDS-661 Alloy, 31.8mm, 0°
GRIPS	ONE1 VLG-1907D2, ONE1 VLG-1962-11D2, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT420, hydraulic disc brake
SEAT POST	ONE1 Race Alloy, SP 218, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J30D, 32H
TIRES	Schwalbe Nobby Nic Evo Super Trail, 29x2.60", ADDIX Speedgrip
SPOKES	Sapim Leader, Stainless Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXP 8089

MATTE BLACK/CHROME SILVER



E-MTB / SPORT

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS EP800, 36V, 250W, 85Nm
BATTERY	DARFON, 36V, 504 Wh, integrated
DISPLAY	SHIMANO SC-E5000, Clamp band
CHARGER	DARFON 2A Smart Plus charger

BENEFITS

- Shimano EP8 250 W Motor: 85 Nm, low noise, high performance
- Full integrated 504 Wh battery ensures a range over 100 km*
- E-TUBE PROJECT: customized motor setting via the E-Tube Shimano application
- 1x11 gear setup for fluent pedaling frequency adjustment
- ICR (Internal Cable Routing): clean, modern looks without visible cables
- Block Lock headset: frame protected against damage by handlebars
- Four-piston brakes to stop the machine safely on any surface

GEOMETRY

FRAME SIZE	15.5" (S)	17" (M)	19" (L)	21" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74.5	74.5	74.5	74.5
EFFECTIVE TOP TUBE LENGTH (MM)	594	620	640	660
REACH (MM)	419	444	463	483
STACK HEIGHT (MM)	631	634	640	640
HEAD TUBE LENGTH (MM)	120	120	120	120
HEAD TUBE ANGLE (DEGREE)	66	66	67	67
CHAINSTAY LENGTH (MM)	445	445	445	445
BB DROP (MM)	54	54	54	54
WHEELBASE (MM)	1173	1190	1198	1218
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	60	80
CRANK LENGTH (MM)	165	165	165	170
SEAT POST LENGTH (MM)	400	400	400	400

FRAMESET

FRAME	Alu X6 Ultralite, Advanced eMTB Geometry, SHIMANO STEPS ready, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-1051, ICR, ZS56/28.6 ZS56/40; BlockLock 120°
COLOUR SIZES	MATTE BLACK/CHROME SILVER 15.5" (S), 17" (M), 19" (L), 21" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M5100-IR RapidFire Plus, 11-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5100 Shadow Plus
CRANKSET	SHIMANO FC-E6000, 34T
CASSETTE	SHIMANO CS-M5100-11, 11-51T
CHAIN	KMC e11T

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-325BT, 6° upsweep, 9° backsweep, 25mm rise, 720mm, 31.8mm
STEM	ONE1 TDS-661 Alloy, 31.8mm, 0°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT420, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Race Alloy, SP 218, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT400-B, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J30D, 32H
TIRES	Schwalbe Smart Sam KevlarGuard, 29x2.60"
SPOKES	Sapim Galvanized Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXP 8089

MATTE OLIVE METALLIC/CHROME SILVER



E-MTB / SPORT

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS EP800, 36V, 250W, 85Nm
BATTERY	DARFON, 36V, 504 Wh, integrated
DISPLAY	SHIMANO SC-E5000, Clamp band
CHARGER	DARFON 2A Smart Plus charger

BENEFITS

- Shimano EP8 250 W Motor: 85 Nm, low noise, high performance
- Full integrated 504 Wh battery ensures a range over 100 km*
- E-TUBE PROJECT: customized motor setting via the E-Tube Shimano application
- 1x11 gear setup for fluent pedaling frequency adjustment
- ICR (Internal Cable Routing): clean, modern looks without visible cables
- Block Lock headset: frame protected against damage by handlebars
- Four-piston brakes to stop the machine safely on any surface

GEOMETRY

FRAME SIZE	15.5" (S)	17" (M)	19" (L)	21" (XL)
WHEEL SIZE	29	29	29	29
SEAT TUBE LENGTH (MM)	393	431	482	533
SEAT TUBE ANGLE (DEGREE)	74.5	74.5	74.5	74.5
EFFECTIVE TOP TUBE LENGTH (MM)	594	620	640	660
REACH (MM)	419	444	463	483
STACK HEIGHT (MM)	631	634	640	640
HEAD TUBE LENGTH (MM)	120	120	120	120
HEAD TUBE ANGLE (DEGREE)	66	66	67	67
CHAINSTAY LENGTH (MM)	445	445	445	445
BB DROP (MM)	54	54	54	54
WHEELBASE (MM)	1173	1190	1198	1218
HANDLEBAR WIDTH (MM)	760	760	760	760
STEM LENGTH (MM)	60	60	60	80
CRANK LENGTH (MM)	165	165	165	170
SEAT POST LENGTH (MM)	400	400	400	400

FRAMESET

FRAME	Alu X6 Ultralite, Advanced eMTB Geometry, SHIMANO STEPS ready, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
HEAD SET	ACROS AZX-1051, ICR, ZS56/28.6 ZS56/40; BlockLock 120°
COLOUR SIZES	MATTE OLIVE METALLIC/CHROME SILVER 15.5" (S), 17" (M), 19" (L), 21" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M5100-IR RapidFire Plus, 11-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5100 Shadow Plus
CRANKSET	SHIMANO FC-E6000, 34T
CASSETTE	SHIMANO CS-M5100-11, 11-51T
CHAIN	KMC e11T

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-325BT, 6° upsweep, 9° backsweep, 25mm rise, 720mm, 31.8mm
STEM	ONE1 TDS-661 Alloy, 31.8mm, 0°
GRIPS	ONE1 VLG-1661D2N, Lock-On
BRAKES	SHIMANO BL-M4100/BR-MT420, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Race Alloy, SP 218, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB	SHIMANO FH-MT400-B, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS	Stars J30D, 32H
TIRES	Schwalbe Smart Sam KevlarGuard, 29x2.60"
SPOKES	Sapim Galvanized Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXC 7039 B

GLOSS GREY/ORANGE



E-MTB / SPORT

SPECIFICATION

E-BIKE

DRIVE UNIT	BOSCH PerformanceLine Cruise, 36V, 250W, 65Nm
BATTERY	BOSCH PowerTube 36V, 625Wh
DISPLAY	BOSCH Purion Anthracite, Clamp band
CHARGER	BOSCH 2A Compact charger

BENEFITS

- Bosch Performance Line drive unit: 250 W and 65 Nm
- The battery capacity of 625 Wh, and 150 km* range
- Remote lockout Suntour air fork
- Comfortable sports geometry
- Shimano Deore 1x11 groupset
- Kickstand, mudguards, and cargo rack optional

GEOMETRY

FRAME SIZE	17.5" (M)	19" (L)	21" (XL)
WHEEL SIZE	29	29	29
SEAT TUBE LENGTH (MM)	431	482	533
SEAT TUBE ANGLE (DEGREE)	73.5	73.5	73.5
EFFECTIVE TOP TUBE LENGTH (MM)	590	610	630
REACH (MM)	401	422	441
STACK HEIGHT (MM)	636	636	636
HEAD TUBE LENGTH (MM)	130	130	130
HEAD TUBE ANGLE (DEGREE)	68	68	68
CHAINSTAY LENGTH (MM)	500	500	500
BB DROP (MM)	60	60	60
WHEELBASE (MM)	1180	1200	1220
HANDLEBAR WIDTH (MM)	720	720	720
STEM LENGTH (MM)	70	70	90
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	400

FRAMESET

FRAME	Alu 6061 T6, Sport eMTB Geometry, Smooth Welding, Bosch system Powertube 625Wh battery ready, Inner Cable Routing
HEAD SET	ACROS AZX-254, ZS44/28.6 EC49/30, BlockLock 150°
COLOUR	GLOSS GREY/ORANGE
SIZES	17.5" (M), 19" (L), 21" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M5100-R RapidFire Plus, 11-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M4120 Shadow
CRANKSET	ONE1 EC33-BH3-F9-BNI-L/R, 38T
CASSETTE	SHIMANO CS-M5100-11, 11-42T
CHAIN	KMC e11T
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-325BT, 6° upsweep, 9° backsweep, 25mm rise, 720mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J30D, 32H
TIRES	Schwalbe Hurricane Performance, 29x2.25", ADDIX
SPOKES	Sapim Galvanized Black

eXC 7039 WB

MATTE DARK PURPLE/PINK



E-MTB / SPORT

SPECIFICATION

E-BIKE

DRIVE UNIT	BOSCH PerformanceLine Cruise, 36V, 250W, 65Nm
BATTERY	BOSCH PowerTube 36V, 625Wh
DISPLAY	BOSCH Purion Anthracite, Clamp band
CHARGER	BOSCH 2A Compact charger

BENEFITS

- Bosch Performance Line drive unit: 250 W and 65 Nm
- The battery capacity of 625 Wh, and 150 km* range
- Remote lockout Suntour air fork
- Comfortable sports-touring geometry
- Shimano Deore 1x11 groupset
- Kickstand, mudguards, and cargo rack optional

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)
WHEEL SIZE	29	29
SEAT TUBE LENGTH (MM)	406	457
SEAT TUBE ANGLE (DEGREE)	73,5	73,5
EFFECTIVE TOP TUBE LENGTH (MM)	570	590
REACH (MM)	382	402
STACK HEIGHT (MM)	636	636
HEAD TUBE LENGTH (MM)	130	130
HEAD TUBE ANGLE (DEGREE)	68	68
CHAINSTAY LENGTH (MM)	500	500
BB DROP (MM)	60	60
WHEELBASE (MM)	1160	1180
HANDLEBAR WIDTH (MM)	660	660
STEM LENGTH (MM)	70	70
CRANK LENGTH (MM)	170	170
SEAT POST LENGTH (MM)	350	350

FRAMESET

FRAME	Alu 6061 T6, Sport eMTB Woman Geometry, Smooth Welding, Bosch system Powertube 625Wh battery ready, Inner Cable Routing
HEAD SET	ACROS AZX-254, ZS44/28.6 EC49/30, BlockLock 150°
COLOUR	MATTE DARK PURPLE/PINK
SIZES	15.5" (S), 17.5" (M)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M5100-R RapidFire Plus, 11-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M4120 Shadow
CRANKSET	ONE1 EC33-BH3-F9-BNI-L/R, 38T
CASSETTE	SHIMANO CS-M5100-11, 11-42T
CHAIN	KMC e11T
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-325BT, 6° upsweep, 9° backsweep, 25mm rise, 660mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo DRN
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J30D, 32H
TIRES	Schwalbe Hurricane Performance, 29x2.25", ADDIX
SPOKES	Sapim Galvanized Black

eXC 7019 B

GLOSS DARK RED/CHROME SILVER



E-MTB / SPORT

SPECIFICATION

E-BIKE

DRIVE UNIT	BOSCH ActiveLine Plus, 36V, 250W, 50Nm
BATTERY	BOSCH PowerTube 36V, 500Wh
DISPLAY	BOSCH Purion Anthracite, Clamp band
CHARGER	BOSCH 2A Compact charger

BENEFITS

- Bosch Active Line Plus powerful drive unit: 250 W and 50 Nm
- PowerTube battery with a capacity of 500 Wh for a range of up to 100 km*
- Comfortable sports-touring geometry
- Kickstand, mudguards, and cargo rack optional

GEOMETRY

FRAME SIZE	17.5 s	19	21
WHEEL SIZE	29	29	29
SEAT TUBE LENGTH (MM)	431	482	533
SEAT TUBE ANGLE (DEGREE)	73.5	73.5	73.5
EFFECTIVE TOP TUBE LENGTH (MM)	590	610	630
REACH (MM)	401	422	441
STACK HEIGHT (MM)	636	636	636
HEAD TUBE LENGTH (MM)	130	130	130
HEAD TUBE ANGLE (DEGREE)	68	68	68
CHAINSTAY LENGTH (MM)	500	500	500
BB DROP (MM)	60	60	60
WHEELBASE (MM)	1180	1200	1220
HANDLEBAR WIDTH (MM)	720	720	720
STEM LENGTH (MM)	70	70	90
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	400

FRAMESET

FRAME	Alu 6061 T6, Sport eMTB Geometry, Smooth Welding, Bosch system Powertube 625Wh battery ready, Inner Cable Routing
HEAD SET	ACROS AZX-254, ZS44/28.6 EC49/30, BlockLock 150°
COLOUR	GLOSS DARK RED/CHROME SILVER
SIZES	17.5 s, 19, 21

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	ONE1 EC33-BH3-F9-BNI-L/R, 38T
CASSETTE	SHIMANO CS-HG200-9, 11-36T
CHAIN	KMC E9s
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-325BT, 6° upsweep, 9° backsweep, 25mm rise, 720mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J30D, 32H
TIRES	Schwalbe Hurricane Performance, 29x2.25", ADDIX
SPOKES	Sapim Galvanized Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXC 7019 WB

GLOSS WHITE/PINK/VIOLET



E-MTB / SPORT

SPECIFICATION

E-BIKE

DRIVE UNIT	BOSCH ActiveLine Plus, 36V, 250W, 50Nm
BATTERY	BOSCH PowerTube 36V, 500Wh
DISPLAY	BOSCH Purion Anthracite, Clamp band
CHARGER	BOSCH 2A Compact charger

BENEFITS

- Bosch Active Line Plus powerful drive unit: 250 W and 50 Nm
- PowerTube battery with a capacity of 500 Wh for a range of up to 100 km*
- Comfortable sports-touring geometry
- Kickstand, mudguards, and cargo rack optional

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)
WHEEL SIZE	29	29
SEAT TUBE LENGTH (MM)	406	457
SEAT TUBE ANGLE (DEGREE)	73,5	73,5
EFFECTIVE TOP TUBE LENGTH (MM)	570	590
REACH (MM)	382	402
STACK HEIGHT (MM)	636	636
HEAD TUBE LENGTH (MM)	130	130
HEAD TUBE ANGLE (DEGREE)	68	68
CHAINSTAY LENGTH (MM)	500	500
BB DROP (MM)	60	60
WHEELBASE (MM)	1160	1180
HANDLEBAR WIDTH (MM)	660	660
STEM LENGTH (MM)	70	70
CRANK LENGTH (MM)	170	170
SEAT POST LENGTH (MM)	350	350

FRAMESET

FRAME	Alu 6061 T6, Sport eMTB Woman Geometry, Smooth Welding, Bosch system Powertube 625Wh battery ready, Inner Cable Routing
HEAD SET	ACROS AZX-254, ZS44/28.6 EC49/30, BlockLock 150°
COLOUR	GLOSS WHITE/PINK/VIOLET
SIZES	15.5" (S), 17.5" (M)

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	ONE1 EC33-BH3-F9-BNI-L/R, 38T
CASSETTE	SHIMANO CS-HG200-9, 11-36T
CHAIN	KMC E9s
PEDALS	Marwi SP-610

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-325BT, 6° upsweep, 9° backsweep, 25mm rise, 660mm, 31.8mm
STEM	ONE1 Sport MAS-D61248 Alloy, 31.8mm, -8°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo DRN
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J30D, 32H
TIRES	Schwalbe Hurricane Performance, 29x2.25", ADDIX
SPOKES	Sapim Galvanized Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXR 6090 Touring

MATTE OLIVE METALLIC/CHROME SILVER



E-TOUR / CROSS

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS EP800, 36V, 250W, 85Nm
BATTERY	DARFON, 36V, 504 Wh, integrated
DISPLAY	SHIMANO SC-E5000, Clamp band
CHARGER	DARFON 4A Smart Plus charger

BENEFITS

- Shimano Steps E7000 motor: 250 W and 60 Nm
- Fully integrated 500 Wh battery ensures a range over 100 km*
- E-TUBE PROJECT: customized motor setting via the E-Tube Shimano application
- Shimano Deore 1x12 setup to master steep hills and fast rides
- ICR (Internal Cable Routing): clean, modern looks without visible cables
- BlockLock headset: frame protected against damage by handlebars
- Fully equipped, with a cargo rack, mudguards, kickstand, chain guard, and lights

GEOMETRY

FRAME SIZE	17" (M)	19" (L)	21" (XL)
WHEEL SIZE	28	28	28
SEAT TUBE LENGTH (MM)	431	482	533
SEAT TUBE ANGLE (DEGREE)	73.5	73.5	73.5
EFFECTIVE TOP TUBE LENGTH (MM)	590	610	630
REACH (MM)	411	431	451
STACK HEIGHT (MM)	604	604	604
HEAD TUBE LENGTH (MM)	120	120	120
HEAD TUBE ANGLE (DEGREE)	68	68	68
CHAINSTAY LENGTH (MM)	450	450	450
BB DROP (MM)	60	60	60
WHEELBASE (MM)	1126	1146	1166
HANDLEBAR WIDTH (MM)	720	720	720
STEM LENGTH (MM)	60	80	80
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	350

FRAMESET

HEAD SET ACROS AZX-1051, ICR, ZS56/28.6 | ZS56/40; BlockLock 120°

COLOUR MATTE OLIVE METALLIC/CHROME SILVER
SIZES 17" (M), 19" (L), 21" (XL)

DRIVETRAIN

SHIFTER SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR SHIMANO DEORE RD-M6100 Shadow Plus
CRANKSET SHIMANO FC-E6000, 34T
CASSETTE SHIMANO CS-M6100-12, 10-51T
CHAIN SHIMANO CN-M6100
PEDALS VP Components VP-836

COMPONENTS

STEM ONE1 TDS-661 Alloy, 31.8mm, 0°
GRIPS Velo VLG-1777D2
BRAKES SHIMANO BL-M4100/BR-MT420, hydraulic disc brake
SADDLE Selle Royal LIFT
SEAT POST ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS Stars J30D, 32H
SPOKES Sapim Leader, Stainless Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXR 6090 L Touring

MATTE OLIVE METALLIC/CHROME SILVER



E-TOUR / CROSS

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS EP800, 36V, 250W, 85Nm
BATTERY	DARFON, 36V, 504 Wh, integrated
DISPLAY	SHIMANO SC-E5000, Clamp band
CHARGER	DARFON 4A Smart Plus charger

BENEFITS

- Shimano Steps E6100 motor: 250 W and 60 Nm
- Fully integrated 500 Wh battery ensures a range over 150 km*
- E-TUBE PROJECT: customized motor setting via the E-Tube Shimano application
- Shimano Deore 1x10 gear setup
- ICR (Internal Cable Routing): clean, modern looks without visible cables
- BlockLock headset: frame protected against damage by handlebars
- Fully equipped, with a cargo rack, mudguards, kickstand, chain guard, and lights

GEOMETRY

FRAME SIZE	16.5" (S)	18" (L)
WHEEL SIZE	28	28
SEAT TUBE LENGTH (MM)	420	457
SEAT TUBE ANGLE (DEGREE)	73.5	73.5
EFFECTIVE TOP TUBE LENGTH (MM)	580	595
REACH (MM)	401	416
STACK HEIGHT (MM)	604	604
HEAD TUBE LENGTH (MM)	120	120
HEAD TUBE ANGLE (DEGREE)	68	68
CHAINSTAY LENGTH (MM)	450	450
BB DROP (MM)	60	60
WHEELBASE (MM)	1117	1131
HANDLEBAR WIDTH (MM)	720	720
STEM LENGTH (MM)	60	60
CRANK LENGTH (MM)	170	170
SEAT POST LENGTH (MM)	350	350

FRAMESET

HEAD SET ACROS AZX-1051, ICR, ZS56/28.6 | ZS56/40; BlockLock 120°

COLOUR MATTE OLIVE METALLIC/CHROME SILVER
SIZES 16.5" (S), 18" (L)

DRIVETRAIN

SHIFTER SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR SHIMANO DEORE RD-M6100 Shadow Plus
CRANKSET SHIMANO FC-E6000, 34T
CASSETTE SHIMANO CS-M6100-12, 10-51T
CHAIN SHIMANO CN-M6100
PEDALS VP Components VP-836

COMPONENTS

STEM ONE1 TDS-661 Alloy, 31.8mm, 0°
GRIPS Velo VLG-1777D2
BRAKES SHIMANO BL-M4100/BR-MT420, hydraulic disc brake
SADDLE Selle Royal LIFT
SEAT POST ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB SHIMANO HB-MT410-B, 32H, CENTER LOCK, 15x110mm THRU Type AXLE
REAR HUB SHIMANO FH-MT410, 32H, CENTER LOCK, 12x148mm THRU Type AXLE
RIMS Stars J30D, 32H
SPOKES Sapim Leader, Stainless Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXR 6090 B Touring

MATTE BLACK/CHROME SILVER



E-TOUR / CROSS

SPECIFICATION

E-BIKE

DRIVE UNIT	BOSCH PerformanceLine Cruise, 36V, 250W, 65Nm
BATTERY	BOSCH PowerTube 36V, 625Wh
DISPLAY	BOSCH Purion Anthracite, Clamp band
CHARGER	BOSCH 2A Compact charger

BENEFITS

- Bosch Performance Line drive unit: 250 W and 65 Nm
- The battery capacity of 625 Wh, and range up to 150 km*
- Remote lockout Rock Shox Paragon air fork
- Comfortable sports-touring geometry
- Shimano Deore 1x12 setup
- Fully equipped, with a cargo rack, mudguards, kickstand, chain guard, lights, and safety lock

GEOMETRY

FRAME SIZE	17" (M)	19" (L)	21" (XL)
WHEEL SIZE	28	28	28
SEAT TUBE LENGTH (MM)	431	482	533
SEAT TUBE ANGLE (DEGREE)	73.5	73.5	73.5
EFFECTIVE TOP TUBE LENGTH (MM)	590	610	630
REACH (MM)	409	429	449
STACK HEIGHT (MM)	610	610	610
HEAD TUBE LENGTH (MM)	130	130	130
HEAD TUBE ANGLE (DEGREE)	68	68	68
CHAINSTAY LENGTH (MM)	495	495	495
BB DROP (MM)	60	60	60
WHEELBASE (MM)	1172	1192	1212
HANDLEBAR WIDTH (MM)	720	720	720
STEM LENGTH (MM)	60	80	80
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	350

FRAMESET

FRAME	Alu 6061 T6, Comfort Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
HEAD SET	ACROS AZX-1051, ICR, ZS56/28.6 ZS56/40; BlockLock 120°
COLOUR	MATTE BLACK/CHROME SILVER
SIZES	17" (M), 19" (L), 21" (XL)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100 Shadow Plus
CRANKSET	ONE1 EC33-BH3-F9-BNI-L/R, 38T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
CHAIN	SHIMANO CN-M6100
PEDALS	VP Components VP-836

COMPONENTS

STEM	ONE1 TDS-661 Alloy, 31.8mm, 0°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-M4100/BR-MT420, hydraulic disc brake, SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SADDLE	Selle Royal LIFT
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-MT401, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J26S, 32H
TIRES	Schwalbe G-One Bite, 28x2.00", reflective tape
SPOKES	Sapim Leader, Stainless Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXR 6090 BL Touring

MATTE BLACK/CHROME SILVER



E-TOUR / CROSS

SPECIFICATION

E-BIKE

DRIVE UNIT	BOSCH PerformanceLine Cruise, 36V, 250W, 65Nm
BATTERY	BOSCH PowerTube 36V, 625Wh
DISPLAY	BOSCH Purion Anthracite, Clamp band
CHARGER	BOSCH 2A Compact charger

BENEFITS

- Powerful Bosch Performance Line drive unit: 250 W and 65 Nm
- The battery capacity of 625 Wh, and range up to 150 km*
- Remote lockout Rock Shox Paragon air fork
- Comfortable sports-touring geometry
- Shimano Deore 1x12 setup
- Fully equipped, with a cargo rack, mudguards, kickstand, chain guard, lights, and safety lock

GEOMETRY

FRAME SIZE	16.5" (S)	18" (L)
WHEEL SIZE	28	28
SEAT TUBE LENGTH (MM)	420	457
SEAT TUBE ANGLE (DEGREE)	73.5	73.5
EFFECTIVE TOP TUBE LENGTH (MM)	585	595
REACH (MM)	401	410
STACK HEIGHT (MM)	620	604
HEAD TUBE LENGTH (MM)	140	140
HEAD TUBE ANGLE (DEGREE)	68	68
CHAINSTAY LENGTH (MM)	495	495
BB DROP (MM)	60	60
WHEELBASE (MM)	1168	1178
HANDLEBAR WIDTH (MM)	720	720
STEM LENGTH (MM)	60	60
CRANK LENGTH (MM)	170	170
SEAT POST LENGTH (MM)	350	350

FRAMESET

FRAME	Alu 6061 T6, Comfort Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
HEAD SET	ACROS AZX-1051, ICR, ZS56/28.6 ZS56/40; BlockLock 120°
COLOUR	MATTE BLACK/CHROME SILVER
SIZES	16.5" (S), 18" (L)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100 Shadow Plus
CRANKSET	ONE1 EC33-BH3-F9-BNI-L/R, 38T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
CHAIN	SHIMANO CN-M6100
PEDALS	VP Components VP-836

COMPONENTS

STEM	ONE1 TDS-661 Alloy, 31.8mm, 0°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-M4100/BR-MT420, hydraulic disc brake, SHIMANO BL-M4100/BR-MT410, hydraulic disc brake
SADDLE	Selle Royal LIFT
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-MT401, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J26S, 32H
TIRES	Schwalbe G-One Bite, 28x2.00", reflective tape
SPOKES	Sapim Leader, Stainless Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXR 6090 BLS Touring

MATTE BLACK/CHROME SILVER



E-TOUR / CROSS

SPECIFICATION

E-BIKE

DRIVE UNIT	BOSCH PerformanceLine Cruise, 36V, 250W, 65Nm
BATTERY	BOSCH PowerTube 36V, 500Wh
DISPLAY	BOSCH Purion Anthracite, Clamp band
CHARGER	BOSCH 2A Compact charger

BENEFITS

- Powerful Bosch Performance Line drive unit: 250 W and 65 Nm
- The battery capacity of 500 Wh, and range up to 100 km*
- Remote lockout Rock Shox Paragon air fork
- New LowStep easy to hop on frame
- Fully equipped, with a cargo rack, mudguards, kickstand, chain guard, lights, and safety lock

GEOMETRY

FRAME SIZE	16.5" (S)	18" (L)
WHEEL SIZE	28	28
SEAT TUBE LENGTH (MM)	420	457
SEAT TUBE ANGLE (DEGREE)	73.5	73.5
EFFECTIVE TOP TUBE LENGTH (MM)	585	595
REACH (MM)	394.6	404.6
STACK HEIGHT (MM)	642.9	642.9
HEAD TUBE LENGTH (MM)	160	160
HEAD TUBE ANGLE (DEGREE)	69	69
CHAINSTAY LENGTH (MM)	495	495
BB DROP (MM)	60	60
WHEELBASE (MM)	1159	1169
HANDLEBAR WIDTH (MM)	660	660
STEM LENGTH (MM)	60	60
CRANK LENGTH (MM)	170	170
SEAT POST LENGTH (MM)	350	350

FRAMESET

FRAME	Alu 6061 T6, Comfort Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
HEAD SET	ACROS AZX-1051, ICR, ZS56/28.6 ZS56/40; BlockLock 120°
COLOUR	MATTE BLACK/CHROME SILVER
SIZES	16.5" (S), 18" (L)

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6100-IR RapidFire Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100 Shadow Plus
CRANKSET	ONE1 EC33-BH3-F9-BNI-L/R, 38T
CASSETTE	SHIMANO CS-M6100-12, 10-51T
CHAIN	SHIMANO CN-M6100
PEDALS	VP Components VP-836

COMPONENTS

STEM	ONE1 TDS-661 Alloy, 31.8mm, 0°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-M4100/BR-MT410, hydraulic disc brake, SHIMANO BL-M4100/BR-MT420, hydraulic disc brake
SADDLE	Selle Royal LIFT
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-MT401, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J26S, 32H
TIRES	Schwalbe G-One Bite, 28x2.00", reflective tape
SPOKES	Sapim Leader, Stainless Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXR 6050 B Touring

GLOSS GRAY/CHROME SILVER



E-TOUR / CROSS

SPECIFICATION

E-BIKE

DRIVE UNIT	BOSCH ActiveLine Plus, 36V, 250W, 50Nm
BATTERY	BOSCH PowerTube 36V, 500Wh
DISPLAY	BOSCH Purion Anthracite, Clamp band
CHARGER	BOSCH 2A Compact charger

BENEFITS

- Powerful Bosch Active Line motor: 250 W and 50 Nm
- PowerTube battery with a capacity of 500 Wh, and 140 km* range
- Comfortable sports-touring geometry
- Simple and intuitive 1x9 gear setup
- Fully equipped, with a cargo rack, mudguards, kickstand, chain guard, night lights, and lock

GEOMETRY

FRAME SIZE	17" (M)	19" (L)	21" (XL)
WHEEL SIZE	28	28	28
SEAT TUBE LENGTH (MM)	431	482	533
SEAT TUBE ANGLE (DEGREE)	73.5	73.5	73.5
EFFECTIVE TOP TUBE LENGTH (MM)	590	610	630
REACH (MM)	409	429	449
STACK HEIGHT (MM)	610	610	610
HEAD TUBE LENGTH (MM)	130	130	130
HEAD TUBE ANGLE (DEGREE)	68	68	68
CHAINSTAY LENGTH (MM)	495	495	495
BB DROP (MM)	60	60	60
WHEELBASE (MM)	1172	1192	1212
HANDLEBAR WIDTH (MM)	720	720	720
STEM LENGTH (MM)	60	80	80
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	350

FRAMESET

FRAME	Alu 6061 T6, Comfort Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
HEAD SET	ACROS AZF-604, ZS56/28.6 ZS56/40; BlockLock 120°
COLOUR	GLOSS GRAY/CHROME SILVER
SIZES	17" (M), 19" (L), 21" (XL)

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	ONE1 EC33-BH3-F9-BNI-L/R, 38T
CASSETTE	SHIMANO CS-HG200-9, 11-36T
CHAIN	KMC E9s
PEDALS	VP Components VP-836

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-320BT, 3° upsweep, 15° backsweep, 20mm rise, 680mm, 31.8mm
STEM	ONE1 Python Alloy, 31.8mm, Adjustable
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J26S, 32H
TIRES	Schwalbe G-One Bite, 28x2.00", reflective tape
SPOKES	Sapim Galvanized Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXR 6050 BL Touring

GLOSS GRAY/CHROME SILVER



E-TOUR / CROSS

SPECIFICATION

E-BIKE

DRIVE UNIT	BOSCH ActiveLine Plus, 36V, 250W, 50Nm
BATTERY	BOSCH PowerTube 36V, 500Wh
DISPLAY	BOSCH Purion Anthracite, Clamp band
CHARGER	BOSCH 2A Compact charger

BENEFITS

- Powerful Bosch Active Line motor: 250 W and 50 Nm
- PowerTube battery with a capacity of 500 Wh, and 140 km* range
- Comfortable sports-touring geometry
- Simple and intuitive 1x9 gear setup
- Fully equipped, with a cargo rack, mudguards, kickstand, chain guard, night lights, and lock

GEOMETRY

FRAME SIZE	16.5" (S)	18" (L)
WHEEL SIZE	28	28
SEAT TUBE LENGTH (MM)	420	457
SEAT TUBE ANGLE (DEGREE)	73.5	73.5
EFFECTIVE TOP TUBE LENGTH (MM)	585	595
REACH (MM)	401	410
STACK HEIGHT (MM)	620	604
HEAD TUBE LENGTH (MM)	140	140
HEAD TUBE ANGLE (DEGREE)	68	68
CHAINSTAY LENGTH (MM)	495	495
BB DROP (MM)	60	60
WHEELBASE (MM)	1168	1178
HANDLEBAR WIDTH (MM)	720	720
STEM LENGTH (MM)	60	60
CRANK LENGTH (MM)	170	170
SEAT POST LENGTH (MM)	350	350

FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system Powertube 625Wh battery ready, Inner Cable Routing
HEAD SET	ACROS AZF-604, ZS56/28.6 ZS56/40; BlockLock 120°
COLOUR	GLOSS GRAY/CHROME SILVER
SIZES	16.5" (S), 18" (L)

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	ONE1 EC33-BH3-F9-BNI-L/R, 38T
CASSETTE	SHIMANO CS-HG200-9, 11-36T
CHAIN	KMC E9s
PEDALS	VP Components VP-836

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-320BT, 3° upsweep, 15° backsweep, 20mm rise, 680mm, 31.8mm
STEM	ONE1 Python Alloy, 31.8mm, Adjustable
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo DRN
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J26S, 32H
TIRES	Schwalbe G-One Bite, 28x2.00", reflective tape
SPOKES	Sapim Galvanized Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXR 6050 BLS Touring

GLOSS GRAY/CHROME SILVER



E-TOUR / CROSS

SPECIFICATION

E-BIKE

DRIVE UNIT	BOSCH ActiveLine Plus, 36V, 250W, 50Nm
BATTERY	BOSCH PowerTube 36V, 500Wh
DISPLAY	BOSCH Purion Anthracite, Clamp band
CHARGER	BOSCH 2A Compact charger

BENEFITS

- Powerful Bosch Active Line motor: 250 W and 50 Nm
- PowerTube battery with a capacity of 500 Wh, and 140 km* range
- New, easy to hop on, comfortable geometry LowStep frame
- Simple 1x9 gear setup
- Fully equipped, with a cargo rack, mudguards, kickstand, chain guard, night lights, and lock

GEOMETRY

FRAME SIZE	16.5" (S)	18" (L)
WHEEL SIZE	28	28
SEAT TUBE LENGTH (MM)	420	457
SEAT TUBE ANGLE (DEGREE)	73.5	73.5
EFFECTIVE TOP TUBE LENGTH (MM)	585	595
REACH (MM)	394.6	404.6
STACK HEIGHT (MM)	642.9	642.9
HEAD TUBE LENGTH (MM)	160	160
HEAD TUBE ANGLE (DEGREE)	69	69
CHAINSTAY LENGTH (MM)	495	495
BB DROP (MM)	60	60
WHEELBASE (MM)	1159	1169
HANDLEBAR WIDTH (MM)	660	660
STEM LENGTH (MM)	60	60
CRANK LENGTH (MM)	170	170
SEAT POST LENGTH (MM)	350	350

FRAMESET

FRAME	Alu 6061 T6, Comfort Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
HEAD SET	ACROS AZF-604, ZS56/28.6 ZS56/40; BlockLock 120°
COLOUR	GLOSS GRAY/CHROME SILVER
SIZES	16.5" (S), 18" (L)

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	ONE1 EC33-BH3-F9-BNI-L/R, 38T
CASSETTE	SHIMANO CS-HG200-9, 11-36T
CHAIN	KMC E9s
PEDALS	VP Components VP-836

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-320BT, 3° upsweep, 15° backsweep, 20mm rise, 680mm, 31.8mm
STEM	ONE1 Python Alloy, 31.8mm, Adjustable
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	fizik Vivo
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J26S, 32H
TIRES	Schwalbe G-One Bite, 28x2.00", reflective tape
SPOKES	Sapim Galvanized Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXR 6030 Touring

MATTE COPPER/CHROME SILVER



E-TOUR / CROSS

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS E5000, 36V, 250W, 40Nm
BATTERY	DARFON, 36V, 504 Wh, integrated
DISPLAY	SHIMANO SC-E5000, Clamp band
CHARGER	DARFON 2A Smart Plus charger

BENEFITS

- Shimano Steps E5000 motor: 250 W and 40 Nm
- Full integrated 504 Wh battery ensures a range over 150 km*
- E-TUBE PROJECT: customized motor setting via the E-Tube Shimano application
- Simple and intuitive 1x9 gear setup
- ICR (Internal Cable Routing): clean, modern looks without visible cables
- BlockLock headset: frame protected against damage by handlebars
- Fully equipped, with a cargo rack, mudguards, kickstand, chain guard, night lights, and lock

GEOMETRY

FRAME SIZE	17" (M)	19" (L)	21" (XL)
WHEEL SIZE	28	28	28
SEAT TUBE LENGTH (MM)	431	482	533
SEAT TUBE ANGLE (DEGREE)	73.5	73.5	73.5
EFFECTIVE TOP TUBE LENGTH (MM)	590	610	630
REACH (MM)	409	429	449
STACK HEIGHT (MM)	610	610	610
HEAD TUBE LENGTH (MM)	130	130	130
HEAD TUBE ANGLE (DEGREE)	68	68	68
CHAINSTAY LENGTH (MM)	450	450	450
BB DROP (MM)	60	60	60
WHEELBASE (MM)	1127	1146	1167
HANDLEBAR WIDTH (MM)	680	680	680
STEM LENGTH (MM)	60	80	80
CRANK LENGTH (MM)	170	170	170
SEAT POST LENGTH (MM)	350	350	350

FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, SHIMANO STEPS ready, NEW integrated battery, Inner Cable Routing
HEAD SET	ACROS AZF-604, ZS56/28.6 ZS56/40; BlockLock 120°
COLOUR	MATTE COPPER/CHROME SILVER
SIZES	17" (M), 19" (L), 21" (XL)

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	SHIMANO FC-E5000, 38T
CASSETTE	SHIMANO CS-HG200-9, 11-36T
CHAIN	KMC E9s
PEDALS	VP Components VP-836

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-320BT, 3° upsweep, 15° backsweep, 20mm rise, 680mm, 31.8mm
STEM	ONE1 Python Alloy, 31.8mm, Adjustable
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo HRN
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J26S, 32H
TIRES	Schwalbe G-One Bite, 28x2.00", reflective tape
SPOKES	Sapim Galvanized Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

eXR 6030 L Touring

MATTE COPPER/CHROME SILVER



GRAPHIC SIMULATION ONLY / REAL PICTURE SOON

E-TOUR / CROSS

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS E5000, 36V, 250W, 40Nm
BATTERY	DARFON, 36V, 504 Wh, integrated
DISPLAY	SHIMANO SC-E5000, Clamp band
CHARGER	DARFON 2A Smart Plus charger

BENEFITS

- Shimano Steps E5000 motor: 250 W and 40 Nm
- Fully integrated 504 Wh battery ensures a range over 150 km*
- E-TUBE PROJECT: customized motor setting via the E-Tube Shimano application
- Simple and intuitive 1x9 gear setup
- ICR (Internal Cable Routing): clean, modern looks without visible cables
- BlockLock headset: frame protected against damage by handlebars
- Fully equipped, with a cargo rack, mudguards, kickstand, chain guard, night lights, and lock

GEOMETRY

FRAME SIZE	16.5" (S)	18" (L)
WHEEL SIZE	28	28
SEAT TUBE LENGTH (MM)	420	457
SEAT TUBE ANGLE (DEGREE)	73.5	73.5
EFFECTIVE TOP TUBE LENGTH (MM)	585	595
REACH (MM)	401	410
STACK HEIGHT (MM)	620	620
HEAD TUBE LENGTH (MM)	140	140
HEAD TUBE ANGLE (DEGREE)	68	68
CHAINSTAY LENGTH (MM)	450	450
BB DROP (MM)	60	60
WHEELBASE (MM)	1123	1131
HANDLEBAR WIDTH (MM)	680	680
STEM LENGTH (MM)	60	60
CRANK LENGTH (MM)	170	170
SEAT POST LENGTH (MM)	350	350

FRAMESET

FRAME	Alu 6061 T6, Touring Geometry, Smooth Welding, SHIMANO STEPS ready, NEW integrated battery, Inner Cable Routing
HEAD SET	ACROS AZF-604, ZS56/28.6 ZS56/40; BlockLock 120°
COLOUR	MATTE COPPER/CHROME SILVER
SIZES	16.5" (S), 18" (L)

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	SHIMANO FC-E5000, 38T
CASSETTE	SHIMANO CS-HG200-9, 11-36T
CHAIN	KMC E9s
PEDALS	VP Components VP-836

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-320BT, 3° upsweep, 15° backsweep, 20mm rise, 680mm, 31.8mm
STEM	ONE1 Python Alloy, 31.8mm, Adjustable
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Vivo DRN
SEAT POST	ONE1 Sport Alloy, SP C207, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 32H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 32H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J26S, 32H
TIRES	Schwalbe G-One Bite, 28x2.00", reflective tape
SPOKES	Sapim Galvanized Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

SBT 600i L

MATTE TITANIUM



E-URBAN

SPECIFICATION

E-BIKE

DRIVE UNIT	BOSCH ActiveLine Plus, 36V, 250W, 50Nm
BATTERY	BOSCH PowerTube 36V, 500Wh
DISPLAY	BOSCH Intuvia Anthracite , Clamp band
CHARGER	BOSCH 2A Compact charger

BENEFITS

- Powerful Bosh Active Line Plus drive unit with a power of 250 W and 50 Nm
- PowerTube battery with the capacity of 500 Wh and the range up to 140 km*
- New LowStep frame with easy on/off and comfortable geometry
- Ready to City: fenders, lights, AXA lock, kickstand, etc.

FRAMESET

HEAD SET	FSA No.10 Semi-Cartrige
FORK	SR Suntour NEX-DS, 1-1/8", Coil, QR Type, 50mm travel
COLOUR	MATTE TITANIUM
SIZES	

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6000-R RapidFire Plus, 10-speed
REAR DERAILLEUR	SHIMANO DEORE RD-T6000 Shadow
CRANKSET	ONE1 EC33-BH3-F9-BNI-L/R, 38T
CASSETE	SHIMANO CS-HG500-10, 11-34T
CHAIN	KMC e10S
PEDALS	Marwi SP-823

COMPONENTS

HANDLEBAR	ONE1 Alloy, NRAL124BT, 38° backsweep, 38mm rise, 620mm, 31.8mm
STEM	ONE1 TDS-C2698 Alloy, 31.8mm, 0°/+90°
GRIPS	HERRMANS LINE DD36BR, HERRMANS LINE DD36BL
SADDLE	Selle Royal Nuvola
SEAT POST	ONE1 Alloy, SP S405, 30.9mm

WHEELS

FRONT HUB	SHIMANO HB-M3050, 36H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-M3050, 36H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J19DC, 36H
TIRES	CST Scalato Mondano, 28x2.00", reflective tape
SPOKES	Sapim Leader, Stainless Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

SBT 300 L

GLOSS DARK GREY



E-URBAN

SPECIFICATION

E-BIKE

DRIVE UNIT	BOSCH ActiveLine Plus, 36V, 250W, 50Nm
DISPLAY	BOSCH Purion Anthracite , Clamp band
CHARGER	BOSCH 2A Compact charger

BENEFITS

- Powerful Bosh Active Line Plus drive unit with a power of 250 W and 50 Nm
- Carrier battery with the capacity of 500 Wh and the range up to 140 km*
- New LowStep frame with easy on/off and comfortable geometry
- Ready to City: fenders, lights, AXA lock, kickstand, etc.

FRAMESET

HEAD SET	FSA TH-805ST Semi-Cartridge, 1-1/8"
FORK	SR Suntour NEX-DS, 1-1/8", Coil, QR Type, 50mm travel
COLOUR	GLOSS DARK GREY
SIZES	

DRIVETRAIN

SHIFTER	SHIMANO DEORE SL-M6000-R RapidFire Plus, 10-speed
REAR DERAILLEUR	SHIMANO DEORE RD-T6000 Shadow
CRANKSET	Wheel Top ICMA-BNI-L/R, 38T
CASSETTE	SHIMANO CS-HG500-10, 11-34T
CHAIN	KMC e10S
PEDALS	Marwi SP-823

COMPONENTS

HANDLEBAR	ONE1 Alloy, NRAL124BT, 38° backsweep, 38mm rise, 620mm, 31.8mm
STEM	ONE1 MTS-C2695 Alloy, 31.8mm, 0°/+90°
GRIPS	HERRMANS LINE DD36BR, HERRMANS LINE DD36BL
SADDLE	Selle Royal Nuvola
SEAT POST	ONE1 Alloy, SP C207, 30.0mm

WHEELS

FRONT HUB	SHIMANO HB-M3050, 36H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-M3050, 36H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J19DC, 36H
SPOKES	Sapim Leader, Stainless Black

SSC 160 L

MATTE GREY



E-URBAN

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS E6100, 36V, 250W, 60Nm
BATTERY	SHIMANO STEPS, BT-E6001, 36V, 504 Wh, rear carrier mount
DISPLAY	SHIMANO SC-E5000, Clamp band

BENEFITS

- Shimano Steps E6100 motor with a power of 250 W and 60 Nm
- Fully integrated battery with the capacity of 504 Wh and the range up to 185 km*
- E-TUBE PROJECT individual setting using E-Tube Shimano application
- Seven-speed shifting in Shimano Nexus hub
- Suspension seat post, a comfortable saddle, adjustable stem
- Full touring equipment: carrier, fenders, lights, kickstand, etc.

FRAMESET

HEAD SET	FSA TH-805ST Semi-Cartrige, 1-1/8"
FORK	SR Suntour NEX-DS, 1-1/8", Coil, QR Type, 50mm travel
COLOUR	MATTE GREY
SIZES	

DRIVETRAIN

SHIFTER	SHIMANO NEXUS SL-C3000-7 Revoshift, 7-speed
CRANKSET	SHIMANO FC-E6100, 38T
CASSETTE	SHIMANO NEXUS, 18T
CHAIN	KMC Z1
PEDALS	Marwi SP-823

COMPONENTS

HANDLEBAR	ONE1 Alloy, NRAL124BT, 38° backsweep, 38mm rise, 620mm, 31.8mm
STEM	ONE1 MTS-C2695 Alloy, 31.8mm, 0°/+90°
GRIPS	HERRMANS LINE DD36AR, HERRMANS LINE DD36BL
SADDLE	Selle Royal Giara
SEAT POST	ONE1 Alloy, SP C207, 30.0mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 36H, CENTER LOCK, QR Type
REAR HUB	SHIMANO NEXUS SG-C3001-7D, 36H, CENTER LOCK, 135x187mm
RIMS	Stars J19ZK, 36H
SPOKES	Sapim Leader

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

SSC 100 L

MATTE SPARKLING GREY



E-URBAN

SPECIFICATION

E-BIKE

DRIVE UNIT	SHIMANO STEPS E5000, 36V, 250W, 40Nm
DISPLAY	SHIMANO SC-E5000, Clamp band

BENEFITS

- Shimano Steps E5000 motor with a power of 250 W and 40 Nm
- Carrier battery with the capacity of 400 Wh and the range up to 120 km*
- E-TUBE PROJECT individual setting using E-Tube Shimano application
- Seven-speed shifting in Shimano Nexus hub
- Suspension seat post, a comfortable saddle, adjustable stem
- Full touring equipment: carrier, fenders, lights, kickstand, etc.

FRAMESET

HEAD SET	FSA TH-805ST Semi-Cartrige, 1-1/8"
FORK	SR Suntour NEX-DS, 1-1/8", Coil, QR Type, 50mm travel
COLOUR	MATTE SPARKLING GREY
SIZES	

DRIVETRAIN

SHIFTER	SHIMANO NEXUS SL-C3000-7 RevoShift, 7-speed
CRANKSET	SHIMANO FC-E5000, 38T
CASSETTE	SHIMANO NEXUS, 18T
CHAIN	KMC Z1
PEDALS	Marwi SP-823

COMPONENTS

HANDLEBAR	ONE1 Alloy, NRAL124BT, 38° backsweep, 38mm rise, 620mm, 31.8mm
STEM	ONE1 MTS-C2695 Alloy, 31.8mm, 0°/+90°
GRIPS	HERRMANS LINE DD36AR, HERRMANS LINE DD36BL
SADDLE	Selle Royal Giara
SEAT POST	ONE1 Alloy, SP C207, 30.0mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 36H, CENTER LOCK, QR Type
RIMS	Stars J19ZK, 36H
SPOKES	Sapim Leader

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

SBC 400i L

GLOSS BROWN



E-URBAN

SPECIFICATION

E-BIKE

DRIVE UNIT	BOSCH ActiveLine Plus, 36V, 250W, 50Nm
BATTERY	BOSCH PowerTube 36V, 500Wh
DISPLAY	BOSCH Intuvia Anthracite , Clamp band
CHARGER	BOSCH 2A Compact charger

BENEFITS

- Powerful Bosch Active Line Plus drive unit with a power of 250 W and 50 Nm
- Integrated battery with the capacity of 500 Wh and the range up to 185 km*
- Shimano hydraulic disc brakes
- Full touring equipment: carrier, fenders, lights, kickstand, etc.

FRAMESET

HEAD SET	FSA No.10 Semi-Cartridge
FORK	SR Suntour NEX-DS, 1-1/8", Coil, QR Type, 50mm travel
COLOUR	GLOSS BROWN
SIZES	

DRIVETRAIN

CRANKSET	ONE1 EC33-BH3-F9-BNI-L/R, 38T
CASSETE	SHIMANO NEXUS, 18T
CHAIN	KMC Z1
PEDALS	Marwi SP-823

COMPONENTS

HANDLEBAR	ONE1 Alloy, NRAL124BT, 38° backsweep, 38mm rise, 620mm, 31.8mm
STEM	ONE1 TDS-C2698 Alloy, 31.8mm, 0°/+90°
GRIPS	HERRMANS LINE DD36BL, HERRMANS LINE DD36AR
SADDLE	Selle Royal Nuvola
SEAT POST	ONE1 Alloy, SP C207, 30.9mm

WHEELS

REAR HUB	SHIMANO NEXUS SG-C3001-7D, 36H, CENTER LOCK, 135x187mm
RIMS	Stars J19DC, 36H
TIRES	CST Scalato Mondano, 28x2.00", reflective tape
SPOKES	Sapim Leader, Stainless Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

SBC 200

MATTE DARK GREEN



E-URBAN

SPECIFICATION

E-BIKE

DRIVE UNIT	BOSCH ActiveLine Plus, 36V, 250W, 50Nm
DISPLAY	BOSCH Purion Anthracite , Clamp band
CHARGER	BOSCH 2A Compact charger

BENEFITS

- Powerful Bosch Active Line Plus drive unit with a power of 250 W and 50 Nm
- Carrier battery with the capacity of 500 Wh and the range up to 140 km*
- Shimano hydraulic disc brakes
- Full touring equipment: carrier, fenders, lights, kickstand, etc.

FRAMESET

HEAD SET	FSA TH-805ST Semi-Cartridge, 1-1/8"
FORK	SR Suntour NEX-DS, 1-1/8", Coil, QR Type, 50mm travel
COLOUR	MATTE DARK GREEN
SIZES	

DRIVETRAIN

SHIFTER	SHIMANO NEXUS SL-C3000-7 Revoshift, 7-speed
CRANKSET	Wheel Top ICMA-BNI-L/R, 38T
CASSETTE	SHIMANO NEXUS, 18T
CHAIN	KMC Z1
PEDALS	Marwi SP-823

COMPONENTS

HANDLEBAR	ONE1 Alloy, NRAL124BT, 38° backsweep, 38mm rise, 620mm, 31.8mm
STEM	ONE1 MTS-C2695 Alloy, 31.8mm, 0°/+90°
GRIPS	HERRMANS LINE DD36BL, HERRMANS LINE DD36AR
SADDLE	Selle Royal Giara
SEAT POST	ONE1 Alloy, SP C207, 30.0mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 36H, CENTER LOCK, QR Type
REAR HUB	SHIMANO NEXUS SG-C3001-7D, 36H, CENTER LOCK, 135x187mm
RIMS	Stars J19ZK, 36H
SPOKES	Sapim Leader, Stainless Black

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country

RX 570

BLACK/SILVER/COPPER



URBAN

BENEFITS

- Lightweight alloy frame for fast & comfortable ride
- Powerful Shimano hydraulic disc brakes
- 3x9 gears for a wide range: flat asphalt to steep off-road climbs
- Comfortable accessories: Selle Royal Rio Plus saddle, alloy seatpost and handlebars

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Gentleman, Trekking Geometry, Disc Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA No.10 Semi-Cartrige
COLOUR	BLACK/SILVER/COPPER
SIZES	

DRIVETRAIN

SHIFTER	SHIMANO ALIVIO SL-M3100-R RapidFire Plus, 9-speed
FRONT DERAILLEUR	SHIMANO ACERA FD-T3000, TOP SWING, DUAL-PULL
REAR DERAILLEUR	SHIMANO ALIVIO RD-M3100 Shadow
CRANKSET	SHIMANO FC-M371, 48-36-26T
CASSETTE	SHIMANO CS-HG200-9, 11-34T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC X9
PEDALS	Marwi SP-823

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 660mm, 31.8mm
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT200/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Rio Plus
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 36H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 36H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J19DC, 36H
TIRES	WTB Riddler Comp, 29x1.75", Reflective Stripe
SPOKES	Sapim Leader, Stainless Black

RX 530

GLOSS GREY/WHITE/ORANGE



URBAN

BENEFITS

- Lightweight alloy frame for fast & comfortable ride
- Powerful Shimano hydraulic disc brakes for safe stopping
- 3x8 gears for a wide range: flat asphalt to steep off-road climbs
- Comfortable accessories: Selle Royal Rio Plus saddle, alloy seatpost and handlebars

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Gentleman, Trekking Geometry, Disc Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA No.10 Semi-Cartrige
COLOUR	GLOSS GREY/WHITE/ORANGE
SIZES	

DRIVETRAIN

FRONT DERAILLEUR	SHIMANO TX FD-TX800-TS3, TOP SWING, DUAL-PULL
CRANKSET	Shimano FC-TY501 48/38/28T
CASSETTE	SHIMANO CS-HG31-8, 11-34T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-872N

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 660mm, 31.8mm
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO ST-EF505-8R/BR-MT200, hydraulic disc brake, SHIMANO ST-EF505/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Rio Plus
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 36H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 36H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J19DC, 36H
TIRES	WTB Riddler Comp, 29x1.75", Reflective Stripe
SPOKES	Sapim Leader, Stainless Black

RX 530 L

MATTE ANTHRACITE/SILVER/COPPER



URBAN

BENEFITS

- Lightweight alloy frame with easy-entry ladies geometry
- Powerful Shimano hydraulic disc brakes for safe stopping
- 3x8 gears for a wide range: flat asphalt to steep off-road climbs
- Comfortable accessories: Selle Royal Rio Plus saddle, alloy seatpost and handlebars

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Lady Low Entry, Trekking Geometry, Disc Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA No.10 Semi-Cartrige
COLOUR	MATTE ANTHRACITE/SILVER/COPPER
SIZES	

DRIVETRAIN

FRONT DERAILLEUR	SHIMANO TX FD-TX800-TS3, TOP SWING, DUAL-PULL
CRANKSET	Shimano FC-TY501 48/38/28T
CASSETTE	SHIMANO CS-HG31-8, 11-34T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-872N

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 660mm, 31.8mm
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO ST-EF505-8R/BR-MT200, hydraulic disc brake, SHIMANO ST-EF505/BR-MT200, hydraulic disc brake
SADDLE	Selle Royal Rio
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	SHIMANO HB-TX505, 36H, CENTER LOCK, QR Type
REAR HUB	SHIMANO FH-TX505-8, 36H, CENTER LOCK, M10x135mm, QR Type
RIMS	Stars J19DC, 36H
TIRES	WTB Riddler Comp, 29x1.75", Reflective Stripe
SPOKES	Sapim Leader, Stainless Black

RX 510

MATTE NIGHT BLUE/SILVER/NEON YELLOW



URBAN

BENEFITS

- Lightweight alloy frame with easy-entry geometry
- Powerful Shimano hydraulic disc brakes for safe stopping
- 3x7 gears for a wide range: flat asphalt to steep off-road climbs
- Comfortable accessories: Selle Royal Rio Plus saddle, alloy seatpost and handlebars

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Gentleman, Trekking Geometry, V-Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA No.10 Semi-Cartrige
COLOUR	MATTE NIGHT BLUE/SILVER/NEON YELLOW
SIZES	

DRIVETRAIN

SHIFTER	SHIMANO ALTUS ST-EF500-L EZ-Fire Plus, 3-speed, SHIMANO ALTUS ST-EF500-7R EZ-Fire Plus, 7-speed
FRONT DERAILLEUR	SHIMANO TY FD-TY510-TS3, TOP SWING, DUAL-PULL
REAR DERAILLEUR	SHIMANO ALTUS RD-M310-L
CRANKSET	Shimano FC-TY501 48/38/28T
CASSETTE	SHIMANO MF-TZ500-7, 14-28T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-872N

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 660mm, 31.8mm
GRIPS	Velo VLG-1777D2
SADDLE	Selle Royal Rio Plus
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTA56F, 36H, 3/8"26Tx100x140mm
REAR HUB	ONE1 KTA51R, 36H, M10x135, FREEWHEEL, NUT Type
RIMS	Stars J19SZ, 36H
TIRES	WTB Riddler Comp, 29x1.75", Reflective Stripe
SPOKES	Sapim Leader, Stainless Black

RX 510

MATTE ANTHRACITE/SILVER/COPPER



URBAN

BENEFITS

- Lightweight alloy frame with easy-entry geometry
- Powerful Shimano hydraulic disc brakes for safe stopping
- 3x7 gears for a wide range: flat asphalt to steep off-road climbs
- Comfortable accessories: Selle Royal Rio Plus saddle, alloy seatpost and handlebars

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Gentleman, Trekking Geometry, V-Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA No.10 Semi-Cartrige
COLOUR	MATTE ANTHRACITE/SILVER/COPPER
SIZES	

DRIVETRAIN

SHIFTER	SHIMANO ALTUS ST-EF500-L EZ-Fire Plus, 3-speed, SHIMANO ALTUS ST-EF500-7R EZ-Fire Plus, 7-speed
FRONT DERAILLEUR	SHIMANO TY FD-TY510-TS3, TOP SWING, DUAL-PULL
REAR DERAILLEUR	SHIMANO ALTUS RD-M310-L
CRANKSET	Shimano FC-TY501 48/38/28T
CASSETTE	SHIMANO MF-TZ500-7, 14-28T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-872N

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 660mm, 31.8mm
GRIPS	Velo VLG-1777D2
SADDLE	Selle Royal Rio Plus
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTA56F, 36H, 3/8"26Tx100x140mm
REAR HUB	ONE1 KTA51R, 36H, M10x135, FREEWHEEL, NUT Type
RIMS	Stars J19SZ, 36H
TIRES	WTB Riddler Comp, 29x1.75", Reflective Stripe
SPOKES	Sapim Leader, Stainless Black

RX 510 L

MATTE NIGHT BLUE/SILVER/NEON YELLOW



URBAN

BENEFITS

- Lightweight alloy frame with easy-entry ladies geometry
- Powerful Shimano hydraulic disc brakes for safe stopping
- 3x7 gears for a wide range: flat asphalt to steep off-road climbs
- Comfortable accessories: Selle Royal Rio Plus saddle, alloy seatpost and handlebars

SPECIFICATION

FRAMESET

FRAME	Alloy 6061, STK Lady Trapez, Trekking Geometry, V-Brake, Direct Attachment dropout, BSA BB
HEAD SET	FSA No.10 Semi-Cartridge
COLOUR	MATTE NIGHT BLUE/SILVER/NEON YELLOW
SIZES	

DRIVETRAIN

SHIFTER	SHIMANO ALTUS ST-EF500-L EZ-Fire Plus, 3-speed, SHIMANO ALTUS ST-EF500-7R EZ-Fire Plus, 7-speed
FRONT DERAILLEUR	SHIMANO TY FD-TY510-TS3, TOP SWING, DUAL-PULL
REAR DERAILLEUR	SHIMANO ALTUS RD-M310-L
CRANKSET	Shimano FC-TY501 48/38/28T
CASSETTE	SHIMANO MF-TZ500-7, 14-28T
BOTTOM BRACKET	SHIMANO BB-UN101 122.5mm, BSA, shell 73mm
CHAIN	KMC Z8.3
PEDALS	Marwi SP-872N

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-312BT, 9° backsweep, 12mm rise, 660mm, 31.8mm
GRIPS	Velo VLG-1777D2
SADDLE	Selle Royal Rio
SEAT POST	ONE1 Alloy, SP C207, 27.2mm

WHEELS

FRONT HUB	ONE1 KTA56F, 36H, 3/8"26Tx100x140mm
REAR HUB	ONE1 KTA51R, 36H, M10x135, FREEWHEEL, NUT Type
RIMS	Stars J19SZ, 36H
TIRES	WTB Riddler Comp, 29x1.75", Reflective Stripe
SPOKES	Sapim Leader, Stainless Black